

FBAH-B075-IAV-020

CFC, R-12, 60Hz, 1- Phase, 208/230 V



Availability : **Obsolete**

Mechanical

Unit Height (in):	13.1
Unit Length (in):	24.0
Unit Width (in):	16.9
Ship Weight (lbs):	93.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 F
Suction Connection Size (in)/Type:	5/8 F
Discharge Line Size(in):	
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	MIN
Oil Recharge Amount (oz):	24

Electrical

Max Fuse Size:	20
Min Circuit Ampacity:	12.4
Compressor:	RR81C2-IAV-100
Compressor LRA - Low:	
Compressor LRA - High:	33.5
Compressor LRA - Half winding:	
Compressor RLA:	9.0
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	0.85
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	07-Nov-2002	Return Gas Temp. (°F):	65	
Compressor:	RR81C2-IAV-100 x 1	Subcooling (°F):	5	
Performance No:	6371	Air Flow Rate (CFM)	680	
90°F Ambient Air Temperature				
<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
45	8,480	129.7	39.7	7.2