

# 3DPHR12ME-TFC

HFC, R-404A, 60Hz, 3- Phase, 208/230 V  
 Medium Temp, Low Condensing



**Production Status:** Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

## Performance

Evap(°F)/Cond(°F)	20 / 120	0 / 110
RG(°F)/Liq(°F)	65.0 / 120.0	65.0 / 110.0
Capacity (Btu/hr)	85000	60000
Power (Watts):	11000	8750
Current (Amps):	33.20	27.60
EER (Btu/Wh):	7.70	6.90
Mass Flow (lbs/hr):	1790	1140
Sound Power (dBA):	0 Avg	0 Max
Vibration (mils(peak-peak)):	0.0 Avg	0.0 Max
Record Date:	2005-10-27	

## Mechanical

Number of Cylinders:	3	Displ(in <sup>3</sup> /Rev):	26.58
Bore Size(in):	2.38	Displ(ft <sup>3</sup> /hr):	1615.11
Stroke(in):	2.00		
Overall Length (in):	25.78	Mounting Length (in):	15.00
Overall Width (in):	15.06	Mounting Width (in):	12.00
Overall Height (in):	21.31	Mounting Height (in):	22.34 *
Suction Size (in):	1 3/8 Sweat		
Discharge Size (in):	1 1/8 Sweat		
Oil Recharge (oz):	115		
Initial Oil Charge (oz):	125		
Net Weight (lbs):	385		
Internal Free Volume (in <sup>3</sup> ):			
Horse Power:	7.5		
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

## Electrical

LRA-High*:	215.0	MCC (Amps):	61.0	UL File No:	SA-2337
LRA-Half Winding:		RPM:	3500	UL File Date:	26-Jul-1985
LRA Low*:		Max Operating Current:			
RLA(=MCC/1.4;use for contactor selection):			43.6		
RLA(=MCC/1.56;use for breaker & wire size selection):			39.1		
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

## Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-404A HFC	50	3	200/220	Medium Temp, Low Condensing
R-507 HFC	50	3	200/220	Medium Temp, Low Condensing
R-407C HFC	50	3	200/220	
R-407C HFC	50	3	200/220	
R-407A HFC	50	3	200/220	
R-407A HFC	50	3	200/220	
R-407F HFC	50	3	200/220	
R-507 HFC	60	3	208/230	Medium Temp, Low Condensing
R-407C HFC	60	3	208/230	Air Conditioning
R-407C HFC	60	3	208/230	Medium Temp, Low Condensing

## Alternate Applications

<u>Refrigerant</u>	<u>Freq (Hz)</u>	<u>Phase</u>	<u>Voltage</u>	<u>Application</u>
R-407A HFC	60	3	208/230	Air Conditioning
R-407A HFC	60	3	208/230	Medium Temp, Low Condensing
R-407F HFC	60	3	208/230	