

# FBAH-B075-IAA-020

CFC, R-12, 60Hz, 1- Phase, 115 V



**Availability :**      **Obsolete**

## Mechanical

Unit Height (in):	13.1
Unit Length (in):	24.0
Unit Width (in):	16.9
Ship Weight (lbs):	89.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 F
Suction Connection Size (in)/Type:	5/8 F
Discharge Line Size(in):	
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	MIN
Oil Recharge Amount (oz):	24

## Electrical

Max Fuse Size:	30
Min Circuit Ampacity:	21.0
Compressor:	RR81C2-IAA-100
Compressor LRA - Low:	
Compressor LRA - High:	66.3
Compressor LRA - Half winding:	
Compressor RLA:	15.2
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	1.7
Fan Motor Quantity:	1

## Air - Cooled Unit Performance

Release Date:	07-Nov-2002	Return Gas Temp. (°F):	65
Compressor:	RR81C2-IAA-100    x    1	Subcooling (°F):	5
Performance No:	6371	Air Flow Rate (CFM)	680

**90°F Ambient Air Temperature**

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
45	8,480	129.7	39.7	7.2