

Gage Tubing



A-201



A-210



A-222



A-225

MODELS

Clear plastic tubing is easily inspected and is therefore best for test applications where a possibility of fluid entering the tubing exists. Rubber tubing has less tendency to kink in storage and occupies less space, thus is best for portable work. Metal Tubing is recommended for permanent installations. Double column tubing is used with Mark II manometers and the Wind Speed Indicator.

A-201, Rubber Tubing, 3/16" I.D., 9 ft length

A-202, Rubber Tubing, 3/16" I.D. length to 50 ft

A-203, PVC Tubing, 1/8" I.D. x 1/4" O. D.

A-225, Flexible Double Column Plastic tubing Lt. Gray, with red color code stripe, 1/8" I.D., lengths to 750 ft

A-210, Aluminum Tubing, 1/4" O.D., 5 ft length, 500 psi maximum pressure @ 200°F

A-211, Aluminum Tubing, 1/4" O. D., length to 50 ft, 500 psi maximum pressure @ 200°F

A-220, Flexible Vinyl Tubing, Clear 3/16" I.D. x 5/16" O.D., lengths to 500 ft, 45 psi maximum pressure @ 73°F

A-221, Flexible Vinyl Tubing, Clear 1/8" I.D. x 3/16" O.D. lengths to 500 ft, 40 psi maximum pressure @ 165°F

A-222, Flexible Vinyl Tubing, Clear .240" I.D. x .375" O.D. lengths to 500 ft, 35 psi maximum pressure @ 73°F.

A-223, Black Polyethylene 1/8" I.D. 1/4" O.D. 10 ft length, 200 psi maximum @ 140°F