



### Split Bolt Connectors\*

Made of silicone bronze. For copper use only.



CATALOG NO.	DESCRIPTION	MAX. SOLID WIRE	MAX. STRANDED WIRE	STANDARD PACK
PI328	Split Bolt Connector	6	7	3

### 6180 Series Terminal Blocks\*

Constructed of high barrier thermoplastic. Rated 20A-250V.



CATALOG NO.	NO. OF POSITIONS	LENGTH (in.)	WIDTH (in.)	SCREW SIZE	MAX. WIRE SIZE	STANDARD PACK
6183	6	2.91	.88	6-32	22-14	1
6185	10	4.41	.88	6-32	22-14	1
6187	14	5.91	.88	6-32	22-14	1

### Heat Shrink Tubing Assortments\*


Heat Shrink Tubing is made of flame-retardant polyolefin. Thin walled, all purpose tubing. Rated 600V, 125°C. 2500 volts/mil. dielectric strength. Inert to fungus. Virtually unaffected by corrosives, common fluids, and solvents. Pieces are 6" in length.



CATALOG NO.	COLOR	INNER DIAMETER		STANDARD PACK
		MAX. SUPPLIED	MIN. RECOVERED	
6370	Black & White	1/8", 1/4"	1/16", 1/8"	12

### SJTO Service Cord\*


Features stranded bare copper, PVC insulation; PVC jacket. Cord is oil resistant. Cords have 3 individually insulated conductors. Ratings: 300V; 60°C.



CATALOG NO.	DESCRIPTION	WIRE GAUGE	LENGTH	STANDARD PACK
6341	SJTO Service Cord	16	20'	20
6343	SJTO Service Cord	14	20'	20

### Pigtails

Wire is stripped 1" on one end; 10-32 x 3/8" slotted hex head grounding screw on the other.



CATALOG NO.	WIRE LENGTH	WIRE GAUGE	WIRE TYPE	STANDARD PACK
PI337-1	6-1/2"	12	Solid	5

### Armored Connector\*


Vinyl enclosed.



CATALOG NO.	FITS CORD DIAMETER	POLES	WIRES	RATING	STANDARD PACK
ED2887	.225" - .60"	2	3	15A-125V	1

### Pigtails

Wire has #10 spade on one end; 10-32 x 3/8" slotted round head screw on the other.



CATALOG NO.	WIRE LENGTH	WIRE GAUGE	WIRE TYPE	STANDARD PACK
PI337-4	8"	12	Stranded	5

### Armored Plug\*

Vinyl enclosed.



CATALOG NO.	FITS CORD DIAMETER	POLES	WIRES	RATING	STANDARD PACK
ED2867	.25" - .625"	2	3	15A-125V	1

\*Items in this section are Underwriter's Laboratories listed or recognized under the prime manufacturer's name.