

# CRNQ-050E-TFD

HCFC, R-22, 60Hz, 3- Phase, 380/460 V

Air Conditioning



**Production Status:** Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

## Performance

Evap(°F)/Cond(°F)	45 / 130	45 / 100
RG(°F)/Liq(°F)	65.0 / 115.0	65.0 / 85.0
Capacity (Btu/hr)	61500	77000
Power (Watts):	6100	4850
Current (Amps):	8.90	7.50
EER (Btu/Wh):	10.10	15.90
Mass Flow (lbs/hr):	900	995
Sound Power (dBA):	80 Avg	85 Max
Vibration (mils(peak-peak)):	5.0 Avg	6.0 Max
Record Date:	2014-03-06	

## Mechanical

Number of Cylinders:	2	Displ(in <sup>3</sup> /Rev):	6.22
Bore Size(in):	1.96	Displ(ft <sup>3</sup> /hr):	756.06
Stroke(in):	1.03		
Overall Length (in):	11.38	Mounting Length (in):	7.50
Overall Width (in):	9.38	Mounting Width (in):	7.50
Overall Height (in):	16.13	Mounting Height (in):	16.50 *
Suction Size (in):		7/8 Stub	
Discharge Size (in):		1/2 Stub	
Oil Recharge (oz):		66	
Initial Oil Charge (oz):		70	
Net Weight (lbs):		82	
Internal Free Volume (in <sup>3</sup> ):			
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

## Electrical

LRA-High*:	65.0	MCC (Amps):	13.5	UL File No:	
LRA-Half Winding:		RPM:	3500	UL File Date:	28-Dec-1984
LRA Low*:		Max Operating Current:			
RLA(=MCC/1.4;use for contactor selection):		9.6			
RLA(=MCC/1.56;use for breaker & wire size selection):		8.7			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

## Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-22 HCFC	50	3	380/420	High Temp
R-22 HCFC	50	3	380/420	Air Conditioning
R-404A HFC	50	3	380/420	High Temp
R-407C HFC	50	3	380/420	Air Conditioning
R-22 HCFC	60	3	380/460	High Temp
R-407C HFC	60	3	380/460	Air Conditioning