

ELECTRICAL PRODUCTS CATALOG



DISCONNECT SWITCHES

DiversiTech Pull-out Disconnect Switches with Side Opening Door

- Fused models designed with fuses in pull-out handle for easy replacement
- Line, load, and ground terminals aligned for ease of wiring
- Patent pending reversible door – opens to the left or to the right
- Side opening door opens more than 180 degrees for maximum access
- Fused models have indicator lights for blown fuses
- Full dead front
- UL Listed IRF9, NEMA TYPE 3R: Raintight, Sleet Resistant – Outdoor



DDS-60



CATALOG NO.	DESCRIPTION	STANDARD PACK
DDS-30	30A Fusible Disconnect Switch	10
DDS-60	60A Fusible Disconnect Switch	10
DDS-60U	60A Non-Fusible Disconnect Switch	10

A/C Pull-out Disconnect Switches with Side Opening Door

- Side hinged cover, Type 3R enclosure offers better access to interior components.
- Compact design for easy installation and low visual profile.
- Easy to install and wire – plenty of wire bending space and knockouts.
- Slot for hanging with mounting holes spaced for standard mortar joints.
- Molded interior trim – one piece design with captive screw.
- Swing down cover latch – prevents damage during shipment and installation.



755-30F



CATALOG NO.	DESCRIPTION	STANDARD PACK
755-30F	30A Fusible Pullout Disconnect Switch	10
755-60F	60A Fusible Pullout Disconnect Switch	10
755-60NF	60A Non-Fusible Pullout Disconnect Switch	10

A/C Pull-out Disconnect Switches with GFI Receptacle

The Square D combination AC Disconnect and GFI Receptacle will help you to save time and material when wiring to NEC 210.63 requirements. This all-in-one unit provides the AC disconnect and GFI receptacle in one NEMA 3R enclosure, eliminating the need for a separate box and weatherproof receptacle cover.

- Weatherproof “while-in-use” cover swings out of the way for maximum accessibility and provides a weatherproof cover for the receptacle per the requirements of NEC 406.8
- 20A GFI Receptacle is conveniently mounted to the trim for easy access to terminations
- Convenient combination knockout provisions (1/2, 3/4, 1”) on side, back and bottom enclosure walls.
- Mounting slot for pre-hanging during installation and receptacle is factory-wired to ground for faster installation.



755-60GFCI



CATALOG NO.	DESCRIPTION	STANDARD PACK
755-60GFCI	60A Non-Fusible Pullout Disconnect Switch with GFI Receptacle	10

DiversiTech Low-Profile Disconnect Switch

- Slightly smaller design than standard DiversiTech Disconnects
- Side opening door
- Full dead front
- UL Listed IRF9, NEMA TYPE 3R: Raintight, Sleet Resistant – Outdoor



EDS-60U

CATALOG NO.	DESCRIPTION	STANDARD PACK
EDS-60U	60A Non-Fusible Disconnect Switch	10

QO200TR A/C Disconnect

- 60 amp molded case switch rated for 10 HP motors at 240 VAC.
- On-Off circuit breaker type switch. No pull-out head that can be lost or stolen.
- Four, one-inch combination knockouts – two in back and two in bottom end wall.
- Removing the cover housing provides open access to lugs for easy wiring.



QO200TR



CATALOG NO.	DESCRIPTION	STANDARD PACK
QO200TR	60A Molded Case Disconnect Switch	1

Non-Metallic Disconnects

NEMA 3R rated non-metallic, pullout type, excellent for coastal environments. Single phase 240 Volts AC.



750-P30F



CATALOG NO.	DESCRIPTION	STANDARD PACK
750-P30F	Fusible 30 Amp	10
750-P60F	Fusible 60 Amp	10
750-P60NF	Non-Fusible 60 Amp	10

Three Phase Disconnects

UL listed, File E5239. Meets UL98 for enclosed switches and NEMA Std. KS-1. Suitable as service entrance equipment when applied with neutral or ground lug kit. Rainproof type 3R enclosure.



750-30F-3PH



CATALOG NO.	DESCRIPTION	STANDARD PACK
750-30F-3PH	Fusible 30 Amp	1
750-60F-3PH	Fusible 60 Amp	1
750-60NF-3PH	Non-Fusible 60 Amp	1

DIVERSIWHIPS, CONDUIT, FITTINGS, CABLE

DiversiWhips

Liquid-tight flexible conduit system. A labor saving convenience kit for A/C unit hookup. Also use for heat pumps, refrigeration, hot tubs, swimming pools and outdoor lighting. Three distinct wire colors for ease of hook-up. 1 straight and 1 90° metallic or non-metallic connector. 90° connector* is removable for straight connections. (Second straight connector not included.) U.L. & C.U.L. Listed.



CATALOG NO.	DESCRIPTION	STANDARD PACK
6-12-4	1/2 x 4' #10 THHN Wire – Metallic Connectors	6
6-12-6	1/2 x 6' #10 THHN Wire – Metallic Connectors	6
6-34-4	3/4 x 4' #8 THHN Wire – Metallic Connectors	6
6-34-6	3/4 x 6' #8 THHN Wire – Metallic Connectors	6
6-12-4NM	1/2 x 4' #10 THHN Wire – Non-Metallic Connectors	6
6-12-6NM	1/2 x 6' #10 THHN Wire – Non-Metallic Connectors	6
6-34-4NM	3/4 x 4' #8 THHN Wire – Non-Metallic Connectors	6
6-34-6NM	3/4 x 6' #8 THHN Wire – Non-Metallic Connectors	6

*For DiversiWhips produced with 2 straight connectors, add S to part number (ex: 6-12-4S).

DiversiWhips Pallet Packs

DiversiWhips are now available in a convenient, bulk-packaged pallet pack at a discounted price. Pallet pack makes an attractive floor-standing display. 1 straight and 1 90° metallic or non-metallic connector.



CATALOG NO.	DESCRIPTION	STANDARD PACK
B6-12-4	1/2 x 4' #10 THHN Wire – Metallic Connectors	90
B6-12-6	1/2 x 6' #10 THHN Wire – Metallic Connectors	60
B6-34-4	3/4 x 4' #8 THHN Wire – Metallic Connectors	60
B6-34-6	3/4 x 6' #8 THHN Wire – Metallic Connectors	45
B6-12-4NM	1/2 x 4' #10 THHN Wire – Non-Metallic Connectors	90
B6-12-6NM	1/2 x 6' #10 THHN Wire – Non-Metallic Connectors	60
B6-34-4NM	3/4 x 4' #8 THHN Wire – Non-Metallic Connectors	60
B6-34-6NM	3/4 x 6' #8 THHN Wire – Non-Metallic Connectors	45

Liquid Tite Flexible Conduit

Specifically for electrical applications. For outside, inside and industrial uses including transformer connections, air conditioning and heating. Joins with metallic or non-metallic connectors, easy to cut. Conduit is impact resistant, chemical resistant and will not kink. U.L. and C.U.L. Listed. For use as indicated in Article 351 of the 1987 NEC.



CATALOG NO.	DESCRIPTION	STANDARD PACK
750-12100	1/2" x 100' Liquid Tite Conduit – Non-Metallic	100' Roll
750-34100	3/4" x 100' Liquid Tite Conduit – Non-Metallic	100' Roll
750-10100	1" x 100' Liquid Tite Conduit – Non-Metallic	100' Roll
750-500	1/2" x 100' Liquid Tite Conduit – Metallic	100' Roll
750-600	3/4" x 100' Liquid Tite Conduit – Metallic	100' Roll

Liquid Tite Connectors

For use with metallic and non-metallic liquid tite conduit, Type B. Provides smooth connection, no sharp edges to strip wire. Wiring easily pulled through. U. L. Listed. C.U.L. Listed.



CATALOG NO.	DESCRIPTION	STANDARD PACK
750-NMLT100	1" Non-Metallic Straight Connector	25
750-NMLT90100	1" Non-Metallic 90 Degree Elbow	25
750-NMLT75	3/4" Non-Metallic Straight Connector	10
750-NMLT4575	3/4" Non-Metallic 45 Degree Elbow Connector	10
750-NMLT9075	3/4" Non-Metallic 90 Degree Elbow Connector	10
750-NMLT50	1/2" Non-Metallic Straight Connector	25
750-NMLT4550	1/2" Non-Metallic 45 Degree Elbow Connector	10
750-NMLT9050	1/2" Non-Metallic 90 Degree Elbow Connector	10
750-MLT4550	1/2" Metallic 45 Degree Elbow Connector	10
750-MLT4575	3/4" Metallic 45 Degree Elbow Connector	10
750-MLT50	1/2" Metallic Straight Connector	25
750-MLT75	3/4" Metallic Straight Connector	10
750-MLT9050	1/2" Metallic 90 Degree Elbow	10
750-MLT9075	3/4" Metallic 90 Degree Elbow	10

Screw-On Liquid Tite Fittings

Conduit threads onto ferrule and up inside the outer body. An inside taper squeezes down on the outside of conduit for a superior liquid tight seal. The cut portion of the conduit does not show, giving a more finished appearance. Easy to use at a lower cost than regular liquid tite fittings.



CATALOG NO.	DESCRIPTION	STANDARD PACK
750-SLTC50	1/2" Straight Screw-On Fitting	25
750-SLTC75	3/4" Straight Screw-On Fitting	25
750-SLTC9050	1/2" 90° Screw-On Fitting	25
750-SLTC9075	3/4" 90° Screw-On Fitting	25

Aluminum Armored MC Cable

90°, C Rated aluminum metal clad cable system. THHN solid copper with specially compounded heat-resistant U.L. Listed insulation and jacket. Flexible interlocked aluminum armor. Extremely durable – withstands severe handling. U.L. Listed #4. Conforms to NEC article 333.



CATALOG NO.	DESCRIPTION	STANDARD PACK
640-122	12-2 Aluminum Armored MC Cable – 100' Roll	1
640-142	14-2 Aluminum Armored MC Cable – 100' Roll	1

CONTACTORS

DiversiTech Definite Purpose Contactors

Two pole, small frame.



CATALOG NO.	FL AMPS	COIL VAC	STANDARD PACK
EC30224	30	24	1
EC302120	30	120	1
EC302240	30	240	1
EC40224	40	24	1
EC402120	40	120	1
EC402240	40	240	1

DiversiTech Three Pole DP Contactors

Three pole, large frame.



CATALOG NO.	FL AMPS	COIL VAC	STANDARD PACK
EC30324	30	24	1
EC303120	30	120	1
EC303240	30	240	1
EC40324	40	24	1
EC403120	40	120	1
EC403240	40	240	1

Definite Purpose Contactors


Single pole, small frame.



CATALOG NO.	FL AMPS	COIL VAC	STANDARD PACK
DP30124	30	24	1
DP301120	30	120	1
DP301240	30	240	1

Definite Purpose Contactors

Two pole, small frame.



CATALOG NO.	FL AMPS	COIL VAC	STANDARD PACK
DP25224	25	24	1
DP252120	25	120	1
DP252240	25	240	1
DP30224	30	24	1
DP302120	30	120	1
DP302240	30	240	1
DP40224	40	24	1
DP402120	40	120	1
DP402240	40	240	1

Definite Purpose Contactors

Three pole, large frame.



CATALOG NO.	FL AMPS	COIL VAC	STANDARD PACK
DP30324	30	24	1
DP303120	30	120	1
DP303240	30	240	1
DP40324	40	24	1
DP403120	40	120	1
DP403240	40	240	1
DP50324	50	24	1
DP503120	50	120	1
DP503240	50	240	1
DP60324	60	24	1
DP603120	60	120	1
DP603240	60	240	1
DP75324	75	24	1
DP753120	75	120	1
DP753240	75	240	1
DP90324	90	24	1
DP903120	90	120	1
DP903240	90	240	1

CONTACTORS cont'd

Contactor Accessories

Auxiliary contacts and replacement coils.



CATALOG NO.	CONTACTOR FRAME SIZE	VOLTAGE	STANDARD PACK
DA1V14	20-40 Amp	24	1
DA1V02	20-40 Amp	120	1
DA1V09	20-40 Amp	240	1
DA1V06	20-40 Amp	480	1
DA2V14	50-60 Amp	24	1
DA2V02	50-60 Amp	120	1
DA2V09	50-60 Amp	240	1
DA2V06	50-60 Amp	480	1
DA3V14	75-90 Amp	24	1
DA3V02	75-90 Amp	120	1
DA3V09	75-90 Amp	240	1
DA3V06	75-90 Amp	480	1

Contactor Accessories

Auxiliary contacts are designed for 20 Amp to 90 Amp 3-pole contactors. You may use 2/contactor.



CATALOG NO.	CONTACTOR FRAME SIZE	VOLTAGE	STANDARD PACK
D10	1-N.O.	20-90	1
D11	1-N.O. 1-N.C.	20-90	1

CAPACITORS

Motor Run Capacitors – 370 VAC

Single capacitance. Oval shape, metal can.



CATALOG NO.	uf	CAN HT. INCHES	STANDARD PACK
37020H	2	2.17	1
37030H	3	2.17	1
37040H	4	2.17	1
37050H	5	2.17	1
37050HB	5	2.17	100 (bulk)
37060H	6	2.63	1
37075H	7.5	2.17	1
37075HB	7.5	2.17	100 (bulk)
37100H	10	2.56	1
37100HB	10	2.56	100 (bulk)
37125H	12.5	2.95	1
37150H	15	2.95	1
37175H	17.5	3.35	1
37200H	20	2.56	1
37250H	25	2.95	1
37300H	30	3.35	1
37350H	35	3.35	1
37400H	40	3.94	1
37450H	45	3.94	1
37500H	50	4.53	1
37600H	60	4.75	1
37700H	70	4.75	1
37800H	80	4.53	1

Motor Run Capacitors – 370 VAC

Dual capacitance. Oval shape, metal can.



CATALOG NO.	uf	CAN HT. INCHES	STANDARD PACK
3GJ0515	15+5	2.63	1
3GJ1015	15+10	3.00	1
3GJ0520	20+5	2.63	1
3GJ1520	20+15	4.75	1
3GJ0525	25+5	3.35	1
3GJ1025	25+10	3.75	1
3GJ0530	30+5	3.94	1
3GJ7530	30+7.5	3.00	1
3GJ0535	35+5	3.94	1
3GJ7535	35+7.5	3.00	1
3GJ0540	40+5	3.94	1
3GJ0545	45+5	3.74	1
3GJ7555	55+7.5	4.75	1
3GJ1060	60+10	4.75	1

Motor Run Capacitors – 370 VAC

Dual capacitance. Round shape, metal can.



CATALOG NO.	uf	CAN HT. INCHES	STANDARD PACK
3GR0425	25+4	3.13	1
3GR0525	25+5	3.54	1
3GR0530	30+5	3.54	1
3GR7530	30+7.5	3.88	1
3GR0435	35+4	3.88	1
3GR0535	35+5	3.74	1
3GR7540	40+7.5	3.88	1
3GR0545	45+5	4.25	1
3GR0550	50+5	3.88	1
3GR0555	55+5	3.88	1
3GR7555	55+7.5	3.88	1
3GR0560	60+5	3.88	1
3GR7560	60+7.5	3.88	1
3GR0580	80+5	5.96	1
3GR7580	80+7.5	3.88	1

Motor Run Capacitors – 370 VAC

Single capacitance. Round shape, metal can.



CATALOG NO.	uf	CAN HT. INCHES	STANDARD PACK
37050R	5	2.63	1
37075R	7.5	2.63	1
37100R	10	2.63	1
37125R	12.5	3.00	1
37250R	25	2.95	1
37300R	30	3.00	1
37350R	35	3.35	1
37400R	40	3.75	1
37450R	45	3.75	1
37500R	50	3.75	1
37550R	55	3.75	1
37600R	60	3.75	1
37800R	80	4.75	1

Motor Run Capacitors – 440 VAC

Single capacitance. Oval shape, metal can.



CATALOG NO.	uf	CAN HT. INCHES	STANDARD PACK
45020H	2	2.63	1
45030H	3	2.17	1
45040H	4	2.17	1
45050H	5	2.17	1
45060H	6	2.63	1
45075H	7.5	2.17	1
45100H	10	2.56	1
45125H	12.5	2.95	1
45150H	15	2.95	1
45175H	17.5	2.63	1
45200H	20	2.56	1
45250H	25	2.95	1
45300H	30	3.35	1
45350H	35	3.35	1
45400H	40	3.94	1
45450H	45	3.94	1
45500H	50	4.53	1
45550H	55	4.53	1
45600H	60	5.31	1
45700H	70	3.75	1
45800H	80	4.75	1

Motor Run Capacitors – 440 VAC

Dual capacitance. Oval shape, metal can.



CATALOG NO.	uf	CAN HT. INCHES	STANDARD PACK
4JJ0525	25+5	3.35	1
4JJ0530	30+5	3.94	1
4JJ0535	35+5	3.94	1
4JJ0540	40+5	3.94	1
4JJ0545	45+5	4.53	1
4JJ0555	55+5	4.75	1
4JJ7535	35+7.5	3.94	1
4JJ7540	40+7.5	4.75	1
4JJ7545	45+7.5	4.75	1
4JJ1055	55+10	4.75	1

Motor Run Capacitors – 440 VAC

Dual capacitance. Round shape, metal can.



CATALOG NO.	uf	CAN HT. INCHES	STANDARD PACK
4JR0525	25+5	3.54	1
4JR7525	25+7.5	3.88	1
4JR0530	30+5	3.54	1
4JR7530	30+7.5	4.13	1
4JR0535	35+5	3.74	1
4JR7535	35+7.5	3.54	1
4JR0540	40+5	3.54	1
4JR7540	40+7.5	3.88	1
4JR0545	45+5	3.74	1
4JR7545	45+7.5	3.88	1
4JR7550	50+7.5	3.88	1
4JR0555	55+5	4.92	1
4JR7555	55+7.5	3.88	1
4JR7560	60+7.5	4.75	1

Motor Run Capacitors – 440 VAC

Single capacitance. Round shape, metal can.



CATALOG NO.	uf	CAN HT. INCHES	STANDARD PACK
45150R	15	2.56	1
45200R	20	2.95	1
45250R	25	2.95	1
45300R	30	3.75	1
45350R	35	3.94	1
45400R	40	3.94	1
45450R	45	4.53	1
45500R	50	4.92	1
45550R	55	3.75	1
45600R	60	4.53	1
45800R	80	4.75	1

Motor Run Capacitors – 440 VAC

Single capacitance. Oval shape, metal can.



CATALOG NO.	uf	CAN HT. INCHES	STANDARD PACK
45020H	2	2.63	1
45030H	3	2.17	1
45040H	4	2.17	1
45050H	5	2.17	1
45060H	6	2.63	1
45075H	7.5	2.17	1
45100H	10	2.56	1
45125H	12.5	2.95	1
45150H	15	2.95	1
45175H	17.5	2.63	1
45200H	20	2.56	1
45250H	25	2.95	1
45300H	30	3.35	1
45350H	35	3.35	1
45400H	40	3.94	1
45450H	45	3.94	1
45500H	50	4.53	1
45550H	55	4.53	1
45600H	60	5.31	1
45700H	70	3.75	1
45800H	80	4.75	1

Motor Start Capacitors – 110/125 VAC

Variable capacitance. Round shape, plastic can.



CATALOG NO.	uf	CASE DIAMETER	CAN HT. INCHES	STANDARD PACK
56-72	56-72	1-7/16"	2.75	1
88-108	88-108	1-7/16"	2.75	1
108-130	108-130	1-7/16"	2.75	1
124-156	124-156	1-7/16"	2.75	1
145-175	145-175	1-7/16"	2.75	1
161-193	161-193	1-7/16"	2.75	1
189-227	189-227	1-7/16"	2.75	1
200-240	200-240	1-7/16"	2.75	1
216-259	216-259	1-7/16"	2.75	1
233-292	233-292	1-7/16"	2.75	1
270-324	270-324	1-7/16"	2.75	1
324-388	324-388	1-13/16"	2.75	1
340-408	340-408	1-13/16"	3.37	1
378-440	378-440	1-13/16"	3.37	1
400-480	400-480	1-13/16"	3.37	1
460-552	460-552	1-13/16"	3.37	1
540-648	540-648	1-13/16"	3.37	1
590-708	590-708	1-13/16"	3.37	1
708-850	708-850	1-13/16"	3.37	1
829-995	829-995	1-13/16"	4.37	1
1000-1200	1000-1200	1-13/16"	4.37	1

CAPACITORS cont'd

Motor Start Capacitors – 220/250 VAC

Variable capacitance. Round shape, plastic can.



CATALOG NO.	uf	CASE DIAMETER	CAN HT. INCHES	STANDARD PACK
88-108220	88-108	1-13/16"	3.37	1
108-130220	108-130	1-13/16"	3.37	1
124-156220	124-156	1-13/16"	3.37	1
145-175220	145-175	2-1/16"	3.37	1
161-193220	161-193	1-13/16"	4.37	1
189-227220	189-227	2-1/16"	4.37	1
216-259220	216-259	2-1/16"	4.37	1
233-292220	233-292	2-1/16"	4.37	1
270-324220	270-324	2-1/16"	4.37	1

Motor Start Capacitors – 330 VAC

Variable capacitance. Round shape, plastic can.



CATALOG NO.	uf	CASE DIAMETER	CAN HT. INCHES	STANDARD PACK
88-108330	88-108	2-1/16"	3.37	1
108-130330	108-130	2-1/16"	4.37	1
124-156330	124-156	2-1/16"	4.37	1
145-175330	145-175	2-9/16"	4.37	1
161-193330	161-193	2-9/16"	4.37	1
189-227330	189-227	2-9/16"	4.37	1
216-259330	216-259	2-9/16"	4.37	1
270-324330	270-324	2-1/16"	4.37	1

TRANSFORMERS

Transformers – Class 2 1585 UL Recognized – Open Enclosure



CATALOG NO.	VA	PRI	SEC
T1401	40	120	24
T1403	40	208/240	24
T1404	40	120/208/240	24


Transformers – Class 2 1585 UL Recognized

Multi-mount with terminal connection secondary.



CATALOG NO.	VA	PRI	SEC
T3401	40	120	24
T3402	40	208/240	24
T3403	40	120/208/240	24
T3501	50	120/208/240	24

Transformers – Class 2 1585 UL Recognized – Foot Mount



CATALOG NO.	VA	PRI	SEC
T2401	40	120	24
T2402	40	277	24
T2403	40	208/240	24
T2404	40	120/208/240	24

Transformers – Class 2 1585 UL Recognized

Plate-mount with terminal connection.



CATALOG NO.	VA	PRI	SEC
T4401	40	120	24
T4403	40	120/208/240	24
T4501	50	120/208/240	24

TRANSFORMERS cont'd

Transformers – Class 2 1585 UL Recognized

Multi-mount with wire connection secondary.



CATALOG NO.	VA	PRI	SEC
T5401	40	120	24
T5402	40	208/240	24
T5403	50	120/208/240	24
T5404	50	120/208/240	24/12/2.5

Transformers – Class 2 1585 UL Recognized

Heavy duty with external fuse (T67XX) or circuit breaker (T77XX).



CATALOG NO.	VA	PRI	SEC
T6751	75	480	24
T6752	75	120/208/240	24
T6753	75	120/208/240/480	24
T7751	75	120/208/240	24
T7752	75	120/208/240/480	24

DRYER DUCT, VENT HOSE, HOSE CLAMPS

SUppurr-FLEX 5 Ply Duct

Pure aluminum 5 ply multi-layered flexible metallic duct. U.L. 181 Listed. Will "contain" a fire up to 265°F.



FUL0425

CATALOG NO.	DESCRIPTION	STANDARD PACK
FUL0425	4" x 25' SUppurr-FLEX	1
FUL0625	6" x 25' SUppurr-FLEX	1

Dryer Vent Hose

High quality flexible white vinyl tubing. Available in 3" or 4" diameters. One 50' roll per box.



650-005

CATALOG NO.	DESCRIPTION	STANDARD PACK
650-005	Dryer Vent Hose – 3" x 50'	1
650-006	Dryer Vent Hose – 4" x 50'	1

Metallic Duct – 2 Ply

2 ply metallic duct – aluminum outside, polyester inside. Ideal for bath fan ducting and all purpose venting.



FM0450

CATALOG NO.	DESCRIPTION	STANDARD PACK
FM0450	4" x 50' Metallic Duct	1

Dryer Hose Clamps

Available for 3" or 4" dryer vent hose. Steel screw design or convenient spring action design.



650-008

CATALOG NO.	DESCRIPTION	STANDARD PACK
650-008	Steel Screw Clamp for 4" Hose	25
650-010	Spring Clamp for 4" Hose	100

Semi-Rigid (Flexible) Aluminum Duct

8' length compressed to 28".




650-011

CATALOG NO.	DESCRIPTION	STANDARD PACK
650-011	4" x 8' Flexible Aluminum Duct	9
650-021	3" x 8' Flexible Aluminum Duct	16

Aluminum Dryer Vent Hoods, Kits, and Fittings

Aluminum vent hood with flange plate. Kits include flexible tubing and two clamps.



CATALOG NO.	DESCRIPTION	STANDARD PACK
650-001	4" Aluminum Hood	24
650-002	3" Aluminum Hood	24
650-003	4" Hood / 8' Tubing	24
650-004	4" Hood / 5' Tubing	24
650-018	4" 90° Elbow	24
650-038	4" Wide Mouth Aluminum Dryer Vent Hood Only	12

DRYER DUCT, VENT HOSE, HOSE CLAMPS cont'd

Louvered Dryer Vent Hood

Deflecto's SUppurr-Vent louvered vent hoods are available with aluminum pipe and collar or hood only. Ideal for dryer and bathroom fan exhausts.



650-014

CATALOG NO.	DESCRIPTION	STANDARD PACK
650-014	4" Hood Only - White	48
650-015	4" Hood Only w/Bird Guard - White	24
650-016	4" Hood, Pipe and Collar - White (Assembled)	6
650-017	4" Hood, Pipe and Collar - White (Unassembled)	6
650-036	3" Hood, Pipe and Collar - White (Assembled)	6

Plastic Wide Mouth Dryer Vent Hood

4" White Hood, aluminum pipe and collar.



650-012

CATALOG NO.	DESCRIPTION	STANDARD PACK
650-012	4" White Hood - Assembled	6
650-013	4" White Hood - Unassembled	6

SHEET METAL SCREWS

Sheet Metal Screws - Taper Point

Hex washer slotted head. Burr-free. Full 1/4" head will not strip out of hex driver opening. Heat treated tapered point will not break or "walk". Packaged in resealable plastic cartons.




5-SCR63-8

5-SCR101

CATALOG NO.	DESCRIPTION	STANDARD PACK
5-SCR63-8	6 x 3/8 Taper Point	1,000
5-SCR63-8BULK	6 x 3/8 Taper Point - Bulk	20,000
5-SCR71-2	7 x 1/2 Taper Point	1,000
5-SCR71-2BULK	7 x 1/2 Taper Point - Bulk	15,000
5-SCR81-2	8 x 1/2 Taper Point	1,000
5-SCR81-2BULK	8 x 1/2 Taper Point - Bulk	12,000
5-SCR83-4	8 x 3/4 Taper Point	1,000
5-SCR83-4BULK	8 x 3/4 Taper Point - Bulk	10,000
5-SCR81	8 x 1 Taper Point	500
5-SCR81BULK	8 x 1 Taper Point - Bulk	7,500
5-SCR81-12	8 x 1-1/2 Taper Point	250
5-SCR81-12W	8 x 1-1/2 Taper Point w/White Head	250
5-SCR81-12BULK	8 x 1-1/2 Taper Point - Bulk	5,000
5-SCR82	8 x 2 Taper Point	350
5-SCR82W	8 x 2 Taper Point w/White Head	250
5-SCR82BULK	8 x 2 Taper Point - Bulk	3,000
5-SCR101-2	10 x 1/2 Taper Point	1,000
5-SCR101-2BULK	10 x 1/2 Taper Point - Bulk	14,000
5-SCR103-4	10 x 3/4 Taper Point	1,000
5-SCR103-4BULK	10 x 3/4 Taper Point - Bulk	10,000
5-SCR101	10 x 1 Taper Point	500
5-SCR101BULK	10 x 1 Taper Point - Bulk	5,000

Masonry Screw



5-SCRMS

CATALOG NO.	DESCRIPTION	STANDARD PACK
5-SCRMS	Masonry Screw - 1/4" x 1-1/4"	250

Masonry Bit



540-DB6

CATALOG NO.	DESCRIPTION	STANDARD PACK
540-DB6	Masonry Bit - 3/16" x 6"	1

Sheet Metal Screw Assortment Kit

The 7 most popular sizes in one multi-compartmented, resealable, plastic container. Perfect for the toolbox. Contains:

- 7x1/2 Taper Point - 175 pieces
- 8x1/2 Drill Point - 100 pieces
- 8x1 Taper Point - 50 pieces
- 8x2 Taper Point - 40 pieces
- 8x1/2 Taper Point - 175 pieces
- 8x3/4 Taper Point - 60 pieces
- 8x1-1/2 Taper Point - 50 pieces
- 1/4" Nut Setter - 1 each



5-SCR-AK

CATALOG NO.	DESCRIPTION	STANDARD PACK
5-SCR-AK	Sheet Metal Screw Assortment Pack	1

Anchor Kit

Plastic anchor kit for sheet rock applications. Kit includes 100 anchors, screws and 1 masonry bit.



540-AK100

CATALOG NO.	DESCRIPTION	STANDARD PACK
540-AK100	Anchor size 1/4 x 1, Screw Size 10 x 1-1/4 HWH Head Size 5/16 hex	100/box

NUT SETTERS

Nut Setter – Power

Magnetic hex drive nut setter to be used with any 1/4" power bit. Individually packed.



CATALOG NO.	DESCRIPTION	STANDARD PACK
5-MSH1/4MC	Hex Drive – 1/4", 1-3/4" long, 1/4" nut	30/Box
5-MSH5/16MC	Hex Drive – 1/4", 1-3/4" long, 5/16" nut	30/Box

Nut Setters – Bulk



CATALOG NO.	DESCRIPTION	STANDARD PACK
540-500	Nut Setters – 5/16"	30
540-400	Nut Setters – 1/4"	30

CHANNEL LOCK® PRODUCTS

Tongue and Groove Pliers

Patented design, permalock fasteners and reinforcing edge. Dipped plastic comfort grips.



CATALOG NO.	DESCRIPTION	STANDARD PACK
545-420	9-1/2" Tongue and Groove Pliers	1
545-422	9-1/2" Curved Jaw Tongue and Groove Pliers	1
545-424	4-1/2" Tongue and Groove Pliers	1
545-426	6-1/2" Tongue and Groove Pliers	1
545-430	10" Tongue and Groove Pliers	1
545-440	12" Tongue and Groove Pliers	1
545-442	12" Curved Jaw Tongue and Groove Pliers	1
545-460	16" Tongue and Groove Pliers	1

MIDWEST® SNIPS, NOTCHERS, CRIMPERS, SEAMERS

Aviation Snips

Moly alloy tool steel blade is hot drop-forged and scientifically heat-treated to provide a strong, longer lasting cutting edge. Durable serrated blades are designed to grip the metal for cutting ease. The patent pending spring on these snips is guaranteed to last for the life of the tool. Will cut 18 gauge cold-rolled steel.



CATALOG NO.	DESCRIPTION	STANDARD PACK
540-6716S	Aviation Snip – Cuts Straight – Yellow Handle	6
540-6716L	Aviation Snip – Cuts Left – Red Handle	6
540-6716R	Aviation Snip – Cuts Right – Green Handle	6
540-6716B	Aviation Snip – Bulldog Notching Snip – Yellow Handle	6

Offset Snips

The same high quality construction as the Aviation Snips with an additional advantage – the Offset Snips allow your hand to stay above metal for cutting ease and comfort.



CATALOG NO.	DESCRIPTION	STANDARD PACK
540-6510L	Offset Snip – Cuts Left – Red Handle	6
540-6510R	Offset Snip – Cuts Right – Green Handle	6

Upright Snips

This snip significantly improves sheet metal cutting. The ergonomic design allows for easier cutting in tight places, improved safety by elevating hands above metal working surfaces, and increases wrist range motion.



CATALOG NO.	DESCRIPTION	STANDARD PACK
540-6900L	Upright Snips – Left-handed Model	6
540-6900R	Upright Snips – Right-handed Model	6

MIDWEST® SNIPS, NOTCHERS, CRIMPERS, SEAMERS cont'd

Tinner Snips

Constructed of the finest quality high carbon tool steel. Hot drop-forged and heat-treated to assure strength and durability. "Kush-N-Cote" vinyl coated handles for added comfort. Available in a Straight Pattern for a powerful straight cutting snip or Duckbill Pattern for cutting scrolls, circles, or straight lines. 12-1/2" long.



CATALOG NO.	DESCRIPTION	STANDARD PACK
540-P127S	Straight Cutting Tinner Snip	6
540-P127D	Duckbill Tinner Snip	6

COMBINATION SCREWDRIVERS

Combination Screwdriver

Multiple bits in one handy screwdriver. No need for a toolbox for those quick jobs. Lifetime guarantee.



CATALOG NO.	DESCRIPTION	STANDARD PACK
5-41	4-in-1 with #1 and #2 Phillips, 3/16 and 5/16 Slotted	12
5-61	6-in-1 with #1 and #2 Phillips, 3/16 and 5/16 Slotted, 1/4 Nut Driver, 5/16 Nut Driver	12

TUBE AND HOSE CUTTERS

Kut-All Plastic Tube and Hose Cutter

Tough, durable nylon. Blade closes into its own handle for safe handling. Replaceable high carbon, teflon coated steel blades. Ideal for cutting up to 1-1/8" I.D. plastic tubing, reinforced plastic tubing, rigid plastic pipe, and rubber hose.



CATALOG NO.	DESCRIPTION	STANDARD PACK
PK-2	Kut-All Plastic Tube and Hose Cutter	1
PK-2B	Replacement Blades	1

Little Helper™ - All Purpose Cutter

Cuts up to 1-1/4" polyethylene, thinwall PVC, ABS, rubber hose, NM conduit and clear vinyl tubing. Reversible stainless steel blade, like two blades in one. Sturdy all metal construction.



CATALOG NO.	DESCRIPTION	STANDARD PACK
548-001	Little Helper™ - Carded	1
548-002	Replacement Blades	1

Big Helper™ PVC Pipe Cutter

Ratchet style pipe cutters cut up to 2-1/2" Sch. 40 PVC Pipe. Ratchet action requires minimal pressure to easily cut through PVC pipe. Molybdenum stainless steel blade won't rust or break and lasts twice as long as most competitor's. The Mega-Cutter is now available - the strongest pipe cutter on the market today!



CATALOG NO.	DESCRIPTION	STANDARD PACK
548-003	1" O.D. Cutting Capacity	1
548-004	1" Replacement Blade	1
548-005	1-1/4" O.D. Cutting Capacity	1
548-006	1-1/4" Replacement Blade	1
548-009	1-5/8" O.D. Cutting Capacity	1
548-010	1-5/8" Replacement Blade	1
548-007	2-1/2" O.D. Mega-Cutter	1
548-008	2-1/2" Mega-Blade	1

SAWS AND SAW BLADES

Deluxe Hi-Tension Hacksaw

Hackframe featuring handle and end pieces made of die cast aluminum. Lightweight yet rigid and highly tensioned (up to 25,000 psi) for cleaner, surer cut. Permanent blade pins feature versatile angling (up to 55°) for flush cutting. Blade can be inserted in handle to be used as compass saw. Frame will fit most standard tool boxes.



CATALOG NO.	DESCRIPTION	STANDARD PACK
540-278HX0002	Hacksaw Frame with Blade	1
540-278BM0024	Replacement Blades for Hacksaw Frame 12" x 24T	1

Bi-Metal Reciprocating Saw Blades

Premium high speed steel with a flexible alloy back. Bi-metal blades fit all reciprocating saws with 1/2" shank.



CATALOG NO.	DESCRIPTION	STANDARD PACK
540-RB636W	6" x 6T Wood and Nail Slope 3/4" x 6" x .050	5
540-RB656WS	6" x 6T Wood and Nail Scroll 3/4" x 6" x .050	5
540-RB956W	9" x 6T Wood and Nail 3/4" x 9" x .050	5
540-RB125W	12" x 6T Wood and Nail 3/4" x 12" x .050	5
540-RB414M	4" x 14T Short Metal Cutting 3/4" x 4" x .035	5
540-RB418M	4" x 18T Short Metal Cutting 5/8" x 4" x .035	5
540-RB424M	4" x 24T Thin Short Metal Cutting 5/8" x 4" x .035	5
540-RB610HDM	6" x 10T HD Metal Cutting 3/4" x 6" x .035	5
540-RB614HDM	6" x 14T HD Metal Cutting 3/4" x 6" x .035	5
540-RB618HDM	6" x 18T HD Metal Cutting 3/4" x 6" x .035	5
540-RB624HDM	6" x 24T HD Metal Cutting 3/4" x 6" x .035	5
540-RB810HDM	8" x 10T HD Metal Cutting 3/4" x 8" x .035	5
540-RB814HDM	8" x 14T HD Metal Cutting 3/4" x 8" x .035	5
540-RB636DW	Drywall Cutting with V Head 5/8" x 6" x .035	5
540-R8CCRF	Cast Iron-Ceramic Tile Carbide Grit 8" Long	1

MEASURING TAPES, STAPLES AND STAPLE GUNS

Power Measuring Tapes


Rust resistant yellow lacquered blade with easy to read inch/foot markings (English). Both chrome and neon case have belt clips and finger-tip blade lock. Ultralife tape is our highest quality tape measure – lasts up to 10 times longer than typical blades, with patented "blade wiper" that cleans the blade as you measure.



CATALOG NO.	DESCRIPTION	STANDARD PACK
540-12	Power Tape – Chrome 1/2" x 12'	6
540-16	Power Tape – Chrome 3/4" x 16'	6
540-25	Power Tape – Chrome 1" x 25'	6
540-25R	Power Tape – Neon Orange 1" x 25'	6
540-25G	Power Tape – Neon Green 1" x 25'	6
540-25UL	Power Tape – Ultralife 1" x 25' with Yellow Case	6

T-50 Series Staples and Staple Guns

The #1 selling staple gun in the world! Used extensively by building contractors, home do-it-yourselfers and specialty trade applications for tacking insulation, ceiling tile, window screening, cornerite, and 1001 other jobs ranging from light to heavy duty work. The T-50 Outward Clinch Staple Gun is ideal for fiberglass ductwork.



CATALOG NO.	DESCRIPTION	STANDARD PACK
540-T50M	T50M Heavy Duty Staple Gun Tacker	1
540-T50MOC	T50MOC Outward Clinch Staple Gun	1
540-504	1/4" Leg Staples for T50 Staple Guns (1250/PK)	4
540-506	3/8" Leg Staples for T50 Staple Guns (1250/PK)	4
540-508	1/2" Leg Staples for T50 Staple Guns (1250/PK)	4
540-509	9/16" Leg Staples for T50 Staple Guns (1250/PK)	4

ROBERTSHAW THERMOSTATS

9400 Series Digital Non-Programmable Thermostat

- 1 Heat/1 Cool
- Large Back-lit Display
- Winter and Summer Setpoint Memory
- 24V Heating & Cooling System Compatibility
- Compressor Short Cycle Protection



675-9400

CATALOG NO.	DESCRIPTION	STANDARD PACK
675-9400	Digital Non-Programmable Thermostat	1

9420 Series Digital Non-Programmable Thermostat

- 2 Heat/2 Cool
- Large Back-lit Display
- Winter and Summer Setpoint Memory
- 24V Heating & Cooling System Compatibility
- Adjustable 1st and 2nd Stage Differential



675-9420

CATALOG NO.	DESCRIPTION	STANDARD PACK
675-9420	2 Heat/2 Cool Heat Pump Thermostat	1

9500 Series Digital Non-Programmable Thermostat

- 1 Heat/1 Cool
- Compatible with all standard 24 VAC heating and cooling systems
- O & B Terminals
- Automatic Compressor Short Cycle Protection



675-9500

CATALOG NO.	DESCRIPTION	STANDARD PACK
675-9500	1 Heat/1 Cool Digital Thermostat	1

9505 Series Digital Non-Programmable Thermostat

- 1 Heat
- Compatible with all standard 24 VAC or millivolt heating systems
- Positive Off Switch



675-9505

CATALOG NO.	DESCRIPTION	STANDARD PACK
675-9505	1 Heat Digital Thermostat	1

9515 Series Digital Non-Programmable Thermostat

- 2 Heat/2 Cool
- Compatible with all standard 24 VAC multi-stage heating & cooling systems
- O & B Terminals
- Automatic Compressor Short Cycle Protection
- Worry-Free Memory Storage
- Adjustable 1st and 2nd Stage Differential



675-9515

CATALOG NO.	DESCRIPTION	STANDARD PACK
675-9515	2 Heat/2 Cool Digital Thermostat	1

9520 Series Digital Non-Programmable Thermostat

- 2 Heat/2 Cool
- Compatible with all Standard 24 VAC Heat Pump Systems
- O & B Terminals
- Automatic Compressor Short Cycle Protection
- Lighted System Status Indicators
- Worry Free Memory Storage
- Adjustable 1st and 2nd stage differential



675-9520

CATALOG NO.	DESCRIPTION	STANDARD PACK
675-9520	2 Heat/2 Cool Digital Heat Pump Thermostat	1

9600 Series Digital Programmable Thermostat

- 1 Heat/1 Cool
- Compatible with all standard 24 VAC heating and cooling systems
- Weekly 5-2 Day Programming
- Automatic Compressor Short Cycle Protection



675-9600

CATALOG NO.	DESCRIPTION	STANDARD PACK
675-9600	1 Heat/1 Cool Programmable Thermostat	1

9610 Series Digital Programmable Thermostat

- 1 Heat/1 Cool
- Compatible with all standard 24 VAC heating and cooling systems
- 7 Day Programming
- Quickset™
- ENERGY STAR rated for Energy Savings
- O & B Terminals



675-9610

CATALOG NO.	DESCRIPTION	STANDARD PACK
675-9610	1 Heat/1 Cool 7 Day Programmable Thermostat	1

9615 Series Digital Programmable Thermostat

- 2 Heat/2 Cool
- Compatible with all standard 24 VAC heat pump systems
- Quickset™
- ENERGY STAR rated for Energy Savings
- Multi Colored LEDs indicate system status
- 24V Powered with Battery Backup
- Adjustable 1st and 2nd stage differential



675-9615

CATALOG NO.	DESCRIPTION	STANDARD PACK
675-9615	2 Heat/2 Cool Programmable Thermostat	1

ROBERTSHAW THERMOSTATS cont'd

9620 Series Digital Programmable Thermostat

- 2 Heat/2 Cool
- Compatible with all standard 24 VAC heat pump systems
- Quickset™
- ENERGY STAR rated for Energy Savings
- Multi Colored LEDs indicate system status
- 24V Powered with Battery Backup
- Adjustable 1st and 2nd stage differential



675-9620

CATALOG NO.	DESCRIPTION	STANDARD PACK
675-9620	2 Heat/2 Cool Digital Programmable Heat Pump Thermostat	1

9715i Invensys Deluxe Programmable Thermostat

- 2 Heat/2 Cool with Auto Changeover
- Compatible with all standard 24 VAC heating and cooling systems, up to two stage heat and two stage cool
- 7-Day, 5-2, 5-1-1 or 24 hour programming
- 2, 4 or 6 events per day
- Worry-Free Memory Storage
- ENERGY STAR rated for energy savings
- Indoor/Outdoor Remote Sensor Capable
- Adjustable 1st and 2nd Stage Temperature Differential



675-9715

CATALOG NO.	DESCRIPTION	STANDARD PACK
675-9715	9715 Invensys Thermostat	1

9701 Invensys Deluxe Programmable Thermostat

- 1 Heat/1 Cool with Auto Changeover
- Compatible with all single stage 24 VAC heating and cooling, including single stage heat pump systems
- 7-Day, 5-2, 5-1-1 or 24 hour programming
- 2, 4 or 6 events per day
- Worry-Free Memory Storage
- ENERGY STAR rated for energy savings
- Indoor/Outdoor Remote Sensor Capable



675-9701

CATALOG NO.	DESCRIPTION	STANDARD PACK
675-9701	9701 Invensys Thermostat	1

9720i Invensys Deluxe Programmable Thermostat

- 2 Heat/2 Cool with Auto Changeover
- Compatible with all standard 24 VAC heat pump systems, up to two stage heat and two stage cool
- 7-Day, 5-2, 5-1-1 or 24 hour programming
- 2, 4 or 6 events per day
- Worry-Free Memory Storage
- ENERGY STAR rated for energy savings
- Indoor/Outdoor Remote Sensor Capable
- Adjustable 1st and 2nd Stage Temperature Differential



675-9720

CATALOG NO.	DESCRIPTION	STANDARD PACK
675-9720	9720 Invensys Thermostat	1

THERMOSTAT WIRE

Thermostat Wire

Now Riser Rated! Class 2 thermostat wire for indoor wiring needs. Soft drawn bare copper wire, semi-rigid PVC insulation and PVC overall jacket. Packaged on aluminum spool.



620-18-2

Plenum Thermostat Wire

UL Listed type CL2P – NEC Article 725.



620-18-2P

CATALOG NO.	DESCRIPTION	STANDARD PACK
620-18-2	18 AWG, 2 Conductors – 500 ft. Spool	4 Rolls
620-18-3	18 AWG, 3 Conductors – 500 ft. Spool	4 Rolls
620-18-4	18 AWG, 4 Conductors – 250 ft. Spool	4 Rolls
620-18-5	18 AWG, 5 Conductors – 250 ft. Spool	4 Rolls
620-18-6	18 AWG, 6 Conductors – 250 ft. Spool	4 Rolls
620-18-7	18 AWG, 7 Conductors – 250 ft. Spool	4 Rolls
620-18-8	18 AWG, 8 Conductors – 250 ft. Spool	4 Rolls
620-18-9	18 AWG, 9 Conductors – 250 ft. Spool	4 Rolls
620-18-10	18 AWG,10 Conductors – 250 ft. Spool	4 Rolls
620-18-12	18 AWG,12 Conductors – 250 ft. Spool	4 Rolls
620-20-2	20 AWG, 2 Conductors – 500 ft. Spool	4 Rolls
620-20-3	20 AWG, 3 Conductors – 500 ft. Spool	4 Rolls
620-20-4	20 AWG, 4 Conductors – 250 ft. Spool	4 Rolls
620-20-5	20 AWG, 5 Conductors – 250 ft. Spool	4 Rolls
620-20-6	20 AWG, 6 Conductors – 250 ft. Spool	4 Rolls
620-20-7	20 AWG, 7 Conductors – 250 ft. Spool	4 Rolls
620-20-8	20 AWG, 8 Conductors – 250 ft. Spool	4 Rolls
620-20-10	20 AWG,10 Conductors – 250 ft. Spool	4 Rolls

CATALOG NO.	DESCRIPTION	STANDARD PACK
620-18-2P	18 AWG, 2 Conductors – 500 ft. Spool	4 Rolls
620-18-3P	18 AWG, 3 Conductors – 500 ft. Spool	4 Rolls
620-18-4P	18 AWG, 4 Conductors – 250 ft. Spool	4 Rolls
620-18-5P	18 AWG, 5 Conductors – 250 ft. Spool	4 Rolls
620-18-6P	18 AWG, 6 Conductors – 250 ft. Spool	4 Rolls
620-18-8P	18 AWG, 8 Conductors – 250 ft. Spool	4 Rolls

U.L. Listed. Meets Subject 13 per Article 725, 1990 NEC.

ELECTRICAL SUPPLIES

Outdoor Extension Cord

Heavy duty, round, vinyl extension cord designed for use by contractors and industrial. Orange vinyl jacket protects against oil, grease, ozone, and gives added flexibility at below freezing temperatures. Vinyl plugs and connectors are molded on and won't break or pull off cord.



CATALOG NO.	DESCRIPTION	STANDARD PACK
7-ECC50725	25' 15 AMP Extension Cord SJTW-A 14/3	14
7-ECC50730	50' 15 AMP Extension Cord SJTW-A 14/3	10
7-ECC50735	100' 13 AMP Extension Cord SJTW-A 14/3	5
7-ECC1625	25' 15 Amp Extension Cord SJTW-A 16/3	24
7-ECC1650	50' 15 Amp Extension Cord SJTW-A 16/3	12
7-ECC16100	100' 13 Amp Extension Cord SJTW-A 16/3	6
7-ECC1225	25' Extension Cord, 12/3 SJTW-A	10
7-ECC1250	50' Extension Cord, 12/3 SJTW-A	6
7-ECC12100	100' Extension Cord, 12/3 SJTW-A	3

Type: SJTW-A U.L. Listed, meets OSHA Requirements.

Power Blocks

Professional design gives contractors and industrial personnel maximum flexibility in arranging portable power needs at the job site. Vinyl connectors are solid molded for high resistance to breakage and abuse.



CATALOG NO.	DESCRIPTION	STANDARD PACK
7-AD010000	Triple tap power block adapter converts single 15 AMP 125V U-ground outlet to 3 15A, 125V U-ground outlets.	1

Power Supply Cord (Pigtails)

Stranded bare copper conductors. Grounding conductors. PVC jacket. Right and straight angle male plug. 110 Volt. 16 AWG x 6' long.



CATALOG NO.	DESCRIPTION	STANDARD PACK
625-16-6	Power Supply Cord – Straight Plug	50
625-16-690	Power Supply Cord – 90 Degree Plug	50

Metal Guard Trouble Lights

Designed for rugged use by contractors and industrial. Tough plastic handles are heat and shock resistant, with switch and 15A, 125V grounding side outlet.



CATALOG NO.	DESCRIPTION	STANDARD PACK
7-TLC10625	25' Metal Guard Trouble Light	1
7-TLC10630	50' Metal Guard Trouble Light	1

AWG: 16/3 TYPE: SJTW-A U.L. Listed, meets OSHA Requirements.

FUSES BY LITTELFUSE

Dual Element Fuses – 250V

Provides time delay for temporary over-current conditions and motor running protection for heating and air conditioning equipment. Eliminates unnecessary maintenance from harmless overloads.



CATALOG NO.	DESCRIPTION	STANDARD PACK
7-CRNR15	15 Amps	10/Box
7-CRNR20	20 Amps	10/Box
7-CRNR25	25 Amps	10/Box
7-CRNR30	30 Amps	10/Box
7-CRNR35	35 Amps	10/Box
7-CRNR40	40 Amps	10/Box
7-CRNR45	45 Amps	10/Box
7-CRNR50	50 Amps	10/Box
7-CRNR60	60 Amps	10/Box

U.L. Class RK-5, Standard for Safety 198E, Current Limiting Fuses, Interrupting Rating 200,000 Amps. rms. A.C.

One Time Fuses

Protection to lighting, heating, and other non-transient circuits.




CATALOG NO.	DESCRIPTION	STANDARD PACK
7-10KOTN30	30 Amps	10/Box
7-10KOTN35	35 Amps	10/Box
7-10KOTN40	40 Amps	10/Box
7-10KOTN45	45 Amps	10/Box
7-10KOTN50	50 Amps	10/Box
7-10KOTN60	60 Amps	10/Box

U.L. Class H, Standard for Safety 1988, One Time Fuse Interrupting Rating 10,000 Amps. rms. A.C.

FUSES BY LITTELFUSE cont'd

Type "S" Non-Tamper Fuses

Provides specific overcurrent protection. Time-delay element protects against premature blowing from motors in air conditioners or compressors. Visual indication of good or blown condition.



626-30S

CATALOG NO.	DESCRIPTION	STANDARD PACK
626-3S	Type "S" Fuse – 3.2 Amp	4
626-4S	Type "S" Fuse – 4 Amp	4
626-5S	Type "S" Fuse – 5 Amp	4
626-6S	Type "S" Fuse – 6.25 Amp	4
626-10S	Type "S" Fuse – 10 Amp	4
626-15S	Type "S" Fuse – 15 Amp	4
626-20S	Type "S" Fuse – 20 Amp	4
626-25S	Type "S" Fuse – 25 Amp	4
626-30S	Type "S" Fuse – 30 Amp	4

U.L. Listed. C.S.A. Approved.

Time Delay Plug Fuses



626-30T

CATALOG NO.	DESCRIPTION	STANDARD PACK
626-10T	Type "T" Plug Fuse – 10 Amp	4
626-15T	Type "T" Plug Fuse – 15 Amp	4
626-20T	Type "T" Plug Fuse – 20 Amp	4
626-25T	Type "T" Plug Fuse – 25 Amp	4
626-30T	Type "T" Plug Fuse – 30 Amp	4

U.L. Listed.

Plug Fuses – Fast Acting

Expels gases caused by the blow, but doesn't allow flame to escape. Glass top for safety against shock. Positive visual indication of OK condition or blown condition. Distinguishes between overload and dead short conditions. Magnifying center of face. Shapes of face openings identify ratings. Meets Federal Specification WF-791E/Gen. Type 791/1. Base "W" Fast acting fuses.




626-30

CATALOG NO.	DESCRIPTION	STANDARD PACK
626-15	Plug Fuse – 15 Amp	4
626-20	Plug Fuse – 20 Amp	4
626-25	Plug Fuse – 25 Amp	4
626-30	Plug Fuse – 30 Amp	4

U.L. Listed.


Fuse Adapters



CATALOG NO.	DESCRIPTION	STANDARD PACK
626-38632	Fuse Adapter – 60 to 30 Reducer for Class H, 250V	1
626-38636	Fuse Adapter – 60 to 30 Reducer for Class H, 600V	1

In-Line Fuse Holder

For fusing all control circuits up to 30 amp. Features rigid plastic protective covering for each fuse. Used on AC and DC circuits.



FH-1

CATALOG NO.	DESCRIPTION	STANDARD PACK
FH-1	In-Line Fuse Holder	10

U.L. Listed.

Box Cover Units

Maximum amps: 15. Maximum AC volts: 125. For use with Type "T" Plug Fuses.



620-608

CATALOG NO.	DESCRIPTION	STANDARD PACK
620-608	Switch/Fuse Combo (ESSU)	1
620-6081	Plug Fuse Base Only (ESOU)	1
620-6082	Receptacle/Fuse Combo (ESRU)	1
620-6083	Switch/Fuse Combo Square (ESSY)	1

U.L. Listed and C.S.A. Certified.

Fuse Pullers



626-38071

626-38073

CATALOG NO.	DESCRIPTION	STANDARD PACK
626-38071	Fuse Puller – For Fuse Sizes 1/4" to 1/2"	10
626-38073	Fuse Puller – For Fuse Sizes 1" to 1-3/4"	1

Fuseblocks



626-23133

626-23333

CATALOG NO.	DESCRIPTION	STANDARD PACK
626-23133	Fuseblock – 1 Pole Screw Class H, 250V	1
626-23233	Fuseblock – 2 Pole Screw Class H, 250V	1
626-23333	Fuseblock – 3 Pole Screw Class H, 250V	1
626-26311	Fuseblock – 3 Pole Box Lug Class H, 250V	1

HANGING WIRE

Hanging Wire

18 gauge galvanized on reel.



CATALOG NO.	DESCRIPTION	STANDARD PACK
710-182G	2# Roll – 330' – 18 Gauge Galvanized	16 Rolls/Carton
710-185G	5# Roll – 830' – 18 Gauge Galvanized	16 Rolls/Carton

ELECTRICAL TAPES

Scotch 3M Super 33+ Electrical Tape

Premium grade, 7 mil thick, all-weather vinyl insulating tape. Performs continuously in a temperature ambient of up to 220°F and as low as 0°F. Resealable plastic case. Made in USA.



CATALOG NO.	DESCRIPTION	STANDARD PACK
ET33	Super 33+ Electrical Tape – 3/4" x 66'	10

Scotch 3M Super 88 Electrical Tape

Premium grade, 8.5 mil thick, all-weather vinyl insulating tape. Performs continuously in a temperature ambient of up to 220°F and as low as 0°F. Excellent resistance to abrasion, moisture, acids and corrosion. Packaged in a resealable plastic case. Made in the USA.



CATALOG NO.	DESCRIPTION	STANDARD PACK
ET44	Super 88 Electrical Tape – 3/4" x 66'	10

Scotch 35 Vinyl Electrical Tape

This 7 mil premium grade electrical vinyl tape stretches to conform to virtually any shape that requires color-coded insulation. Abrasion and weather resistant. Measures 3/4" x 66'.



CATALOG NO.	DESCRIPTION	STANDARD PACK
ET35N	Vinyl Electrical Tape – Orange	10
ET35G	Vinyl Electrical Tape – Green	10
ET35R	Vinyl Electrical Tape – Red	10
ET35W	Vinyl Electrical Tape – White	10

Glass Cloth, Moisture Sealing, and Economy Electrical Tapes



CATALOG NO.	DESCRIPTION	STANDARD PACK
GC275	1/2" x 66' Glass Cloth Electrical Tape by 3M	10
GC277	3/4" x 66' Glass Cloth Electrical Tape by 3M	10
ET130C1	1" x 30' Moisture Sealing Splicing Tape by 3M	24
ET22	3/4" x 66' Hiawatha Electrical Tape by 3M	10
6-3460	3/4" x 60' Economy Electrical Tape	10

TERMINALS, CONNECTORS

Multi Color Test Leads


Easy to use multi-colored test leads. 5 colors (white, red, black, yellow, green) with 2 connections each for easy testing on the job. Wire is 18 gauge, 18" long.



CATALOG NO.	DESCRIPTION	STANDARD PACK
CT800	Multi Color Test Leads	1

Test Leads

Alligator clips are covered by pure vinyl boots for flexibility at any temperature without cracking.



CATALOG NO.	DESCRIPTION	STANDARD PACK
FTL3	Pair, Red and Black – 36"	1
FTL3D	Pair, Red and Black – Super Heavy Duty – 36"	1
ACK4	Two Red and Two Black Boots with Four Alligator Clips	1

Butt Connectors – Insulated



CATALOG NO.	DESCRIPTION	STANDARD PACK
B211	Butt Connector – 22-18 W	18
B211C	Butt Connector – 22-18 W	100
B222	Butt Connector – 16-14 W	18
B222C	Butt Connector – 16-14 W	100
B233	Butt Connector – 12-10 W	11
B233C	Butt Connector – 12-10 W	100
BA22	Butt Connectors – Assorted	16
BS22	Splice Connectors – 18-14 W	10

Flag Disconnects



CATALOG NO.	DESCRIPTION	STANDARD PACK
FD11	Flag Disconnect – 22-18 W. .187	25
FD11C	Flag Disconnect – 22-18 W. .187	100
FD12	Flag Disconnect – 22-18 W. .250	25
FD12C	Flag Disconnect – 22-18 W. .250	100
FD21	Flag Disconnect – 16-14 W. .187	25
FD21C	Flag Disconnect – 16-14 W. .187	100
FD22	Flag Disconnect – 16-14 W. .250	25
FD22C	Flag Disconnect – 16-14 W. .250	100
FD32	Flag Disconnect – 12-10 W. .250	10
FD32C	Flag Disconnect – 12-10 W. .250	100
FD211	Full Insulated Flag Disconnect – 22-18 W. .187	6
FD211C	Full Insulated Flag Disconnect – 22-18 W. .187	100
FD212	Full Insulated Flag Disconnect – 22-18 W. .250	6
FD212C	Full Insulated Flag Disconnect – 22-18 W. .250	100
FD221	Full Insulated Flag Disconnect – 16-14 W. .187	6
FD221C	Full Insulated Flag Disconnect – 16-14 W. .187	100
FD222	Full Insulated Flag Disconnect – 16-14 W. .250	6
FD222C	Full Insulated Flag Disconnect – 16-14 W. .250	100

Flag Rings



CATALOG NO.	DESCRIPTION	STANDARD PACK
FR22	Flag Ring 16-14 W. 10 S.	20
FR22C	Flag Ring 16-14 W. 10 S.	100

Special Disconnects



CATALOG NO.	DESCRIPTION	STANDARD PACK
DMM2	Double Male Insulated – .250	4
DMM2C	Double Male Insulated – .250	100
DS20	Stud Adapter – #8, .250	15
DS20C	Stud Adapter – #8, .250	100
DS21	Stud Adapter – #10, .250	20
DS21C	Stud Adapter – #10, .250	100
DS22	F/M Piggyback – 16-14 W. .250	10
DS22C	F/M Piggyback – 16-14 W. .250	100
DS23	F/M Piggyback – .250 (Volkswagon)	20
DS23C	F/M Piggyback – .250 (Volkswagon)	100
DS24	F/M Wire Piggyback – 16-14 W. .250	5
DS24C	F/M Wire Piggyback – 16-14 W. .250	100
DS224	F/M Wire Piggyback Insulated – 16-14 W. .250	6
DS224C	F/M Wire Piggyback Insulated – 16-14 W. .250	100
DS25	Stud Adapter – .250, #6 Screw	5
DS25C	Stud Adapter – .250, #6 Screw	100
DS26	Double Male Screw Mount Connector	5
DS26C	Double Male Screw Mount Connector	100
DS27	F/M Open Barrel Piggyback	8
DS27C	F/M Open Barrel Piggyback	100
DSC3	F/M Piggyback – .250 (Chair)	7
DSC3C	F/M Piggyback – .250 (Chair)	100
DXF1	Full Insulated Female Disconnect – 22-18 W. .250	10
DXF1C	Full Insulated Female Disconnect – 22-18 W. .250	100
DXF2	Full Insulated Female Disconnect – 16-14 W. .250	10
DXF2C	Full Insulated Female Disconnect – 16-14 W. .250	100
DXF3	Full Insulated Female Disconnect – 12-10 W. .250	7
DXF3C	Full Insulated Female Disconnect – 12-10 W. .250	100
DXM1	Full Insulated Male Disconnect – 22-18 W. .250	10
DXM1C	Full Insulated Male Disconnect – 22-18 W. .250	100
DXM2	Full Insulated Male Disconnect – 16-14 W. .250	10
DXM2C	Full Insulated Male Disconnect – 16-14 W. .250	100
DXM3	Full Insulated Male Disconnect – 12-10 W. .250	7
DXM3C	Full Insulated Male Disconnect – 12-10 W. .250	100

COLOR CODES FOR INSULATION

	#22, #20, #18
	#16, #14
	#12, #10

Heat Shrink Tubing – Polyolefin 50% Shrink Commercial Grade – Black



CATALOG NO.	DESCRIPTION	STANDARD PACK
HS03	3/16" I.D. Expanded – 4" Long	8
HS03B	3/16" I.D. Expanded – Per Foot	Bulk
HS04	1/4" I.D. Expanded – 4" Long	7
HS04B	1/4" I.D. Expanded – Per Foot	Bulk
HS06	3/8" I.D. Expanded – 4" Long	6
HS06B	3/8" I.D. Expanded – Per Foot	Bulk
HS08	1/2" I.D. Expanded – 4" Long	5
HS08B	1/2" I.D. Expanded – Per Foot	Bulk
HS012	3/4" I.D. Expanded – 4" Long	4
HS012B	3/4" I.D. Expanded – Per Foot	Bulk
HS16	1" I.D. Expanded – 4" Long	3
HS16B	1" I.D. Expanded – Per Foot	Bulk
HS24	1.5" I.D. Expanded – Per Foot	Bulk
HS32	2" I.D. Expanded – Per Foot	Bulk
HSA1	Assorted 3/16", 1/4", 3/8" – 4" Long	7
HSA2	Assorted 1/2", 3/4", 1" – 4" Long	4

Available in lengths up to 250 ft.

Rings – Brazed Seam – Not Insulated



CATALOG NO.	DESCRIPTION	STANDARD PACK
R042	Ring – 8 W. 10 Stud	5
R042C	Ring – 8 W. 10 Stud	100
R043	Ring – 8 W. 1/4 Stud	5
R043C	Ring – 8 W. 1/4 Stud	100
R044	Ring – 8 W. 5/16 Stud	5
R044C	Ring – 8 W. 5/16 Stud	100
R045	Ring – 8 W. 3/8 Stud	5
R045C	Ring – 8 W. 3/8 Stud	100
R052	Ring – 6 W. 10 Stud	3
R052C	Ring – 6 W. 10 Stud	100
R053	Ring – 6 W. 1/4 Stud	3
R053C	Ring – 6 W. 1/4 Stud	100
R054	Ring – 6 W. 5/16 Stud	3
R054C	Ring – 6 W. 5/16 Stud	100
R055	Ring – 6 W. 3/8 Stud	3
R055C	Ring – 6 W. 3/8 Stud	100
R056	Ring – 6 W. 1/2 Stud	2
R056C	Ring – 6 W. 1/2 Stud	100

Rings – Butted Seam – Not Insulated



CATALOG NO.	DESCRIPTION	STANDARD PACK
R010	Ring – 22-18 W. 6 Stud	30
R010C	Ring – 22-18 W. 6 Stud	100
R011	Ring – 22-18 W. 8 Stud	30
R011C	Ring – 22-18 W. 8 Stud	100
R012	Ring – 22-18 W. 10 Stud	30
R012C	Ring – 22-18 W. 10 Stud	100
R013	Ring – 22-18 W. 1/4 Stud	20
R013C	Ring – 22-18 W. 1/4 Stud	100
R014	Ring – 22-18 W. 5/16 Stud	20
R014C	Ring – 22-18 W. 5/16 Stud	100
R015	Ring – 22-18 W. 3/8 Stud	20
R015C	Ring – 22-18 W. 3/8 Stud	100
R020	Ring – 16-14 W. 6 Stud	30
R020C	Ring – 16-14 W. 6 Stud	100
R021	Ring – 16-14 W. 8 Stud	30
R021C	Ring – 16-14 W. 8 Stud	100
R022	Ring – 16-14 W. 10 Stud	30
R022C	Ring – 16-14 W. 10 Stud	100
R023	Ring – 16-14 W. 1/4 Stud	20
R023C	Ring – 16-14 W. 1/4 Stud	100
R024	Ring – 16-14 W. 5/16 Stud	20
R024C	Ring – 16-14 W. 5/16 Stud	100
R025	Ring – 16-14 W. 3/8 Stud	20
R025C	Ring – 16-14 W. 3/8 Stud	100
R030	Ring – 12-10 W. 6 Stud	20
R030C	Ring – 12-10 W. 6 Stud	100
R031	Ring – 12-10 W. 8 Stud	20
R031C	Ring – 12-10 W. 8 Stud	100
R032	Ring – 12-10 W. 10 Stud	20
R032C	Ring – 12-10 W. 10 Stud	100
R033	Ring – 12-10 W. 1/4 Stud	15
R033C	Ring – 12-10 W. 1/4 Stud	100
R034	Ring – 12-10 W. 5/16 Stud	15
R034C	Ring – 12-10 W. 5/16 Stud	100
R035	Ring – 12-10 W. 3/8 Stud	15
R035C	Ring – 12-10 W. 3/8 Stud	100

Block Spades – 0.20 Wide To Fit Terminal Blocks



CATALOG NO.	DESCRIPTION	STANDARD PACK
SN010	Uninsulated Block Spades – 22-18 W. 6 Stud	30
SN010C	Uninsulated Block Spades – 22-18 W. 6 Stud	100
SN020	Uninsulated Block Spades – 16-14 W. 6 Stud	30
SN020C	Uninsulated Block Spades – 16-14 W. 6 Stud	100
SN210	Insulated Block Spades – 22-18 W. 6 Stud	16
SN210C	Insulated Block Spades – 22-18 W. 6 Stud	100
SN220	Insulated Block Spades – 16-14 W. 6 Stud	16
SN220C	Insulated Block Spades – 16-14 W. 6 Stud	100

Rings – Butted Seam – Insulated



CATALOG NO.	DESCRIPTION	STANDARD PACK
R210	Ring – 22-18 W. 6 Stud	16
R210C	Ring – 22-18 W. 6 Stud	100
R211	Ring – 22-18 W. 8 Stud	16
R211C	Ring – 22-18 W. 8 Stud	100
R212	Ring – 22-18 W. 10 Stud	16
R212C	Ring – 22-18 W. 10 Stud	100
R213	Ring – 22-18 W. 1/4 Stud	12
R213C	Ring – 22-18 W. 1/4 Stud	100
R214	Ring – 22-18 W. 5/16 Stud	12
R214C	Ring – 22-18 W. 5/16 Stud	100
R215	Ring – 22-18 W. 3/8 Stud	12
R215C	Ring – 22-18 W. 3/8 Stud	100
R220	Ring – 16-14 W. 6 Stud	16
R220C	Ring – 16-14 W. 6 Stud	100
R221	Ring – 16-14 W. 8 Stud	16
R221C	Ring – 16-14 W. 8 Stud	100
R222	Ring – 16-14 W. 10 Stud	16
R222C	Ring – 16-14 W. 10 Stud	100
R223	Ring – 16-14 W. 1/4 Stud	12
R223C	Ring – 16-14 W. 1/4 Stud	100
R224	Ring – 16-14 W. 5/16 Stud	12
R224C	Ring – 16-14 W. 5/16 Stud	100
R225	Ring – 16-14 W. 3/8 Stud	12
R225C	Ring – 16-14 W. 3/8 Stud	100
R230	Ring – 12-10 W. 6 Stud	12
R230C	Ring – 12-10 W. 6 Stud	100
R231	Ring – 12-10 W. 8 Stud	12
R231C	Ring – 12-10 W. 8 Stud	100
R232	Ring – 12-10 W. 10 Stud	12
R232C	Ring – 12-10 W. 10 Stud	100
R233	Ring – 12-10 W. 1/4 Stud	10
R233C	Ring – 12-10 W. 1/4 Stud	100
R234	Ring – 12-10 W. 5/16 Stud	10
R234C	Ring – 12-10 W. 5/16 Stud	100
R235	Ring – 12-10 W. 3/8 Stud	10
R235C	Ring – 12-10 W. 3/8 Stud	100

Snap Spade Terminals – Insulated



CATALOG NO.	DESCRIPTION	STANDARD PACK
SS210C	Spade – 22-18 W. 6 Stud	100
SS211C	Spade – 22-18 W. 8 Stud	100
SS212C	Spade – 22-18 W. 10 Stud	100
SS220C	Spade – 16-14 W. 6 Stud	100
SS221C	Spade – 16-14 W. 8 Stud	100
SS222C	Spade – 16-14 W. 10 Stud	100
SS230C	Spade – 12-10 W. 6 Stud	100
SS231C	Spade – 12-10 W. 8 Stud	100
SS232C	Spade – 12-10 W. 10 Stud	100

Rings – Brazed Seam – Insulated



CATALOG NO.	DESCRIPTION	STANDARD PACK
R242	Ring – 8 W. 10 Stud	4
R242C	Ring – 8 W. 10 Stud	100
R243	Ring – 8 W. 1/4 Stud	4
R243C	Ring – 8 W. 1/4 Stud	100
R244	Ring – 8 W. 5/16 Stud	4
R244C	Ring – 8 W. 5/16 Stud	100
R245	Ring – 8 W. 3/8 Stud	4
R245C	Ring – 8 W. 3/8 Stud	100
R252	Ring – 6 W. 10 Stud	3
R252C	Ring – 6 W. 10 Stud	100
R253	Ring – 6 W. 1/4 Stud	3
R253C	Ring – 6 W. 1/4 Stud	100
R254	Ring – 6 W. 5/16 Stud	3
R254C	Ring – 6 W. 5/16 Stud	100
R255	Ring – 6 W. 3/8 Stud	3
R255C	Ring – 6 W. 3/8 Stud	100
R256	Ring – 6 W. 1/2 Stud	3
R256C	Ring – 6 W. 1/2 Stud	100
RSA2	Rings and Spades Assorted	15

Spade Terminals – Insulated



CATALOG NO.	DESCRIPTION	STANDARD PACK
S210	Spade – 22-18 W. 6 Stud	16
S210C	Spade – 22-18 W. 6 Stud	100
S211	Spade – 22-18 W. 8 Stud	16
S211C	Spade – 22-18 W. 8 Stud	100
S212	Spade – 22-18 W. 10 Stud	16
S212C	Spade – 22-18 W. 10 Stud	100
S220	Spade – 16-14 W. 6 Stud	16
S220C	Spade – 16-14 W. 6 Stud	100
S221	Spade – 16-14 W. 8 Stud	16
S221C	Spade – 16-14 W. 8 Stud	100
S222	Spade – 16-14 W. 10 Stud	16
S222C	Spade – 16-14 W. 10 Stud	100
S230	Spade – 12-10 W. 6 Stud	12
S230C	Spade – 12-10 W. 6 Stud	100
S231	Spade – 12-10 W. 8 Stud	12
S231C	Spade – 12-10 W. 8 Stud	100
S232	Spade – 12-10 W. 10 Stud	12
S232C	Spade – 12-10 W. 10 Stud	100

COLOR CODES FOR INSULATION	
	#22, #20, #18
	#16, #14
	#12, #10

Spade Terminals – Not Insulated



CATALOG NO.	DESCRIPTION	STANDARD PACK
S010	Spade – 22-18 W. 6 Stud	30
S010C	Spade – 22-18 W. 6 Stud	100
S011	Spade – 22-18 W. 8 Stud	30
S011C	Spade – 22-18 W. 8 Stud	100
S012	Spade – 22-18 W. 10 Stud	30
S012C	Spade – 22-18 W. 10 Stud	100
S020	Spade – 16-14 W. 6 Stud	30
S020C	Spade – 16-14 W. 6 Stud	100
S021	Spade – 16-14 W. 8 Stud	30
S021C	Spade – 16-14 W. 8 Stud	100
S022	Spade – 16-14 W. 10 Stud	30
S022C	Spade – 16-14 W. 10 Stud	100
S030	Spade – 12-10 W. 6 Stud	22
S030C	Spade – 12-10 W. 6 Stud	100
S031	Spade – 12-10 W. 8 Stud	22
S031C	Spade – 12-10 W. 8 Stud	100
S032	Spade – 12-10 W. 10 Stud	22
S032C	Spade – 12-10 W. 10 Stud	100

Disconnects – Not Insulated



CATALOG NO.	DESCRIPTION	STANDARD PACK
D010	Female Disconnect – 22-18 W. 0.110 (1/8")	30
D010C	Female Disconnect – 22-18 W. 0.110 (1/8")	100
D011	Female Disconnect – 22-18 W. 0.187 (3/16")	30
D011C	Female Disconnect – 22-18 W. 0.187 (3/16")	100
D012	Female Disconnect – 22-18 W. 0.250 (1/4")	30
D012C	Female Disconnect – 22-18 W. 0.250 (1/4")	100
D021	Female Disconnect – 16-14 W. 0.187 (3/16")	30
D021C	Female Disconnect – 16-14 W. 0.187 (3/16")	100
D022	Female Disconnect – 16-14 W. 0.250 (1/4")	30
D022C	Female Disconnect – 16-14 W. 0.250 (1/4")	100
D032	Female Disconnect – 12-10 W. 0.250 (1/4")	25
D032C	Female Disconnect – 12-10 W. 0.250 (1/4")	100
D033	Female Disconnect – 12-10 W. 0.375 (3/8")	10
D033C	Female Disconnect – 12-10 W. 0.375 (3/8")	100
DM011	Male Disconnect – 22-18 W. 0.187 (3/16")	25
DM011C	Male Disconnect – 22-18 W. 0.187 (3/16")	100
DM012	Male Disconnect – 22-18 W. 0.250 (1/4")	30
DM012C	Male Disconnect – 22-18 W. 0.250 (1/4")	100
DM022	Male Disconnect – 16-14 W. 0.250 (1/4")	30
DM022C	Male Disconnect – 16-14 W. 0.250 (1/4")	100
DM032	Male Disconnect – 12-10 W. 0.250 (1/4")	25
DM032C	Male Disconnect – 12-10 W. 0.250 (1/4")	100

Disconnects – Insulated



CATALOG NO.	DESCRIPTION	STANDARD PACK
D210	Female Disconnect – 22-18 W. 0.110 (1/8")	16
D210C	Female Disconnect – 22-18 W. 0.110 (1/8")	100
D211	Female Disconnect – 22-18 W. 0.187 (3/16")	16
D211C	Female Disconnect – 22-18 W. 0.187 (3/16")	100
D212	Female Disconnect – 22-18 W. 0.250 (1/4")	16
D212C	Female Disconnect – 22-18 W. 0.250 (1/4")	100
D220	Female Disconnect – 16-14 W. 0.110 (1/8")	16
D220C	Female Disconnect – 16-14 W. 0.110 (1/8")	100
D221	Female Disconnect – 16-14 W. 0.187 (3/16")	16
D221C	Female Disconnect – 16-14 W. 0.187 (3/16")	100
D222	Female Disconnect – 16-14 W. 0.250 (1/4")	16
D222C	Female Disconnect – 16-14 W. 0.250 (1/4")	100
D232	Female Disconnect – 12-10 W. 0.250 (1/4")	12
D232C	Female Disconnect – 12-10 W. 0.250 (1/4")	100
D233	Female Disconnect – 12-10 W. 0.375 (3/8")	6
D233C	Female Disconnect – 12-10 W. 0.375 (3/8")	100
DM11	Male Disconnect – 22-18 W. 0.187 (3/16")	16
DM11C	Male Disconnect – 22-18 W. 0.187 (3/16")	100
DM12	Male Disconnect – 22-18 W. 0.250 (1/4")	16
DM12C	Male Disconnect – 22-18 W. 0.250 (1/4")	100
DM21	Male Disconnect – 16-14 W. 0.187 (3/16")	16
DM21C	Male Disconnect – 16-14 W. 0.187 (3/16")	100
DM22	Male Disconnect – 16-14 W. 0.250 (1/4")	16
DM22C	Male Disconnect – 16-14 W. 0.250 (1/4")	100
DM32	Male Disconnect – 12-10 W. 0.250 (1/4")	12
DM32C	Male Disconnect – 12-10 W. 0.250 (1/4")	100
DA22	Assorted Female Disconnects	18

Hook Terminals – Insulated



CATALOG NO.	DESCRIPTION	STANDARD PACK
H211	Hook – 22-18 W, 8 Stud	14
H211C	Hook – 22-18 W, 8 Stud	100
H212	Hook – 22-18 W, 10 S	14
H212C	Hook – 22-18 W, 10 S	100
H221	Hook – 16-14 W, 8 Stud	14
H221C	Hook – 16-14 W, 8 Stud	100
H222	Hook – 16-14 W, 10 S	14
H222C	Hook – 16-14 W, 10 S	100
H231	Hook – 12-10 W, 8 Stud	10
H231C	Hook – 12-10 W, 8 Stud	100
H232	Hook – 12-10 W, 10 S	10
H232C	Hook – 12-10 W, 10 S	100

High Temperature Terminals

DiversiTech high temperature terminals are made of nickel plated steel. The nickel plating prevents rust and provides a good electrical conductivity. They tolerate temperatures up to 900°F and withstand vibration well.



CATALOG NO.	DESCRIPTION	STANDARD PACK
BH11	Butt Connectors – 22-18 W.	20
BH11C	Butt Connectors – 22-18 W.	100
BH22	Butt Connectors – 16-14 W.	20
BH22C	Butt Connectors – 16-14 W.	100
BH33	Butt Connectors – 12-10 W.	18
BH33C	Butt Connectors – 12-10 W.	100
DH11	Female Disconnects – 22-18 W. 0.187 (3/16")	20
DH11C	Female Disconnects – 22-18 W. 0.187 (3/16")	100
DH12	Female Disconnects – 22-18 W. 0.250 (1/4")	20
DH12C	Female Disconnects – 22-18 W. 0.250 (1/4")	100
DH21	Female Disconnects – 16-14 W. 0.187 (3/16")	20
DH21C	Female Disconnects – 16-14 W. 0.187 (3/16")	100
DH22	Female Disconnects – 16-14 W. 0.250 (1/4")	20
DH22C	Female Disconnects – 16-14 W. 0.250 (1/4")	100
DH32	Female Disconnects – 12-10 W. 0.250 (1/4")	13
DH32C	Female Disconnects – 12-10 W. 0.250 (1/4")	100
DHM12	Male Disconnects – 22-18 W. 0.250 (1/4")	20
DHM12C	Male Disconnects – 22-18 W. 0.250 (1/4")	100
DHM21	Male Disconnects – 16-14 W. 0.187 (3/16")	20
DHM21C	Male Disconnects – 16-14 W. 0.187 (3/16")	100
DHM22	Male Disconnects – 16-14 W. 0.250 (1/4")	20
DHM22C	Male Disconnects – 16-14 W. 0.250 (1/4")	100
FH22	Flag Disconnects – 16-14 W. 0.250 (1/4")	18
FH22C	Flag Disconnects – 16-14 W. 0.250 (1/4")	100
FH32	Flag Disconnects – 12-10 W. 0.250 (1/4")	12
FH32C	Flag Disconnects – 12-10 W. 0.250 (1/4")	100
RH10	Ring – 22-18 W. 6 Stud	22
RH10C	Ring – 22-18 W. 6 Stud	100
RH11	Ring – 22-18 W. 8 Stud	22
RH11C	Ring – 22-18 W. 8 Stud	100
RH12	Ring – 22-18 W. 10 Stud	22
RH12C	Ring – 22-18 W. 10 Stud	100
RH13	Ring – 22-18 W. 1/4 Stud	22
RH13C	Ring – 22-18 W. 1/4 Stud	100
RH20	Ring – 16-14 W. 6 Stud	22
RH20C	Ring – 16-14 W. 6 Stud	100
RH21	Ring – 16-14 W. 8 Stud	22
RH21C	Ring – 16-14 W. 8 Stud	100
RH22	Ring – 16-14 W. 10 Stud	22
RH22C	Ring – 16-14 W. 10 Stud	100
RH23	Ring – 16-14 W. 1/4 Stud	18
RH23C	Ring – 16-14 W. 1/4 Stud	100
RH30	Ring – 12-10 W. 6 Stud	15
RH30C	Ring – 12-10 W. 6 Stud	100
RH31	Ring – 12-10 W. 8 Stud	15
RH31C	Ring – 12-10 W. 8 Stud	100
RH32	Ring – 12-10 W. 10 Stud	15
RH32C	Ring – 12-10 W. 10 Stud	100
RH33	Ring – 12-10 W. 1/4 Stud	15
RH33C	Ring – 12-10 W. 1/4 Stud	100
RH34	Ring – 12-10 W. 5/16 Stud	15
RH34C	Ring – 12-10 W. 5/16 Stud	100
RH35	Ring – 12-10 W. 3/8 Stud	15
RH35C	Ring – 12-10 W. 3/8 Stud	100
RH43	Ring – 8 Wire, 1/4 Stud	4
RH55	Ring – 6 Wire, 3/8 Stud	3
RH65	Ring – 4 Wire, 3/8 Stud	2
SH12	Spade – 22-18 W. 10 Stud	22
SH12C	Spade – 22-18 W. 10 Stud	100
SH22	Spade – 16-14 W. 10 Stud	22
SH22C	Spade – 16-14 W. 10 Stud	100
SH32	Spade – 12-10 W. 10 Stud	22
SH32C	Spade – 12-10 W. 10 Stud	100
HTA2	Assorted Hi-Temp Terminals	20

Compressor Terminals

The only terminals recommended for the wiring of compressors. Made from a phosphorous bronze material to allow for a very tight grip while allowing full current flow.



CATALOG NO.	DESCRIPTION	STANDARD PACK
CC32	Compressor Terminals – .250	6
CC32C	Compressor Terminals – .250	100

Alligator Clips



CATALOG NO.	DESCRIPTION	STANDARD PACK
ACK4	Two Red and Two Black Boots with 4 Clips	1

Compartmented Storage Boxes



CATALOG NO.	DESCRIPTION	STANDARD PACK
MB21	21 Compartmented Metal Box	1
MB22	21 Compartmented Metal Box with 230 popular items including hi-temp and compressor terminals, nylon ties and clamps	1

Transparent Plastic Boxes with Terminal Assortments

Boxes are made of soft, pliable, durable "K" resin with 18 compartments containing the most popular terminals, including hi-temp and compressor terminals.




CATALOG NO.	DESCRIPTION	STANDARD PACK
PA10	180 Terminals (10 Each Kind)	1
PA25	450 Terminals (25 Each Kind)	1
PA25AP	Appliance Parts Technician Assortment – Mostly Hi-Temp	1
PA18	"K" Resin Plastic Box Only	1

COLOR CODES FOR INSULATION

	#22, #20, #18
	#16, #14
	#12, #10

WIRE/CABLE TIES, MOUNTS, CLAMPS

White Nylon Wire Ties



CATALOG NO.	DESCRIPTION	STANDARD PACK
WT04	White Wire Ties – 4" Nylon	40
WT04C	White Wire Ties – 4" Nylon	100
WT05	White Wire Ties – 5" Nylon	35
WT05C	White Wire Ties – 5" Nylon	100
WT07	White Wire Ties – 7" Nylon	30
WT07C	White Wire Ties – 7" Nylon	100
WT11	White Wire Ties – 11" Nylon	15
WT11C	White Wire Ties – 11" Nylon	100
WT15	White Wire Ties – 15" Nylon	12
WT15C	White Wire Ties – 15" Nylon	100
WTA1	White Wire Ties – Assorted 4", 7", and 11" Nylon	30


Black Nylon Ties with Mounting Hole



CATALOG NO.	DESCRIPTION	STANDARD PACK
WTMB05	Black Wire Ties with Mounting Hole – 5" Nylon	12
WTMB05C	Black Wire Ties with Mounting Hole – 5" Nylon	100
WTMB07	Black Wire Ties with Mounting Hole – 7" Nylon	10
WTMB07C	Black Wire Ties with Mounting Hole – 7" Nylon	100
WTMB11	Black Wire Ties with Mounting Hole – 11" Nylon	6
WTMB11C	Black Wire Ties with Mounting Hole – 11" Nylon	100
WTMB14	Black Wire Ties with Mounting Hole – 14" Nylon	5
WTMB14C	Black Wire Ties with Mounting Hole – 14" Nylon	100

Black Nylon Wire Ties

Ultraviolet resistant for outdoor use.



CATALOG NO.	DESCRIPTION	STANDARD PACK
WTB05	Black Wire Ties – 5" Nylon	35
WTB05C	Black Wire Ties – 5" Nylon	100
WTB07	Black Wire Ties – 7" Nylon	30
WTB07C	Black Wire Ties – 7" Nylon	100
WTB11	Black Wire Ties – 11" Nylon	15
WTB11C	Black Wire Ties – 11" Nylon	100
WTB15	Black Wire Ties – 15" Nylon	12
WTB15C	Black Wire Ties – 15" Nylon	100
WTBA1	Black Wire Ties – Assorted 4", 7", and 11" Nylon	28

Wire Tie Mounts



CATALOG NO.	DESCRIPTION	STANDARD PACK
WTM1	White Wire Tie Mounts – Adhesive Back	4
WTM1C	White Wire Tie Mounts – Adhesive Back	100
WTM2	White Wire Tie Mounts – #8 Screw	7
WTM2C	White Wire Tie Mounts – #8 Screw	100

White Nylon Ties with Mounting Hole



CATALOG NO.	DESCRIPTION	STANDARD PACK
WTM05	White Wire Ties with Mounting Hole – 5" Nylon	13
WTM05C	White Wire Ties with Mounting Hole – 5" Nylon	100
WTM07	White Wire Ties with Mounting Hole – 7" Nylon	11
WTM07C	White Wire Ties with Mounting Hole – 7" Nylon	100
WTM11	White Wire Ties with Mounting Hole – 11" Nylon	6
WTM11C	White Wire Ties with Mounting Hole – 11" Nylon	100
WTM14	White Wire Ties with Mounting Hole – 14" Nylon	5
WTM14C	White Wire Ties with Mounting Hole – 14" Nylon	100

Cable Tie Assortment Pack



CATALOG NO.	DESCRIPTION	STANDARD PACK
7-711	Natural Cable Tie Assortment – 7" and 11"	25 Bags
7-711-B	Black Cable Tie Assortment – 7" and 11"	25 Bags
7-5811	Natural Cable Tie Assortment – 5", 8", and 11"	30 Bags
7-5811-B	Black Cable Tie Assortment – 5", 8", and 11"	30 Bags

Cable Tie Holder

Finally an easier way to hold 24" to 48" cable ties. Easy to carry across your back or around your waist.



CATALOG NO.	DESCRIPTION	STANDARD PACK
CTH-1	Cable Tie Holder	1

Wire and Cable Clamps – Nylon



CATALOG NO.	DESCRIPTION	STANDARD PACK
WC02	Wire and Cable Clamps – 1/8" Diameter	40
WC03	Wire and Cable Clamps – 3/16" Diameter	40
WC04	Wire and Cable Clamps – 1/4" Diameter	35
WC05	Wire and Cable Clamps – 5/16" Diameter	35
WC06	Wire and Cable Clamps – 3/8" Diameter	30
WC07	Wire and Cable Clamps – 7/16" Diameter	30
WC08	Wire and Cable Clamps – 1/2" Diameter	25
WC09	Wire and Cable Clamps – 9/16" Diameter	20
WC10	Wire and Cable Clamps – 5/8" Diameter	20
WC12	Wire and Cable Clamps – 3/4" Diameter	15
WC14	Wire and Cable Clamps – 7/8" Diameter	15
WC16	Wire and Cable Clamps – 1" Diameter	14
WCA1	Wire and Cable Clamps Assortment – 1/8" to 1"	26

All the above sizes are available in 100 pks.

Heavy Duty Cable Ties

6.6 nylon, the heavy duty duct straps feature smooth insertion, and a locking mechanism that gives ductwork a firm hold. Accommodates 7 to 15 inch duct. Tensioning tool for 32"+ allows operator to adjust strap to any desired tension.



CATALOG NO.	DESCRIPTION	STANDARD PACK
7-P24	24" Long – Fits up to 6" Duct – 175 lb. Tensile	50
7-P36	36" Long – Fits up to 10" Duct – 175 lb. Tensile	50
7-P36B	36" Long – Black – Fits up to 10" Duct – 175 lb. Tensile	50
7-P48	48" Long – Fits up to 14" Duct – 175 lb. Tensile	50
7-P48B	48" Long – Black – Fits up to 14" Duct – 175 lb. Tensile	50
7-L300	Tensioning Tool for 120-175 lb. Ties	1

WIRE CONNECTORS

Wire Connectors – Contractor Packs



CATALOG NO.	DESCRIPTION	STANDARD PACK
C222	Closed End Connectors 22-14 W	18
C222C	Closed End Connectors 22-14 W	100
C223	Closed End Connectors 18-10 W	15
C223C	Closed End Connectors 18-10 W	100
C241	Blue Wire Connectors 22-16 W	20
C243	Orange Wire Connectors 22-14 W	15
C245	Yellow Wire Connectors 18-10 W	13
C247	Red Wire Connectors 18-10 W	10
C312	Yellow Winged Wire Connectors – 3 - #12	13
C312L	Yellow Winged Wire Connectors – 3 - #12	50
C512	Red Winged Wire Connectors – 5 - #12	10
C512L	Red Winged Wire Connectors – 5 - #12	50

U.L. Listed. CSA Approved.

Wire Connectors – Winged

Wings give surer grip and offset center design provides great twisting leverage. Expandable square-wire spring instantly adjusts to the shape and size to create a strong, vibration-resistant connection. Same superior shell as screw-on type.



CATALOG NO.	DESCRIPTION	STANDARD PACK
623-000	Lg. Gray Winged – Size 78B, #14 to #8 AWG, 600V Max.	50/Box
623-006	Yellow Winged – Size 84, #22 to #10 AWG, 600V Max.	100/Box
623-007	Red Winged – Size 86, #18 to #10 AWG, 600V Max.	100/Box
623-008	Blue Winged – Size 88, #10 to #6, 600V Max.	50/Box

U.L. Listed. C.S.A. Approved.

Wire Connectors – Screw-On

Color-coded wire connectors make quick, secure connections for positive continuity. Tough, high-dielectric thermoplastic shell resists chemical action from hydrocarbons, dilute acid or alkaline solutions and features deep skirt design to prevent exposure of bare wire.



CATALOG NO.	DESCRIPTION	STANDARD PACK
623-001	Gray Screw-On – Size 71B, #22 to #16 AWG, 300V Max.	100/Box
623-002	Blue Screw-On – Size 72B, #22 to #16 AWG, 300V Max.	100/Box
623-003	Orange Screw-On – Size 73B, #22 to #14 AWG, 600V Max.	100/Box
623-004	Yellow Screw-On – Size 74B, #18 to #10 AWG, 600V Max.	100/Box
623-005	Red Screw-On – Size 76B, #18 to #10 AWG, 600V Max.	100/Box

U.L. Listed. CSA Approved.

MONITORS

Digital Three Phase Line Voltage Monitor

Offers continuous protection against voltage anomalies which can damage compressors, motors and other sensitive electrically operated devices.

PROTECTION: Loss of Phase, Phase Reversal, Voltage Imbalance, Low Voltage, High Voltage

DISPLAY: Large custom LCD display indicates all operating conditions at a glance. Three large sets of digits provide easy system troubleshooting.

VOLTMETER: Three independent voltmeters read both line and contactor load (backside) voltages.

MONITORED VOLTAGE: 160 to 600 Volts 50-60 Hz.

POWER SUPPLY: Power for the WPC-500 is automatically derived from any active phase. System operation is not dependent on the control voltage or a specific phase for power.

CONTROL VOLTAGE: 19-277 VAC. Anticipator load is provided for operation with 24 volt electronic and mechanical thermostats.

OPERATING VOLTAGE SET POINT: 175 to 650 VAC. Digitally adjustable in one volt increments.

VOLTAGE TRIP POINT: Adjustable in 1% increments between 6% and 18% of selected operating voltage. Restart voltage set point (hysteresis) fixed at cutout voltage + 3%.

VOLTAGE SYMMETRY: Adjustable imbalance trip point from 2% to 25% of selected operating voltage.

RESPONSE TIMES: Phase Loss/Reversal: 100 mS max.
Imbalance: Adjustable Response Timer
Over or Under Voltage: Adjustable Response Timer

LOCKOUT DELAY TIMER: Fully adjustable 0 to 720 Seconds (0 to 12 minutes). Digital display shows remaining time and user set points.

SEQUENTIAL START TIMER: 0 to 30 seconds in one second increments.

RESPONSE TIMER: 0.1 to 20 Seconds. Digital display shows remaining time and user set points.

MEMORY: Up to 25 past fault conditions are stored for later retrieval and analysis. The faults may be displayed or cleared by the front panel buttons.



DTP-3

Digital Single Phase Line Voltage Monitor

Automatic voltage monitor and control system. Continuously measures incoming line voltage, allowing detection of any voltage outside the tolerances that you set. If these limits are exceeded, the response timer begins counting. You may also set response time – a short time for a quick response or a long time to avoid nuisance tripping. If the voltage remains outside the tolerance after the time has elapsed, the DSP-1 will turn off its output relay and protect your device. While output is off, an additional delay timer activates to avoid rapid restarts.

FEATURES:
Digital voltmeter displays instantaneous line voltage;
Automatic voltage tester adjusts from 90 to 300 volts;
Adjustable response timer (0.1 to 10 sec.) prevents nuisance tripping;
Adjustable delay timer (1 to 720 sec.) prevents rapid restarts;
Digital display makes for easy viewing and operation

SPECIFICATIONS:
Voltmeter: 70 to 325 Volts
Voltage Set Point: 90 to 300 Volts
Tolerance Limits: 6 to 18%
Response Timer: 0.1 to 10 seconds
Delay Timer: 1 to 720 seconds
Output Relay: 10 Amps, 250 VAC resistive, single-pole/double-throw
Control Input: 18 to 250 VAC with anticipator load for 24 volt thermostats



DSP-1

CATALOG NO.	DESCRIPTION	STANDARD PACK
DSP-1	Digital Single Phase Motor Protector	1

CATALOG NO.	DESCRIPTION	STANDARD PACK
DTP-3	Digital 3-Phase Motor Protector	1



CHARLES GALLO BRAND DRAIN GUN AND SWOOSH CO₂ CARTRIDGES

Charles Gallo brand Drain Gun and SWOOSH CO₂ Cartridges

Clears condensate drains with a SWOOSH! A lightweight (3 oz.) portable tool designed to blow out drain lines instantly. New larger SWOOSH CO₂ cartridges now deliver 1200 PSI of oil free food grade to clear the line. Each unit comes equipped with a tapered fitting to work on 3/8" – 3/4" drain openings. Flexible hose assembly maneuvers through cabinets, coils and hard to reach drains. Cartridges are environmentally safe and recyclable. No need for air or nitrogen tanks. Reduces labor costs and time on service calls.





GG-1

CATALOG NO.	DESCRIPTION	STANDARD PACK
GG-1	Charles Gallo Drain Gun for A/C Condensate Lines	6
GGC-12	SWOOSH CO ₂ Cartridges – 12 per Pack	6
GG-1A	Charles Gallo Drain Gun Adapter Kit	1
GG-1H	Charles Gallo Drain Gun Hose Assembly	1

MOTORS

Direct Drive Furnace Blower Motors

- Installs with all Standard 48 Frame Mounting Brackets
- Standard Shaft Length, Diameter, and Flats
- Uses 370V Capacitors
- Standard Motor Casing Size
- 2.5" Diameter Hub Rings included
- Low Power Consumption
- Automatic Thermal Overload Protector
- Continuous Duty, Air Over
- Electrically Reversible
- Class B Insulation
- Speed: 1075/3
- Quiet Operation
- 60 HZ



CATALOG NO.	HP	VOLTAGE	SPEED	FLA
WG840583	1/4	115	1075/3	4.6
WG840584	1/4	208-230	1075/3	2.2
WG840585	1/3	115	1075/3	6.7
WG840586	1/3	208-230	1075/3	2.9
WG840587	1/2	115	1075/3	10.2
WG840588	1/2	208-230	1075/3	5.0
WG840589	3/4	115	1075/3	12.4
WG840590	3/4	208-230	1075/3	5.4
WG840595	1	115	1075/3	14.0
WG840596	1	208-230	1075/3	5.2

Condenser Fan Motors

- Installs with all Standard 48 Frame Mounting Brackets
- Standard Shaft Length, Diameter, and Flats
- Drain Holes with Plugs in both end plates
- Automatic Thermal Overload Protector
- Standard Motor Casing Size
- Low Power Consumption
- 60 C Ambient Design
- Electrically Reversible
- Continuous Air Over
- Class B Insulation
- Speed: 1075/1
- Quiet Operation
- Extended Studs
- 30" Leads
- 60 HZ



CATALOG NO.	HP	VOLTAGE	SPEED	FLA
WG840727	1/6	208-230	1075/1	0.3
WG840728	1/4	208-230	1075/1	2.2
WG840729	1/3	208-230	1075/1	2.8
WG840730	1/2	208-230	1075/1	4.2
WG840731	3/4	208-230	1075/1	4.5

Multiple Horsepower Motors

The Multi-Horsepower motors are specially designed to cover a range of applications. The condenser fan motors range from 1/2 to 1/5; 1/3 to 1/6 both at 1075 rpm; 1/3 to 1/6 at 825rpm. The direct drive furnace blower motors range from 1/2 to 1/6 in both 115 and 230 volts and 3/4 to 1/5 in both 115 and 230 volts all at 1075rpm. These motors feature reversing plugs, extended thru bolts 36 inch leads and are designed for 370 volt capacitors.




CATALOG NO.	APPLICATION	VOLTAGE	SPEED	(1) HP-FLA	(2) HP-FLA	(3) HP-FLA	(4) HP-FLA	(5) HP-FLA
WG840463	DDFB	115	1075/4	1/2-7.0	1/3-6.7	1/4-4.4	1/5-3.2	1/6-2.4
WG840464	DDFB	208-230	1075/4	1/2-3.9	1/3-3.6	1/4-2.5	1/5-1.8	1/6-1.3
WG840465	CF	208-230	1075/2	1/3-2.8	1/4-2.0	1/5-1.7	1/6-1.5	
WG840466	DDFB	115	1075/4	3/4-8.1	1/2-6.6	1/3-4.6	1/4-3.8	1/5-3.1
WG840467	DDFB	208-230	1075/4	3/4-3.8	1/2-3.7	1/3-2.5	1/4-1.8	1/5-1.7
WG840468	CF	208-230	1075/2	1/2-3.0	1/3-2.5	1/4-2.0	1/5-1.3	
WG840469	CF	208-230	825/2	1/3-2.1	1/4-1.7	1/5-1.5	1/6-1.2	

ANTI-VIBRATION PADS

E.V.A. Anti-Vibration Pad


The latest generation in vibration dampening technology – the EVA pad. The most effective vibration dampening pad available on the market. We tested the EVA Pad against other pads at four different vibration settings. In the most severe vibration extremes, the new EVA Pad outperforms cork and rubber by a margin of greater than 3:1! This enhanced performance is due to the special composite foam centre. The composite foam is much more structurally sound than cork. It is not affected by oils or chemicals that can sometimes break down cork, and is much more effective at vibration dampening than solid rubber. In essence, the EVA Pad gives you the best of both worlds, at a very competitive price. Designed to withstand 50 lbs. psi.



CATALOG NO.	DESCRIPTION	STANDARD PACK
MP-2E	2" x 2" x 7/8" E.V.A. Pad	48
MP-3E	3" x 3" x 7/8" E.V.A. Pad	36
MP-4E	4" x 4" x 7/8" E.V.A. Pad	24
MP-6E	6" x 6" x 7/8" E.V.A. Pad	24
MP-12E	12" x 12" x 7/8" E.V.A. Pad	12
MP-18E	18" x 18" x 7/8" E.V.A. Pad	6

Rubber Anti-Vibration Pad


Highest quality elastomeric oil resistant padding. Designed to withstand 50 lbs. psi. The rubber pads are corrugated on both sides. Ideal for air conditioners, compressors, cooling towers, presses, machines, etc.



CATALOG NO.	DESCRIPTION	STANDARD PACK
MP-2	2" x 2" x 3/8" Rubber	48
MP-3	3" x 3" x 3/8" Rubber	36
MP-4	4" x 4" x 3/8" Rubber	24
MP-6	6" x 6" x 3/8" Rubber	24
MP-8	8" x 8" x 3/8" Rubber	12
MP-12	12" x 12" x 3/8" Rubber	12
MP-18	18" x 18" x 3/8" Rubber	6

Rubber/Cork Anti-Vibration Pad

Highest quality elastomeric oil resistant padding. Designed to withstand 50 lbs. per square inch. The rubber pads are corrugated on both sides. The cork is laminated between two corrugated pads. Ideal for air conditioners, compressors, cooling towers, presses, machines, etc.



CATALOG NO.	DESCRIPTION	STANDARD PACK
MP-2C	2" x 2" x 7/8" Rubber/Cork	48
MP-3C	3" x 3" x 7/8" Rubber/Cork	36
MP-4C	4" x 4" x 7/8" Rubber/Cork	24
MP-6C	6" x 6" x 7/8" Rubber/Cork	24
MP-8C	8" x 8" x 7/8" Rubber/Cork	12
MP-12C	12" x 12" x 7/8" Rubber/Cork	12
MP-18C	18" x 18" x 7/8" Rubber/Cork	6

Iso-Cube Anti-Vibration Pad

Natural rubber pads, designed to reduce vibration and noise emanating from refrigeration and air conditioning equipment. The circular design in each pad offers a suction cup effect, which eliminates the need to bolt the pads down. A standard 18" (46cm) pad is divided into eighty-one 2" (5cm) segments, each of which may be cut or torn to provide smaller pads. These 50 durometer pads will withstand a load of 180 psi with greater resiliency.



CATALOG NO.	DESCRIPTION	STANDARD PACK
ISO-2	2" x 2" x 3/4" Iso-Cube	12
ISO-4	4" x 4" x 3/4" Iso-Cube	12
ISO-18	18" x 18" x 3/4" Iso-Cube	6

PVC PRIMER, CEMENT, SEALANT

Pro-Prime™ PVC Solvent Primer


Pro-Prime™ PVC Solvent Primer is a purple-tinted primer formulated to remove dirt and oil from the surface of Type I and II PVC piping, as well as soften the piping in preparation for solvent welding. Pro-Prime™ contains purple pigment which provides verification that the primer has been applied to the pipe surface. Pro-Prime™ meets ASTM Standard F-656.



CATALOG NO.	DESCRIPTION	STANDARD PACK
PP-4	Pro-Prime™ – 4 oz. Brush-Top Container	24
PP-8	Pro-Prime™ – 8 oz. Brush-Top Container	24
PP-16	Pro-Prime™ – 16 oz. Brush-Top Container	24
PP-32	Pro-Prime™ – 32 oz. Brush-Top Container	12

Pro-Weld™ PVC Cement

Pro-Weld™ PVC Cement is a clear, regular bodied solvent cement designed to be used on Type I and II PVC pipe and fittings up to and including 4 inch diameter. Pro-Weld™ meets ASTM Standard D-2564.



CATALOG NO.	DESCRIPTION	STANDARD PACK
PW-4	Pro-Weld™ – 4 oz. Brush-Top Container	24
PW-8	Pro-Weld™ – 8 oz. Brush-Top Container	24
PW-16	Pro-Weld™ – 16 oz. Brush-Top Container	24
PW-32	Pro-Weld™ – 32 oz. Brush-Top Container	12

Oatey Clear Primer

Clear Primer is a clear aggressive primer for use on PVC and CPVC pipe and fittings, all schedules and all diameters. It removes all surface dirt, grease and grime as well as softens pipe in preparation for solvent cement. Meets ASTM F-656, and is NSF listed.



CATALOG NO.	DESCRIPTION	STANDARD PACK
530-30750	Clear Primer – 4 oz. Brush-Top Container	24
530-30751	Clear Primer – 8 oz. Brush-Top Container	24
530-30752	Clear Primer – 16 oz. Brush-Top Container	24
530-30753	Clear Primer – 32 oz. Brush-Top Container	12

Pro-Air Duct Sealant – UL 181 AM-BM Listed

Water-based fiber-reinforced duct sealant/mastic formulated for indoor/outdoor use. Meets U.L. Class 1 rating and local codes while featuring long term flexibility and strength. Use on metal heating, ventilating, and air conditioning duct systems; as well as fiberglass duct board systems and flex duct systems. Recommended for use to 10" of water column pressure without the need for fiberglass mesh reinforcement.



CATALOG NO.	DESCRIPTION	STANDARD PACK
800-008	Pro-Air Duct Sealant – 1/10 Gallon Tube	24
800-009	Pro-Air Duct Sealant – 1 Gallon Pail	4

Caulk Gun



CATALOG NO.	DESCRIPTION	STANDARD PACK
7-100	Caulk Gun – Super Ratchet Type	12
7-200	Caulk Gun – Standard Duty	12

Silicone Sealant


Food grade 100% RTV Silicone Sealant. Can be used in applications for continuous use to 450°F. UV and water resistant. Long-term flexibility. Non-paintable. Available in 10.3 fl. oz. tube for use in standard caulk gun or in 3 fl. oz. squeeze tube.



CATALOG NO.	DESCRIPTION	STANDARD PACK
7-4000	Clear Silicone Sealant – 10.3 fl. oz. Tube	12
7-4001	Clear Silicone Sealant – 3 fl. oz. Squeeze Tube	72
7-4100	White Silicone Sealant – 10.3 fl. oz. Tube	12
7-4101	White Silicone Sealant – 3 fl. oz. Squeeze Tube	72
7-4200	Aluminum Silicone Sealant – 10.3 fl. oz. Tube	12

High Temp Red Silicone Sealant

A one part non-slumping paste that cures to a tough, rubbery solid at room temperature. Formulated to perform at temperatures ranging from -85°F to 500°F for continuous operation, and to 600°F for intermittent exposure. Tack free cure time – 15 minutes. Full cure time – 24 hours.



CATALOG NO.	DESCRIPTION	STANDARD PACK
7-4300	High Temp Red Silicone Sealant – 10.1 oz. Cartridge	12

Foam Sealant – One Component

One component closed-cell expanding polyurethane foam sealant for lineal caulking applications. Air-moisture cure. Tack free in 20 minutes; fully cured in 12 hours. Paintable. Use for insulating and sealing around windows, doors, pipes, ducts and vents. Non-toxic when cured. Paint to protect from UV exposure. "R" value 4.7 (1" thickness). Foam contains fire retarding chemical and is U.L. Listed but not rated as a firestop product. Environmental concerns have led us to replace CFC's and HCFC's with hydrocarbon material in our one component foam products. See instructions on each product to ensure safe use and quality results.



CATALOG NO.	DESCRIPTION	STANDARD PACK
01714	Foam Sealant – 12 oz. Can – Yields 275' (3/8" bead)	12
01724	Foam Sealant – 20 oz. Can – Yields 460' (3/8" bead)	12

Firestop Products for Class A Buildings

U.L. Classified. Code Approved. Seal penetrations of plumbing, refrigeration and AC lines, ducts, vents and electrical cable through fire-rated floors, walls and ceilings. Easy-to-use, non-shrinking, non-toxic and permanently flexible. Blocks fire, gas, smoke, air and water migration. Use ceramic fiber filler together with putty or caulk for thick penetrations. Technical bulletins available.



CATALOG NO.	DESCRIPTION	STANDARD PACK
16491	Firestop Caulk – Red – 10.3 fl. oz. cartridge	10

GAUGES AND TESTERS

Audible/Visual Circuit Tester

- Contact and Non Contact Audible and Visual Indication
- Detects Hot Side
- 70 to 250 VAC
- Detects Break in Line
- Checks Fuses
- Detects the Presence of AC Voltage “Non Contact” Through Wires, Dry Wall & Wood
- 3 Position Sensitivity
- Batteries Included



6-CT500AV

CATALOG NO.	DESCRIPTION	STANDARD PACK
6-CT500AV	Deluxe Audible/Visual Circuit Tester	1

LED Screwdriver Continuity Tester

- A Screwdriver/Tester You Can See!
- Self Test
- AC Voltage Test 70 to 250BAC
- Continuity Test
- Polarity Check
- Checks Fuses
- Bright Red LED
- When the tip is in direct contact with the live (HOT) part of the AC Voltage, the red LED lights up.



6-ST600LED

CATALOG NO.	DESCRIPTION	STANDARD PACK
6-ST600LED	Red LED Screwdriver Continuity Tester	1

FLASHLIGHTS BY MAG-LITE®

Each Mag-Lite Flashlight offers these features: 1. Exclusive cam-driven beam that changes from spot to flood with a turn of the head. 2. Patented, self-cleaning switch. 3. High quality White Star Krypton bulb (second bulb included in the tail cap) 4. High grade rubber O-rings at each opening to insure water resistance and enhance ability to withstand shock. 5. Anodized finish both inside and out to offer optimum corrosion resistance. 6. Limited lifetime warranty. 7. Manufactured in the USA.

Mag-Lite C and D Cell Flashlights

Police, security, emergency, medical and fire professionals have come to rely on Mag-Lite C and D Cell flashlights more than any other brand. They know serious duty demands serious equipment. The finest flashlight in the world!



CATALOG NO.	DESCRIPTION	STANDARD PACK
7-S2C016	2 Cell C Mag-Lite Flashlight – Black	1
7-S3C016	3 Cell C Mag-Lite Flashlight – Black	1
7-S4C016	4 Cell C Mag-Lite Flashlight – Black	1
7-S2D016	2 Cell D Mag-Lite Flashlight – Black	1
7-S3D016	3 Cell D Mag-Lite Flashlight – Black	1
7-S4D016	4 Cell D Mag-Lite Flashlight – Black	1
7-S5D016	5 Cell D Mag-Lite Flashlight – Black	1
7-S6D016	6 Cell D Mag-Lite Flashlight – Black	1

Mini Mag-Lite

Until the Mini Mag-Lite was introduced, no one had ever dreamed a flashlight could be so small, yet so powerful. Named as one of the “products America makes best” by Fortune and Money magazines.




7-M3A016

CATALOG NO.	DESCRIPTION	STANDARD PACK
7-M3A016	Mini Mag-Lite AAA – Black	1
7-M3A036	Mini Mag-Lite AAA – Red	1
7-M2A016	Mini Mag-Lite AA – Black	1
7-M2A036	Mini Mag-Lite AA – Red	1
7-M2A026	Mini Mag-Lite AA – Camouflage	1
7-AM2A056	Mini Mag-Lite AA Holster – Black	12

Solitaire AAA Single Cell Flashlights

Less than an ounce and about three inches in length. Using only a single AAA battery, its focusing beam is surprisingly bright. A spare bulb, battery, and a key lead are included.



7-K3A016

CATALOG NO.	DESCRIPTION	STANDARD PACK
7-K3A016	Solitaire AAA Flashlight – Black	1
7-K3A036	Solitaire AAA Flashlight – Red	1
7-K3A116	Solitaire AAA Flashlight – Blue	1

Mag Charger System

The ultimate lighting tool. The rechargeable Mag Charger is the most powerful and durable hand-held flashlight of its size. Battery pack is rechargeable 1000 times. State-of-the-art, electro-formed reflector that emits an incredibly bright, high intensity light. System includes: Mag Charger Flashlight, charging unit, battery pack, two mounting brackets, 12V Cigarette Lighter Adapter, and 110V AC Converter.



7-RX1019

CATALOG NO.	DESCRIPTION	STANDARD PACK
7-RX1019	Mag Charger System	1

Mag-Lite Replacement Bulbs



7-LK3A001

CATALOG NO.	DESCRIPTION	STANDARD PACK
7-LK3A001	Solitaire Replacement Bulb – 2 per Card	12
7-LM2A001	Mini Mag-Lite AA Replacement Bulb – 2 per Card	12
7-LWSA201	2 Cell C or D Replacement Bulb – 2 per Card	12
7-LWSA301	3 Cell C or D Replacement Bulb – 2 per Card	12
7-LWSA401	4 Cell C or D Replacement Bulb – 2 per Card	12

FLASHLIGHTS BY MAG-LITE® cont'd

Magna-Lite

Unbreakable pocket flashlight/magnifier. Ideal for checking small serial numbers and names on compressors or where poor light makes reading difficult. Powerful, optical-quality magnifying lens. Lightweight. Replacable penlight batteries.



ML-100

CATALOG NO.	DESCRIPTION	STANDARD PACK
ML-100	Magna-Lite – 1-1/2 oz.	12

MARKERS

Valve Action Marker

Large ink supply for increased mileage. Fast drying, smear and water resistant. Utilizes a patented valve-activated ink feed mechanism to supply ink as required, down to the last drop. Replacement tips available.



540-800

CATALOG NO.	DESCRIPTION	STANDARD PACK
540-799	Valve Action Marker-Regular Tip – Red	12
540-800	Valve Action Marker-Regular Tip – Black	12

Valve Action Paint Marker

Bright, crisp, opaque colors. The oil-based paint is quick drying and permanent on most surfaces. These markers also feature the patented valve-operated feed mechanism and a medium point.



540-808

CATALOG NO.	DESCRIPTION	STANDARD PACK
540-805	Valve Action Paint Marker – Black	12
540-806	Valve Action Paint Marker – Red	12
540-807	Valve Action Paint Marker – White	12
540-808	Valve Action Paint Marker – Yellow	12

Felt Tip Markers

Permanent markers for metal, glass, paper, and plastic. 20% more ink than competitors. Durable metal body.



540-811

CATALOG NO.	DESCRIPTION	STANDARD PACK
540-811	Metal Bodied Felt Tip Marker – Black	12

LUBRICANTS

Pull-A-Spout Oiler

All purpose oiler with a 14" telescoping spout. Zooms out for long shots, and in for short shots, even zooms around corners. Squeeze bottle action. Perfect lubricant for general industrial use. Contains four ounces of finest quality carbon free, rust and oxidation inhibited lubricating oil. Plastic container won't short out around electrical connections. No leakage.



CO-1

CATALOG NO.	DESCRIPTION	STANDARD PACK
CO-1	Pull-A-Spout Oiler – 4 oz.	12 (Display)

Greaseless Lubricant

Thin film lubrication. Water displacer dries out wet electrical/electronic components. Contains no chlorinated solvents. Ideal for delicate mechanisms. Fast penetrating and no oily mess. Safe on rubber, paint, plastic, and fabrics. Won't attract dust or dirt.



LPS-1

CATALOG NO.	DESCRIPTION	STANDARD PACK
LPS-1	Greaseless Lubricant – 11 oz.	12
LPS-1G	Greaseless Lubricant – 1 Gallon	1

LUBRICANTS

Rust Breaker

Quickly loosens rusted bolts, screws, shafts, piping, and all types of "Frozen" connections and assemblies. The answer for rusty or corroded fastenings on cars, trucks, trailers, tractors, farm machinery, appliances, washing machines, plumbing, water pumps, fishing reels, power tools, gardening equipment, and hundreds of other mechanisms. Packaged in a handy telescoping spout applicator.



CR-1

CATALOG NO.	DESCRIPTION	STANDARD PACK
CR-1	Rust Breaker – 4 oz.	12 (Display)

Industrial Strength Lubricant

Leaves light oily coating. Quick release for seized mechanisms. Reduces wear caused by friction corrosion. Contains no chlorinated solvents. Safe on rubber, paint, plastic, fabrics.



LPS-2

CATALOG NO.	DESCRIPTION	STANDARD PACK
LPS-2	Industrial Strength Lubricant – 11 oz.	12
LPS-2G	Industrial Strength Lubricant – 1 Gallon	1

WD-40

Loosens rusted parts. Stops squeaks. Removes tar, grease and adhesives. Displaces moisture. Protects metal.



741-001

CATALOG NO.	DESCRIPTION	STANDARD PACK
741-001	WD-40 – 8 oz.	12
741-002	WD-40 – 11 oz.	12

Heavy Duty Rust Inhibitor

Forms heavy waxy coating. Effective corrosion inhibition under severe conditions and corrosive environments indoors and outdoors up to two years. Safe on rubber, paint, plastics, fabric. Excellent anti-seize compound. Superior chain lubricant.



LPS-3

CATALOG NO.	DESCRIPTION	STANDARD PACK
LPS-3	Heavy Duty Rust Inhibitor – 11 oz.	12
LPS-3G	Heavy Duty Rust Inhibitor – 1 Gallon	1

All Purpose Lubricant

Compared to others, TKX by LPS is the best all-purpose lubricant. "Wicks" faster and penetrates quickly due to lower surface tension. Formulated to deliver greater clinging power and better protection. Safe to use on operating equipment. High 175°F flashpoint. Exclusive "invertvalve" permits spraying in all positions – even upside down.



LPS-40

CATALOG NO.	DESCRIPTION	STANDARD PACK
LPS-40	All Purpose Lubricant – 11 oz.	12

Cold Galvanize

95% zinc rich coating inhibits corrosion up to three years. Works as a primer or finish coat to repair damaged or worn hot-dipped galvanized coatings. Leaves a matte gray finish. Works on rusted surfaces and all metals. Won't crack, chalk, or peel.



LPS-5

CATALOG NO.	DESCRIPTION	STANDARD PACK
LPS-5	Cold Galvanize – 16 oz.	12

BrightCoat Cold Galvanize

Prevents rust and corrosion on all metals. Produces a shiny zinc coating that dries to the touch in 15 to 30 minutes. Heat resistant. Will not yellow, chalk, crack or peel. Meets ASTM A780-93A.



LPS-5BC

CATALOG NO.	DESCRIPTION	STANDARD PACK
LPS-5BC	BrightCoat Cold Galvanize – 13 oz.	12

Thermaplex Multi-Purpose Grease

Specifically developed to outperform conventional bearing greases and extend relubrication periods, reducing maintenance requirements and grease use. Blue colored paste with excellent load carrying properties. Temperature range -22°F to 350°F.



LPS-13

CATALOG NO.	DESCRIPTION	STANDARD PACK
LPS-13	Thermaplex Bearing Grease – 14.1 oz.	30

LUBRICANTS cont'd

Heavy Duty Silicone Lubricant

Dry film lubricant. Water based and ideal for surfaces where petroleum based products are unsuitable. Contains no chlorinated solvents and is safe on metal, plastic, rubber, vinyl, leather and wood. Non-stain, anti-static, and approved by USDA for use in federally inspected meat and poultry plants. Approved for use in areas with incidental food contact.



LPS-6

CATALOG NO.	DESCRIPTION	STANDARD PACK
LPS-6	Heavy Duty Silicone Lubricant – 13 oz.	12

White Lithium w/Teflon

Pure white lubricant with Teflon additives. Provides maximum lubrication. Rust and oxidation inhibitors protect metal. Heat and water resistant. Rapidly forms into a pure white grease that won't melt or wash away.



LPS-9

CATALOG NO.	DESCRIPTION	STANDARD PACK
LPS-9	White Lithium Lubricant – 10 oz.	12

LST Penetrant

Specially formulated with low surface tension for fast penetrating action. Displaces moisture. Powerful foaming action provides complete surface coverage. Flash point of 175°F.



LPS-8

CATALOG NO.	DESCRIPTION	STANDARD PACK
LPS-8	LST Penetrant – 11 oz.	12

KB88 The Ultimate Penetrant

Penetrates quickly and makes the toughest maintenance job faster, safer, and simpler.



LPS-1KB

CATALOG NO.	DESCRIPTION	STANDARD PACK
LPS-1KB	KB88 Penetrant – 13 oz.	12

CONTACT CLEANERS

Electro 140° Contact Cleaner

Ideal for electrical/electronic parts. Flash point above 140°F. No rinsing or residue. Contains no CFCs or 1,1,1. Superior wetting and penetrating action.



LPS-4-140

CATALOG NO.	DESCRIPTION	STANDARD PACK
LPS-4-140	Electro 140° Contact Cleaner – 11 oz.	12

CFC-Free Electro Contact Cleaner

A fast penetrating, quick evaporating, non-residue cleaner for precision parts. Ideal for electrical and electronic fine parts. Penetrates to remove light greases, oil, dirt and other contaminants. Contains no CFCs, NCFs, or 1,1,1 trichloroethane. No rinsing or wiping necessary. Will not stain fabric. Good solvency, low odor, low toxicity. Non conductive, safe on metals and plastics.



LPS-4CF

CATALOG NO.	DESCRIPTION	STANDARD PACK
LPS-4CF	CFC-Free Electro Contact Cleaner – 11 oz.	12

NoFlash NU Precision Contact Cleaner

New patent-pending non-flammable formula. Fast evaporating, quick penetrating, no residue formula. Safe on most surfaces. Replaces HCFC 141b or other chlorinated solvents. No flash point.



LPS-4NU

CATALOG NO.	DESCRIPTION	STANDARD PACK
LPS-4NU	No-Flash NU Contact Cleaner – 15 oz.	12

NoSpark Electrical Cleaner

New patent-pending non-flammable formula. Fast evaporating, quick penetrating, no residue formula that is safe on most surfaces, including plastics. Non-conductive. Replaces HCFC 141n or other HCFC cleaners.



LPS-4NS

CATALOG NO.	DESCRIPTION	STANDARD PACK
LPS-4NS	NoSpark Electrical Cleaner – 14 oz.	12

DEGREASERS

HDX Heavy Duty Degreaser

Quickly removes oil, grease, and dirt. Fast acting, non-flammable. Very fast evaporation. Does not contain CFCs. Does not require rinsing or wiping. Not flammable or conductive.



LPS-7X

CATALOG NO.	DESCRIPTION	STANDARD PACK
LPS-7X	HDX Heavy Duty Degreaser – 19 oz.	12

PreSolve

Quickly removes oil, grease, and dirt. Natural based solvent. Moderate evaporation. Does not contain CFCs. Does not require rinsing or wiping. Flashpoint 104°. Not conductive.



CATALOG NO.	DESCRIPTION	STANDARD PACK
LPS-7PS	PreSolve – 15 oz.	12

ZeroTri

Quickly removes oil, grease, and dirt. Evaporates completely and very rapidly. Does not contain CFCs. Does not require rinsing or wiping. Flashpoint 0°F. Not conductive.



LPS-7Z

CATALOG NO.	DESCRIPTION	STANDARD PACK
LPS-7Z	ZeroTri – 15 oz.	12

Precision Clean

Quickly removes oil, grease, and dirt. Biodegradable. Super industrial strength. USDA approved, non-toxic. Slow evaporation. Does not contain CFCs. Does not require rinsing or wiping. Non flammable. Conductive. Now available in a foaming aerosol!



LPS-728


LPS-728A

CATALOG NO.	DESCRIPTION	STANDARD PACK
LPS-728	Precision Clean – 28 oz.	12
LPS-728A	Precision Clean – 18 oz. Aerosol	12

2" UltraLite® Lightweight Equipment Pads

A true concrete equipment pad at the weight of plastic (about 2.5 lbs. per square foot). UltraLite® is strengthened by miles of fiber in each square foot of fiber-cement coating. This fiber allows the pad to flex instead of cracking or breaking. The textured surface prevents the condensing unit or portable generator from sliding, and allows water drainage, while the engineered encapsulated polystyrene (EPS) core prevents warping and provides a solid bottom to resist settling. Unaffected by soil conditions, ultraviolet (UV) light, temperature extremes, and other weather conditions.

The 2" thick UltraLite® pad is the industry standard. Used across a wide variety of applications, unless a thicker pad (3") is required by the local building code.




UC2424-2



CATALOG NO.	DESCRIPTION	STANDARD PACK
UC1636-2	UltraLite® 2" Equipment Pad – 16" x 36" x 2"	20
UC2424-2	UltraLite® 2" Equipment Pad – 24" x 24" x 2"	20
UC2430-2	UltraLite® 2" Equipment Pad – 24" x 30" x 2"	20
UC2436-2	UltraLite® 2" Equipment Pad – 24" x 36" x 2"	20
UC2448-2	UltraLite® 2" Equipment Pad – 24" x 48" x 2"	20
UC2626-2	UltraLite® 2" Equipment Pad – 26" x 26" x 2"	20
UC2628-2	UltraLite® 2" Equipment Pad – 26" x 28" x 2"	20
UC2636-2	UltraLite® 2" Equipment Pad – 26" x 36" x 2"	20
UC3030-2	UltraLite® 2" Equipment Pad – 30" x 30" x 2"	20
UC3036-2	UltraLite® 2" Equipment Pad – 30" x 36" x 2"	20
UC3040-2	UltraLite® 2" Equipment Pad – 30" x 40" x 2"	20
UC3143-2	UltraLite® 2" Equipment Pad – 31" x 43" x 2"	20
UC3232-2	UltraLite® 2" Equipment Pad – 32" x 32" x 2"	20
UC3234-2	UltraLite® 2" Equipment Pad – 32" x 34" x 2"	20
UC3237-2	UltraLite® 2" Equipment Pad – 32" x 37" x 2"	20
UC3434-2	UltraLite® 2" Equipment Pad – 34" x 34" x 2"	20
UC3445-2	UltraLite® 2" Equipment Pad – 34" x 45" x 2"	20
UC3636-2	UltraLite® 2" Equipment Pad – 36" x 36" x 2"	20
UC3640-2	UltraLite® 2" Equipment Pad – 36" x 40" x 2"	20
UC3648-2	UltraLite® 2" Equipment Pad – 36" x 48" x 2"	20
UC3842-2	UltraLite® 2" Equipment Pad – 38" x 42" x 2"	20
UC4040-2	UltraLite® 2" Equipment Pad – 40" x 40" x 2"	20
UC4147-2	UltraLite® 2" Equipment Pad – 41" x 47" x 2"	20

U.S. Patents 6,931,822; 6,927,183; 5,728,458; 5,664,394; 5,268,226; 5,209,968, and patents pending. ICBO PFC-5112.

The Black Pad®



ACP24242

CATALOG NO.	DESCRIPTION	STANDARD PACK
ACP24242	The Black Pad® – 24" x 24" x 2"	24
ACP24243	The Black Pad® – 24" x 24" x 3"	16
ACP24362	The Black Pad® – 24" x 36" x 2"	24
ACP24363	The Black Pad® – 24" x 36" x 3"	16
ACP28383	The Black Pad® – 28" x 38" x 3"	16
ACP30302	The Black Pad® – 30" x 30" x 2"	24
ACP30303	The Black Pad® – 30" x 30" x 3"	16
ACP30363	The Black Pad® – 30" x 36" x 3"	16
ACP32322	The Black Pad® – 32" x 32" x 2"	24
ACP32323	The Black Pad® – 32" x 32" x 3"	16
ACP32442	The Black Pad® – 32" x 44" x 2"	24
ACP32443	The Black Pad® – 32" x 44" x 3"	16
ACP36362	The Black Pad® – 36" x 36" x 2"	24
ACP36363	The Black Pad® – 36" x 36" x 3"	16
ACP36483	The Black Pad® – 36" x 48" x 3"	16
ACP38422	The Black Pad® – 38" x 42" x 2"	24
ACP40403	The Black Pad® – 40" x 40" x 3"	16
ACP45503	The Black Pad® – 45" x 50" x 3"	16
ACP52523	The Black Pad® – 52" x 52" x 3"	15

2" E Lite® Plastic Equipment Pads

E Lite's rugged design provides uniform and generous ribbing for optimum, self-leveling ground support without inserts. The result is a pad that is lightweight, but not too light. A subtle texture prevents unit slide and presents a classic appearance, which is enhanced by rounded edges and a concrete gray color. Each pad is molded with a size label and a symbol representing content of recycled material.



EL2424-2



CATALOG NO.	DESCRIPTION	STANDARD PACK
EL2424-2	E Lite® 2" Equipment Pad – 24" x 24" x 2"	20
EL2430-2	E Lite® 2" Equipment Pad – 24" x 30" x 2"	20
EL2436-2	E Lite® 2" Equipment Pad – 24" x 36" x 2"	20
EL2626-2	E Lite® 2" Equipment Pad – 26" x 26" x 2"	20
EL3030-2	E Lite® 2" Equipment Pad – 30" x 30" x 2"	20
EL3036-2	E Lite® 2" Equipment Pad – 30" x 36" x 2"	20
EL3040-2	E Lite® 2" Equipment Pad – 30" x 40" x 2"	20
EL3232-2	E Lite® 2" Equipment Pad – 32" x 32" x 2"	20
EL3238-2	E Lite® 2" Equipment Pad – 32" x 38" x 2"	20
EL3244-2	E Lite® 2" Equipment Pad – 32" x 44" x 2"	20
EL3434-2	UltraLite® 2" Equipment Pad – 34" x 34" x 2"	20
EL3636-2	UltraLite® 2" Equipment Pad – 36" x 36" x 2"	20
EL3640-2	UltraLite® 2" Equipment Pad – 36" x 40" x 2"	20
UC3648-2	UltraLite® 2" Equipment Pad – 36" x 48" x 2"	20
UC3842-2	UltraLite® 2" Equipment Pad – 38" x 42" x 2"	20

U.S. GENERAL TERMS AND CONDITIONS

General Policy

WE ARE COMMITTED TO DO WHAT IT TAKES TO DELIVER WORLD CLASS SERVICE AND PRODUCTS

All items not ordered in multiples of standard package quantities will automatically be increased to the next standard package quantity. All purchase orders submitted by our customers are assumed as accepting our general terms and conditions as stated herein, any conflicting terms stated on the purchase order cannot supersede our terms.

Order Discrepancies:

All order discrepancies must be reported to us within 5 working days from the date of delivery. Any discrepancies reported after this period cannot be honored.

Terms:

1% 15 days. Net 30 days. Late charges of 1-1/2% per month will be charged following the due date of the invoice. Prices subject to change without notice.

Minimum Order:

\$100.00 minimum order on all original orders. \$15.00 Broken Pallet Charge will be added for each pad size less than the standard pallet quantities.

Freight Policy

CONTINENTAL U.S.

All orders in excess of \$750 will ship prepaid. This policy applies to any combination of DiversiTech, Wagner, and Specialty Chemical products.

Pick Up Allowance

3% of net invoice, 24-hour notice requested. Order must qualify for prepaid freight to receive pick up allowance.

Lost or Damaged Freight

Although we take special care to insure the safe arrival of your merchandise, our responsibility for damages cease when the customer accepts the shipment. To protect your interest, we suggest that you thoroughly inspect all items before accepting delivery. If your order was damaged in shipment or contains a shortage, report the loss or damage AT ONCE to DiversiTech. Any claims for lost or damaged freight must be noted on the Bill of Lading at the time of delivery. If damage is present, you MUST hold the original carton and merchandise for credit by your Sales Representative – otherwise, no claim can be honored.

Returns:

No merchandise will be accepted for return without prior authorization. Call our Customer Service Department to request permission to return goods. Instructions on method of return will be given to you at that time. All returns are subject to a 25% restocking charge.

Warranty Disclaimer

DiversiTech has made a diligent effort to illustrate and describe the products in this catalog accurately; however, such illustrations and descriptions are for the sole purpose of identification, and do not express or imply a warranty that the products are merchantable or fit for a particular purpose, or that the products will necessarily conform to the illustrations or descriptions. DiversiTech assumes no liability for typographical or photographic errors.

DiversiTech reserves the right to make changes in design, material or finish in an effort to improve our products without special notification. If necessary, DiversiTech reserves the right to replace any product shown in catalog with another comparable product without special notification.

DiversiTech's ULTRALITE®, CLADLITE®, and E LITE® Limited Lifetime Warranty

To the original owner of the ULTRALITE®, CLADLITE®, or E LITE® equipment base, DiversiTech warrants the base to be free of defects in materials and workmanship for the life of the equipment under which it is installed so long as the installing homeowner lives there. All defective merchandise must be returned to the factory, transportation prepaid, and if the same is found to be defective, it will be repaired or replaced free of charge, F.O.B. factory. This warranty does not cover replacement labor cost, or any cost claim incident to the defect, replacement, or reinstallation, nor field repair expenses. This warranty gives you specific legal rights and you may also have other rights which vary from state to state. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation of exclusion may not apply to you.

Exclusions and Limitations

DiversiTech's ULTRALITE®, CLADLITE®, and E LITE® equipment pads are designed and manufactured to be used as bases for light, ground supported equipment such as air conditioning condensers, swimming pool filters and heat pumps. Use of ULTRALITE®, CLADLITE®, and E LITE® pads for purposes other than those listed above or improper installation of ULTRALITE®, CLADLITE®, and E LITE® pads may result in pad failure. DiversiTech Corporation disclaims any liability due to such misuse or improper installation. If you have questions concerning the proper installation or use of DiversiTech's ULTRALITE®, CLADLITE®, and E LITE® equipment pads, you should contact our Customer Service Department at 888-261-2978.

DOMESTIC CREDIT APPLICATION

COMPANY NAME: _____

For internal use only

CUSTOMER #: _____

SHIP TO _____ PHONE # _____

ADDRESS _____ FAX # _____

CITY/STATE _____ ZIP CODE _____

E-MAIL _____

BILL TO _____

NAME _____ PHONE # _____

ADDRESS _____ FAX # _____

CITY/STATE _____ ZIP CODE _____

E-MAIL _____

PRINCIPALS**BUYING GROUP MEMBER**

BUSINESS STRUCTURE*: CORPORATION _____ PARTNERSHIP _____ INDIVIDUAL _____ *Please check one

CREDIT LIMIT REQUESTED _____ DUNS # _____

ESTIMATED SALES VOLUME _____ FEDERAL TAX ID # _____

YEARS IN BUSINESS _____

BANK REFERENCE

NAME _____ PHONE # _____

ADDRESS _____ OFFICER _____

CITY/STATE _____ ZIP CODE _____

ACCOUNT # _____

THREE MAJOR TRADE REFERENCES (U.S. based are preferred)

NAME _____ TITLE _____

CONTACT _____ PHONE # _____

CITY/STATE/ZIP _____ FAX # _____

E-MAIL _____ ACCOUNT NUMBER _____

NAME _____ TITLE _____

CONTACT _____ PHONE # _____

CITY/STATE/ZIP _____ FAX # _____

E-MAIL _____ ACCOUNT NUMBER _____

NAME _____ TITLE _____

CONTACT _____ PHONE # _____

CITY/STATE/ZIP _____ FAX # _____

E-MAIL _____ ACCOUNT NUMBER _____

PART NUMBER INDEX

Part #.....Page #	3GR0550.....6	540-6716L.....11	620-18-4P.....15	675-9610.....14	7-P24.....25	D022C.....22	DP402240.....4	FD211C.....19
1714.....29	3GR0555.....6	540-6716R.....11	620-18-5.....15	675-9615.....14	7-P36.....25	D032.....22	DP403120.....4	FD212.....19
1724.....29	3GR0560.....6	540-6900L.....11	620-18-5P.....15	675-9620.....15	7-P36B.....25	D032C.....22	DP40324.....4	FD212C.....19
16491.....29	3GR0580.....6	540-6900R.....11	620-18-6.....15	675-9701.....15	7-P48.....25	D033.....22	DP403240.....4	FD21C.....19
1428646.....24	3GR7530.....6	540-799.....31	620-18-6P.....15	675-9715.....15	7-P48B.....25	D033C.....22	DP503120.....4	FD22.....19
1000-1200.....7	3GR7540.....6	540-800.....31	620-18-7.....15	675-9720.....15	7-RX1019.....30	DOM11.....22	DP50324.....4	FD221.....19
108-130.....7	3GR7555.....6	540-805.....31	620-18-8.....15	6-CT500AV.....30	7-S2C016.....30	DOM11C.....22	DP503240.....4	FD221C.....19
108-130220.....8	3GR7560.....6	540-806.....31	620-18-8P.....15	6-ST600LED.....30	7-S2D016.....30	DOM12.....22	DP603120.....4	FD222.....19
108-130330.....8	3GR7580.....6	540-807.....31	620-18-9.....15	708-850.....29	7-S3C016.....30	DOM12C.....22	DP60324.....4	FD222C.....19
124-156.....7	400-480.....7	540-808.....31	620-20-10.....15	7-100.....27	7-S3D016.....30	DOM22.....22	DP603240.....4	FD22C.....19
124-156220.....8	45020H.....6	540-811.....31	620-20-2.....15	710-182G.....18	7-S4C016.....30	DOM22C.....22	DP753120.....4	FD32.....19
124-156330.....8	45030H.....6	540-AK100.....10	620-20-3.....15	710-185G.....18	7-S4D016.....30	DOM32.....22	DP75324.....4	FD32C.....19
145-175.....7	45040H.....6	540-DB7D.....10	620-20-4.....15	7-10KOTN30.....16	7-S5D016.....30	DOM32C.....22	DP753240.....4	FH22.....23
145-175220.....8	45050H.....6	540-P127.....12	620-20-5.....15	7-10KOTN35.....16	7-S6D016.....30	D10.....5	DP903120.....4	FH22C.....23
145-175330.....8	45060H.....6	540-P127S.....12	620-20-6.....15	7-10KOTN40.....16	7-TLC10625.....16	D11.....5	DP90324.....4	FH32.....23
161-193.....7	45075H.....6	540-R8CCRF.....13	620-20-7.....15	7-10KOTN45.....16	7-TLC10630.....16	D210.....22	DP903240.....4	FH32C.....23
161-193220.....8	45100H.....6	540-RB125W.....13	620-20-8.....15	7-10KOTN50.....16	800-008.....29	D210C.....22	FM0450.....9	FR22.....19
161-193330.....8	45125H.....6	540-RB414M.....13	620-608.....17	7-10KOTN60.....16	800-009.....29	D211.....22	FR22.....19	FR22C.....19
189-227.....7	45150H.....6	540-RB418M.....13	620-6081.....17	7-200.....29	829-995.....7	D211C.....22	FR22C.....19	FTL3.....18
189-227220.....8	45150R.....7	540-RB424M.....13	620-6082.....17	741-001.....32	88-108.....7	D212.....22	FR22C.....19	FTL3D.....18
189-227330.....8	45175H.....6	540-RB610HDM.13	620-6083.....17	741-002.....32	88-108220.....8	D212C.....22	FR22C.....19	FUL0425.....9
200-240.....7	45200H.....6	540-RB614HDM.13	623-000.....25	750-10100.....3	88-108330.....8	D220.....22	FR22C.....19	FUL0625.....9
216-259.....7	45200R.....7	540-RB618HDM.13	623-001.....25	750-12100.....3	ACK4.....18	D220C.....22	FR22C.....19	GC275.....18
216-259220.....8	45250H.....6	540-RB624HDM.13	623-002.....25	750-30F-3PH.....2	ACP24242.....35	D221.....22	FR22C.....19	GC277.....18
216-259330.....8	45250R.....7	540-RB636DW.....13	623-003.....25	750-34100.....3	ACP24243.....35	D221C.....22	FR22C.....19	H211.....22
233-292.....7	45300H.....6	540-RB636W.....13	623-004.....25	750-500.....3	ACP24362.....35	D222.....22	FR22C.....19	H211C.....22
233-292220.....8	45300R.....7	540-RB656WS.....13	623-005.....25	750-600.....3	ACP24363.....35	D222C.....22	FR22C.....19	H211C.....22
270-324.....7	45350H.....6	540-RB810HDM.13	623-006.....25	750-60F-3PH.....2	ACP28383.....35	D232.....22	FR22C.....19	H212.....22
270-324220.....8	45350R.....7	540-RB814HDM.13	623-007.....25	750-60NF-3PH.....2	ACP30302.....35	D232C.....22	FR22C.....19	H212C.....22
270-324330.....8	45400H.....6	540-RB956W.....13	623-008.....25	750-MLT4550.....3	ACP30303.....35	D233.....22	FR22C.....19	H221.....22
324-388.....7	45400R.....7	540-T50M.....13	625-16-6.....16	750-MLT4575.....3	ACP30363.....35	D233C.....22	FR22C.....19	H221C.....22
340-408.....7	45450H.....6	540-T50MOC.....13	625-16-690.....16	750-MLT50.....3	ACP32322.....35	DA1V02.....5	FR22C.....19	H222.....22
37020H.....5	45450R.....7	545-420.....11	626-10S.....17	750-MLT75.....3	ACP32323.....35	DA1V06.....5	FR22C.....19	H222C.....22
37030H.....5	45500H.....6	545-422.....11	626-10T.....17	750-MLT9050.....3	ACP32442.....35	DA1V09.....5	FR22C.....19	H231.....22
37040H.....5	45500R.....7	545-424.....11	626-15.....17	750-MLT9075.....3	ACP32443.....35	DA1V14.....5	FR22C.....19	H231C.....22
37050H.....5	45550H.....6	545-426.....11	626-15S.....17	750-NMLT100.....3	ACP36362.....35	DA22.....22	FR22C.....19	H232.....22
37050HB.....5	45550R.....7	545-430.....11	626-15T.....17	750-NMLT4550.....3	ACP36363.....35	DA2V02.....5	FR22C.....19	H232C.....22
37050R.....6	45600H.....6	545-440.....11	626-20.....17	750-NMLT4575.....3	ACP36483.....35	DA2V06.....5	FR22C.....19	HS012.....20
37060H.....5	45600R.....7	545-442.....11	626-20S.....17	750-NMLT50.....3	ACP38422.....35	DA2V09.....5	FR22C.....19	HS012B.....20
37075H.....5	45700H.....6	545-460.....11	626-20T.....17	750-NMLT75.....3	ACP40403.....35	DA2V14.....5	FR22C.....19	HS03.....20
37075HB.....5	45800H.....6	548-001.....12	626-23233.....17	750-NMLT90100.....3	ACP45503.....35	DA3V02.....5	FR22C.....19	HS03B.....20
37075R.....6	45800R.....7	548-002.....12	626-23333.....17	750-NMLT9050.....3	ACP52523.....35	DA3V06.....5	FR22C.....19	HS04.....20
37100H.....5	460-552.....7	548-003.....12	626-25.....17	750-NMLT9075.....3	B211.....19	DA3V09.....5	FR22C.....19	HS04B.....20
37100HB.....5	41J0525.....6	548-004.....12	626-25S.....17	750-P30F.....2	B211C.....19	DA3V14.....5	FR22C.....19	HS06.....20
37100R.....6	41J0530.....6	548-005.....12	626-25T.....17	750-P60F.....2	B222.....19	DDS-30.....2	FR22C.....19	HS06B.....20
37125H.....5	41J0535.....6	548-006.....12	626-26311.....17	750-P60NF.....2	B222C.....19	DDS-60.....2	FR22C.....19	HS08.....20
37125R.....6	41J0540.....6	548-007.....12	626-30.....17	750-SLTC50.....3	B233.....19	DDS-60U.....2	FR22C.....19	HS08B.....20
37150H.....5	41J0545.....6	548-008.....12	626-30S.....17	750-SLTC75.....3	B233C.....19	DH11.....23	FR22C.....19	HS16.....20
37175H.....5	41J0555.....6	548-009.....12	626-30T.....17	750-SLTC9050.....3	B6-12-4NM.....3	DH11C.....23	FR22C.....19	HS16B.....20
37200H.....5	41J1055.....6	548-010.....12	626-38071.....17	750-SLTC9075.....3	B6-12-6.....3	DH12.....23	FR22C.....19	HS24.....20
37250H.....5	41J7535.....6	56-72.....7	626-38073.....17	755-60F.....2	B6-12-6NM.....3	DH12C.....23	FR22C.....19	HS32.....20
37250R.....6	41J7540.....6	590-708.....7	626-38632.....17	755-60GFCI.....2	B6-34-4.....3	DH21.....23	FR22C.....19	HS32A.....20
37300H.....5	41J7545.....6	5-MSH14MC.....11	626-38636.....17	755-60NF.....2	B6-34-4NM.....3	DH21C.....23	FR22C.....19	HS32B.....20
37300R.....6	41R0525.....7	5-MSH516MC.....11	626-3S.....17	7-5811-B.....24	B6-34-6.....3	DH22.....23	FR22C.....19	HTA2.....23
37350H.....5	41R0530.....7	5-SCR101.....10	626-4S.....17	7-711.....24	B6-34-6NM.....3	DH22C.....23	FR22C.....19	ISO-18.....28
37350R.....6	41R0535.....7	5-SCR101-2.....10	626-5S.....17	7-711-B.....24	BAO2.....19	DH22C.....23	FR22C.....19	ISO-2.....28
37400H.....5	41R0540.....7	5-SCR101-2BULK10	626-6S.....17	7-AD010000.....16	BH11.....23	DH32C.....23	FR22C.....19	ISO-4.....28
37400R.....6	41R0545.....7	5-SCR101BULK.....10	6-34-4.....3	7-AM2A056.....30	BH11C.....23	DHM12.....23	FR22C.....19	LPS-1.....31
37450H.....5	41R0555.....7	5-SCR103-4.....10	6-34-4NM.....3	7-CRNR15.....16	BH22.....23	DHM12C.....23	FR22C.....19	LPS-13.....32
37450R.....6	41R7525.....7	5-SCR103-4BULK10	6-34-6.....3	7-CRNR20.....16	BH22C.....23	DHM21.....23	FR22C.....19	LPS-1G.....31
37500H.....5	41R7530.....7	5-SCR63-8.....10	6-34-6NM.....3	7-CRNR25.....16	BH33.....23	DHM21C.....23	FR22C.....19	LPS-1KB.....33
37500R.....6	41R7535.....7	5-SCR63-8BULK.10	640-122.....3	7-CRNR30.....16	BH33C.....23	DHM22.....23	FR22C.....19	LPS-1KB.....33
37550R.....6	41R7540.....7	5-SCR71-2.....10	640-142.....3	7-CRNR35.....16	BS22.....19	DHM22C.....23	FR22C.....19	LPS-2G.....32
37600H.....5	41R7545.....7	5-SCR71-2BULK.10	650-001.....9	7-CRNR40.....16	C222.....25	DM11.....22	FR22C.....19	LPS-3.....32
37600R.....6	41R7550.....7	5-SCR81.....10	650-002.....9	7-CRNR45.....16	C222C.....25	DM11C.....22	FR22C.....19	LPS-3G.....32
37700H.....5	41R7555.....7	5-SCR81-12.....10	650-003.....9	7-CRNR50.....16	C223.....25	DM12.....22	FR22C.....19	LPS-40.....32
37800H.....5	41R7560.....7	5-SCR81-12BULK10	650-004.....9	7-CRNR60.....16	C223C.....25	DM12C.....22	FR22C.....19	LPS-4-140.....33
37800R.....6	530-30750.....29	5-SCR81-12W.....10	650-005.....9	7-ECC12100.....16	C241.....25	DM21.....22	FR22C.....19	LPS-4CF.....33
378-440.....7	530-30751.....29	5-SCR81-2.....10	650-006.....9	7-ECC1225.....16	C243.....25	DM21C.....22	FR22C.....19	LPS-4NS.....33
3GJ0515.....5	530-30752.....29	5-SCR81-2BULK.10	650-008.....9	7-ECC1250.....16	C245.....25	DM22.....22	FR22C.....19	LPS-4NU.....33
3GJ0520.....5	530-30753.....29	5-SCR81BULK.....10	650-010.....9	7-ECC16100.....16	C247.....25	DM22C.....22	FR22C.....19	LPS-5.....32
3GJ0525.....5	540-12.....13	5-SCR82.....10	650-011.....9	7-ECC1625.....16	C312.....25	DM32.....22	FR22C.....19	LPS-5BC.....32
3GJ0530.....5	540-16.....13	5-SCR82BULK.....10	650-012.....10	7-ECC1650.....16	C312L.....25	DM32C.....22	FR22C.....19	LPS-6.....33
3GJ0535.....5	540-25.....13	5-SCR82W.....10	650-013.....10	7-ECC50725.....16	C512.....25	DMM2.....19	FR22C.....19	LPS-6.....33
3GJ0540.....5	540-25G.....13	5-SCR83-4.....10	650-014.....10	7-ECC50730.....16	C512L.....25	DMM2C.....19	FR22C.....19	LPS-728.....34
3GJ0545.....5	540-25R.....13	5-SCR83-4BULK.10	650-015.....10	7-ECC50735.....16	CC32.....23	DM2120.....4	FR22C.....19	LPS-728A.....34
3GJ1015.....5	540-25UL.....13	5-SCR8K.....10	650-016.....10	7-ECC50755.....16	CC32C.....23	DP252240.....4	FR22C.....19	LPS-7PS.....34
3GJ1025.....5	540-278BM002413	5-SCRMS.....10	650-017.....10	7-KSA036.....30	CO-1.....31	DP25224.....4	FR22C.....19	LPS-7X.....34
3GJ1060.....5	540-278HX0002.13	6-12-4.....3	650-018.....9	7-K3A116.....30	CT800.....24	DP252240.....4	FR22C.....19	LPS-7Z.....34
3GJ1520.....5	540-400.....11	6-12-4NM.....3	650-021.....9	7-L300.....25	CTH1.....18	DP301120.....4	FR22C.....19	LPS-8.....33
3GJ7530.....5	540-500.....11	6-12-6.....3	650-036.....10	7-LK3A001.....24	DP010.....22	DP30124.....4	FR22C.....19	LPS-9.....33
3GJ7535.....5	540-504.....13	6-12-6NM.....3	650-038.....10	7-LM2A001.....30	D010.....22	DP301240.....4	FR22C.....19	MB21.....23
3GJ7555.....5	540-506.....13	620-18-10.....15	675-9400.....14	7-LWSA201.....30	D010C.....22	DP302120.....4	FR22C.....19	MB22.....23
3GR0425.....6	540-508.....13	620-18-12.....15	675-9420.....14	7-LWSA301.....30	D011.....22	DP30224.....4	FR22C.....19	MP-12.....28
3GR0435.....6	540-509.....13	620-18-2.....15	675-9500.....14	7-M2A016.....30	D012.....22	DP303120.....4	FR22C.....19	MP-12E.....28
3GR0525.....6	540-648.....7	620-18-2P.....15	675-9505.....14	7-M2A026.....30	D012C.....22	DP30324.....4	FR22C.....19	MP-18.....28
3GR0530.....6	540-6510L.....11	620-18-3.....15	675-9515.....14	7-M2A036.....30	D021.....22	DP303240.....4	FR22C.....19	MP-18C.....28
3GR0535.....6	540-6510R.....11	620-18-3P.....15	675-9520.....14	7-M3A016.....30	D021C.....22	DP402120.....4	FR22C.....19	MP-18E.....28
3GR0545.....6	540-6716B.....11	620-18-4.....15	675-9600.....14	7-M				

PART NUMBER INDEX cont'd

MP-2C.....28	R214.....21	S022C.....22	UC3636-2.....35
MP-2E.....28	R214C.....21	S030.....22	UC3640-2.....35
MP-3.....28	R215.....21	S030C.....22	UC3648-2.....35
MP-3C.....28	R215C.....21	S031.....22	UC3842-2.....35
MP-3E.....28	R220.....21	S031C.....22	UC4040-2.....35
MP-4.....28	R220C.....21	S032.....22	UC4147-2.....35
MP-4C.....28	R221.....21	S032C.....22	WC02.....25
MP-4E.....28	R221C.....21	S210.....21	WC03.....25
MP-6.....28	R222.....21	S210C.....21	WC04.....25
MP-6C.....28	R222C.....21	S211.....21	WC05.....25
MP-6E.....28	R223.....21	S211C.....21	WC06.....25
MP-8.....28	R223C.....21	S212.....21	WC07.....25
MP-8C.....28	R224.....21	S212C.....21	WC08.....25
PA10.....23	R224C.....21	S220.....21	WC09.....25
PA18.....23	R225.....21	S220C.....21	WC10.....25
PA25.....23	R225C.....21	S221.....21	WC12.....25
PA25AP.....23	R230.....21	S221C.....21	WC14.....25
PK-2.....12	R230C.....21	S222.....21	WC16.....25
PK-2B.....12	R231.....21	S222C.....21	WCA1.....25
PP-16.....28	R231C.....21	S230.....21	WG840463.....27
PP-32.....28	R232.....21	S230C.....21	WG840464.....27
PP-4.....28	R232C.....21	S231.....21	WG840465.....27
PP-8.....28	R233.....21	S231C.....21	WG840466.....27
PW-16.....28	R233C.....21	S232.....21	WG840467.....27
PW-32.....28	R234.....21	S232C.....21	WG840468.....27
PW-4.....28	R234C.....21	SH12.....23	WG840469.....27
PW-8.....28	R235.....21	SH12C.....23	WG840583.....27
RO10.....20	R235C.....21	SH22.....23	WG840584.....27
RO10C.....20	R242.....21	SH22C.....23	WG840585.....27
RO11.....20	R242C.....21	SH32.....23	WG840586.....27
RO11C.....20	R243.....21	SH32C.....23	WG840587.....27
RO12.....20	R243C.....21	SNO10.....20	WG840588.....27
RO12C.....20	R244.....21	SNO10C.....20	WG840589.....27
RO13.....20	R244C.....21	SNO20.....20	WG840590.....27
RO13C.....20	R245.....21	SNO20C.....20	WG840595.....27
RO14.....20	R245C.....21	SN210.....20	WG840596.....27
RO14C.....20	R252.....21	SN210C.....20	WG840727.....27
RO15.....20	R252C.....21	SN220.....20	WG840728.....27
RO15C.....20	R253.....21	SN220C.....20	WG840729.....27
RO20.....20	R253C.....21	Spade.....21	WG840730.....27
RO20C.....20	R254.....21	SS210C.....21	WG840731.....27
RO21.....20	R254C.....21	SS211C.....21	WT04.....24
RO21C.....20	R255.....21	SS212C.....21	WT04C.....24
RO22.....20	R255C.....21	SS220C.....21	WT05.....24
RO22C.....20	R256.....21	SS221C.....21	WT05C.....24
RO23.....20	R256C.....21	SS222C.....21	WT07.....24
RO23C.....20	RH10.....23	SS230C.....21	WT07C.....24
RO24.....20	RH10C.....23	SS231C.....21	WT11.....24
RO24C.....20	RH11.....23	SS232C.....21	WT11C.....24
RO25.....20	RH11C.....23	T1401.....8	WT15.....24
RO25C.....20	RH12.....23	T1403.....8	WT15C.....24
RO30.....20	RH12C.....23	T1404.....8	WTA1.....24
RO30C.....20	RH13.....23	T2401.....8	WTB05.....24
RO31.....20	RH13C.....23	T2402.....8	WTB05C.....24
RO31C.....20	RH20.....23	T2403.....8	WTB07.....24
RO32.....20	RH20C.....23	T2404.....8	WTB07C.....24
RO32C.....20	RH21.....23	T3401.....8	WTB11.....24
RO33.....20	RH21C.....23	T3402.....8	WTB11C.....24
RO33C.....20	RH22.....23	T3403.....8	WTB15.....24
RO34.....20	RH22C.....23	T3501.....8	WTB15C.....24
RO34C.....20	RH23.....23	T4401.....8	WTBA1.....24
RO35.....20	RH23C.....23	T4403.....8	WTM05.....24
RO35C.....20	RH30.....23	T4501.....8	WTM05C.....24
RO42.....20	RH30C.....23	T5401.....9	WTM07.....24
RO42C.....20	RH31.....23	T5402.....9	WTM07C.....24
RO43.....20	RH31C.....23	T5403.....9	WTM1.....24
RO43C.....20	RH32.....23	T5404.....9	WTM11.....24
RO44.....20	RH32C.....23	T6751.....9	WTM11C.....24
RO44C.....20	RH33.....23	T6752.....9	WTM14.....24
RO45.....20	RH33C.....23	T6753.....9	WTM14C.....24
RO45C.....20	RH34.....23	T7751.....9	WTM1C.....24
RO52.....20	RH34C.....23	T7752.....9	WTM2.....24
RO52C.....20	RH35.....23	UC1636-2.....35	WTM2C.....24
RO53.....20	RH35C.....23	UC2424-2.....35	WTM05.....24
RO53C.....20	RH43.....23	UC2430-2.....35	WTM05C.....24
RO54.....20	RH55.....23	UC2436-2.....35	WTMB07.....24
RO54C.....20	RH65.....23	UC2448-2.....35	WTMB07C.....24
RO55.....20	RSA2.....21	UC2626-2.....35	WTMB11.....24
RO55C.....20	S010.....22	UC2628-2.....35	WTMB11C.....24
RO56.....20	S010C.....22	UC2636-2.....35	WTMB14.....24
RO56C.....20	S011.....22	UC3030-2.....35	WTMB14C.....24
R210.....21	S011C.....22	UC3036-2.....35	
R210C.....21	S012.....22	UC3040-2.....35	
R211.....21	S012C.....22	UC3143-2.....35	
R211C.....21	S020.....22	UC3232-2.....35	
R212.....21	S020C.....22	UC3234-2.....35	
R212C.....21	S021.....22	UC3237-2.....35	
R213.....21	S021C.....22	UC3434-2.....35	
R213C.....21	S022.....22	UC3445-2.....35	

ALPHABETICAL INDEX

Aerosol lubricant.....31	Plenum thermostat wire.....15
Anchor.....10	Pliers.....11
AV Pads.....28	Power block.....16
Butt connector.....19	Power supply cords.....16
Cable clamps.....25	Pull A Spout.....31
Capacitors.....5, 6, 7, 8	PVC cement.....28
Caulk gun.....29	PVC pipe cutter.....12
Charles Gallo gun.....26	PVC primer.....28, 29
Circuit tester.....30	PVC solvent.....28, 29
Clamps.....9	Ring terminals.....20
Connectors.....19	Robertshaw®.....14, 15
Contact cleaner.....33	Saw blades.....13
Contactors.....4	Screwdriver.....12
Cutter.....12	Screws.....10
Degreaser.....34	Sealant.....29
Disconnects.....2	Sheet metal screws.....10
Drill bit.....10	Silicone sealant.....29
Dryer clamps.....9	Snips.....11
Dryer vent.....9	Spade terminals.....20
Electrical tape.....18	Staple gun.....13
E-Lite®.....35	Staples.....13
Extension cord.....16	Tape.....13
Flag disconnects.....19	Tape.....18
Flag rings.....19	Terminal assortments.....23
Flashlights.....30	Terminals.....20
Foam sealant.....29	Test leads.....18
Fuse adaptors.....17	The Black Pad®.....35
Fuse block.....17	Thermostat wire.....15
Fuse holder.....17	Thermostats.....14, 15
Fuse puller.....17	Tin snips.....11
Fuses.....16, 17	Tinner snips.....12
Hacksaw.....13	Transformers.....8, 9
Hanging wire.....18	Troublelights.....16
Heat shrink.....20	UltraLite®.....35
Hoods.....9	Vent.....9
Hook terminals.....20	Vent hoods.....9
Kut-All.....12	Voltage monitors.....26
LiquidTite Conduit.....3	Wall anchor.....10
LiquidTite Fittings.....3	Whips.....3
Lubricant.....31	Wire connectors.....25
Mag-Lite.....30	
Magna Lite.....31	
Markers.....31	
Masonry bit.....10	
Mastic.....29	
MC Cable.....3	
Measuring tape.....13	
Motors.....27	
Nut setter.....11	
Nylon wire ties.....24, 25	
Pads.....35	
Paint.....32	
Pigtails.....16	
Pipe cutter.....12	

**WE ARE COMMITTED
TO DO WHAT IT TAKES TO
DELIVER WORLD CLASS
SERVICE AND PRODUCTS.**



6650 Sugarloaf Parkway
Duluth, GA 30097

888.261.2978

678.542.3700 Fax

www.diversitech.com

Download an electronic copy of this catalog at
www.diversitech.com/literature/lit-cat-elec.pdf