



**Johns Manville**

## DUCT WRAPS AND LINERS

MEETS NFPA 90A & B  
CONFORMS TO PERFORMANCE REQUIREMENT ASTM C 1071  
SURFACE BURNING CHARACTERISTICS FHC 25/50

### DUCT WRAPS

STOCK CODE	DESCRIPTION	DENSITY	"R" VALUE
145-0140	UN-FACED 1" X 36" X 100' - CUT 8'	80 LBS	2.7
145-0150	UN-FACED 1" X 36" X 100' -UN-CUT	80 LBS	2.7
145-0155	FOIL-FACED FSK 1-1/2" X 48" X 100'	75 LBS	4.2
145-0160	FOIL-FACED FSK 2" X 48" X 75'	75 LBS	5.7



### PERMACOTE LINACOUSTIC DUCT LINERS

STOCK CODE	DESCRIPTION	DENSITY	"R" VALUE
145-0100	DUCT LINER 1/2" X 47" X 100'	2.0 LBS	2.2
145-0120	DUCT LINER 1" X 46-1/4" X 100'	1.5 LBS	6.3
145-0130	DUCT LINER 1" X 35-1/2" X 100'	1.5 LBS	4.2
145-0105	DUCT LINER 1" X 48" X 100'	1.5 LBS	4.2
145-0110	DUCT LINER 1-1/2" X 47" X 50'	1.5 LBS	6.0



UL Listed  
Classified R3711  
ISO 9002