

DJAL-015Z-TFC-081

HFC, R-404A, 60Hz, 3- Phase, 208/230 V



Availability : Standard US Wholesaler

Mechanical

Unit Height (in):	19.0
Unit Length (in):	25.2
Unit Width (in):	34.0
Ship Weight (lbs):	200.0
Condensor Type:	Air
Copevap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 S
Suction Connection Size (in)/Type:	1-1/8 S
Discharge Line Size (in):	0.500
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	
Oil Recharge Amount (oz):	44

Electrical

Max Fuse Size:	20
Min Circuit Ampacity:	13.9
Compressor:	ZF06K4E-TF5-231
Compressor LRA - Low:	
Compressor LRA - High:	55.0
Compressor LRA - Half winding:	
Compressor RLA:	9.3
UL:	
UL File #:	
UL Guide Card:	
UL Fan Motor FLA Rating Per Motor:	0.6
Fan Motor Quantity:	2

Air Cooled Unit Performance

Release Date:	13-Jan-2006	Return Gas Temp. (°F):	65
Compressor:	ZF06K4E-TF5-231 x 1	Subcooling (°F):	5
Performance No:	7779	Air Flow Rate (CFM)	1680

90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-40	4,750	100.8	10.8	2.6
-35	5,460	101.6	11.6	2.9
-30	6,220	102.4	12.4	3.3
-25	7,020	103.3	13.3	3.6
-20	7,870	104.3	14.3	3.9
-15	8,770	105.4	15.4	4.2
-10	9,730	106.5	16.5	4.5
-5	10,700	107.7	17.7	4.8
0	11,800	109.4	19.4	5.0