

DLAL-0301-TAC-020

HCFC, R-22, 60Hz, 3- Phase, 208/230 V

**Availability :** **Standard US Wholesaler****Mechanical**

Unit Height (in):	18.9
Unit Length (in):	26.2
Unit Width (in):	34.1
Ship Weight (lbs):	0.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 S
Suction Connection Size (in)/Type:	1-1/8 S
Discharge Line Size(in):	0.500
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	MIN
Oil Recharge Amount (oz):	80

Electrical

Max Fuse Size:	20
Min Circuit Ampacity:	19.2
Compressor:	LAHA-0310-TAC-100
Compressor LRA - Low:	
Compressor LRA - High:	82.0
Compressor LRA - Half winding:	
Compressor RLA:	10.7
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	22-Jul-2002	Return Gas Temp. (°F):	65
Compressor:	LAHA-0310-TAC-100 x 1	Subcooling (°F):	5
Performance No:	3959	Air Flow Rate (CFM)	2170

90°F Ambient Air Temperature				
<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-40	5,570	98.2	8.2	2.7
-35	6,930	99.6	9.6	3.1
-30	8,510	101.1	11.1	3.4
-25	10,300	102.9	12.9	3.8
-20	12,300	104.8	14.8	4.2
-15	14,400	106.9	16.9	4.6
-10	16,700	109.0	19.0	4.9
-5	19,100	111.3	21.3	5.2
0	21,500	113.8	23.8	5.5