

# DJAL-022Z-TFC-020

HFC, R-404A, 60Hz, 3- Phase, 208/230 V



**Availability :** Standard US Wholesaler

## Mechanical

Unit Height (in):	19.0
Unit Length (in):	25.2
Unit Width (in):	34.0
Ship Weight (lbs):	205.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 S
Suction Connection Size (in)/Type:	1-1/8 S
Discharge Line Size(in):	0.500
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	49

## Electrical

Max Fuse Size:	20
Min Circuit Ampacity:	16.2
Compressor:	ZF09K4E-TF5-231
Compressor LRA - Low:	
Compressor LRA - High:	77.0
Compressor LRA - Half winding:	
Compressor RLA:	11.1
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	0.6
Fan Motor Quantity:	2

## Air - Cooled Unit Performance

Release Date:	04-Oct-2002	Return Gas Temp. (°F):	65
Compressor:	ZF09K4E-TF5-231 x 1	Subcooling (°F):	5
Performance No:	5771	Air Flow Rate (CFM)	1680

### 90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-40	6,680	103.0	13.0	3.1
-35	7,580	103.9	13.9	3.4
-30	8,540	105.0	15.0	3.8
-25	9,560	106.1	16.1	4.1
-20	10,600	107.3	17.3	4.5
-15	11,800	108.7	18.7	4.8
-10	13,000	110.0	20.0	5.2
-5	14,300	111.5	21.5	5.5
0	15,600	113.4	23.4	5.8