

# FPAK-015Z-CFV-072

HFC, R-134a, 60Hz, 1- Phase, 208/230 V



**Availability :** Standard US Wholesaler

## Mechanical

Unit Height (in):	16.6
Unit Length (in):	24.1
Unit Width (in):	18.3
Ship Weight (lbs):	112.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 S
Suction Connection Size (in)/Type:	7/8 S
Discharge Line Size(in):	0.375
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	25

## Electrical

Max Fuse Size:	40
Min Circuit Ampacity:	23.9
Compressor:	ZS19KAE-PFV-118
Compressor LRA - Low:	
Compressor LRA - High:	75.0
Compressor LRA - Half winding:	
Compressor RLA:	18.0
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	
Fan Motor Quantity:	1

## Air - Cooled Unit Performance

Release Date:	26-Jul-2013	Return Gas Temp. (°F):	40
Compressor:	ZS19KAE-PFV-118 x 1	Subcooling (°F):	5
Performance No:	8905	Air Flow Rate (CFM)	1070

### 90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
0	7,410	108.0	18.0	5.3
5	8,330	109.7	19.7	5.7
10	9,310	111.5	21.5	6.2
15	10,300	113.4	23.4	6.6
20	11,500	115.5	25.5	7.1
25	12,600	117.6	27.6	7.5