

FFAP-040Z-CFV-071

HFC, R-134a, 60Hz, 1- Phase, 208/230 V



Availability : Standard US Wholesaler

Mechanical

Unit Height (in):	26.8
Unit Length (in):	28.2
Unit Width (in):	44.1
Ship Weight (lbs):	322.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	1/2 S
Suction Connection Size (in)/Type:	1-1/8 S
Discharge Line Size(in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	42

Electrical

Max Fuse Size:	50
Min Circuit Ampacity:	33.1
Compressor:	ZS26KAE-PFV-118
Compressor LRA - Low:	
Compressor LRA - High:	104.0
Compressor LRA - Half winding:	
Compressor RLA:	23.6
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	1.5
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	05-Jun-2012	Return Gas Temp. (°F):	40
Compressor:	ZS26KAE-PFV-118 x 1	Subcooling (°F):	5
Performance No:	8421	Air Flow Rate (CFM)	4240

90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
0	11,800	98.3	8.3	5.8
5	13,400	98.9	8.9	6.4
10	15,100	99.6	9.6	7.1
15	16,900	100.4	10.4	7.7
20	18,900	101.2	11.2	8.5
25	21,000	102.1	12.1	9.2