

# FJAM-A150-TFC-020

HFC, R-507, 60Hz, 3- Phase, 208/230 V



**Availability :** Standard US Wholesaler

## Mechanical

Unit Height (in):	16.2
Unit Length (in):	24.0
Unit Width (in):	18.3
Ship Weight (lbs):	133.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 S
Suction Connection Size (in)/Type:	7/8 S
Discharge Line Size(in):	0.375
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	45

## Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	12.2
Compressor:	CS10K6E-TF5-256
Compressor LRA - Low:	
Compressor LRA - High:	51.0
Compressor LRA - Half winding:	
Compressor RLA:	8.1
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	
Fan Motor Quantity:	1

## Air - Cooled Unit Performance

Release Date:	31-May-2002	Return Gas Temp. (°F):	40
Compressor:	CS10K6E-TF5-256 x 1	Subcooling (°F):	5
Performance No:	3744	Air Flow Rate (CFM)	1070

### 90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-5	5,880	106.3	16.3	4.3
0	6,860	108.7	18.7	4.7
5	8,000	110.3	20.3	5.1
10	9,100	112.4	22.4	5.4
15	10,200	114.4	24.4	5.8
20	11,400	116.4	26.4	6.1
25	12,500	118.4	28.4	6.4