

EBAM-A050-IAA-020

CFC, R-12, 60Hz, 1- Phase, 115 V



Availability : Standard US Wholesaler

Mechanical

Unit Height (in):	12.1
Unit Length (in):	19.5
Unit Width (in):	16.3
Ship Weight (lbs):	112.0
Condensor Type:	Air
Copevap Water Storage:	NA
Liquid Connection Size (in)/Type:	1/4 F
Suction Connection Size (in)/Type:	1/2 F
Discharge Line Size (in):	0.250
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	MIN
Oil Recharge Amount (oz):	22

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	10.9
Compressor:	KAE2-0050-IAA-100
Compressor LRA - Low:	
Compressor LRA - High:	45.0
Compressor LRA - Half winding:	
Compressor RLA:	7.8
UL:	
UL File #:	
UL Guide Card:	
UL Fan Motor FLA Rating Per Motor:	0.58
Fan Motor Quantity:	1

Air Cooled Unit Performance

Release Date:	20-Jul-2002	Return Gas Temp. (°F):	65
Compressor:	KAE2-0050-IAA-100 x 1	Subcooling (°F):	5
Performance No:	3883	Air Flow Rate (CFM)	330

90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-5	2,410	101.2	11.2	4.2
0	2,760	102.7	12.7	4.6
5	3,120	104.5	14.5	5.0
10	3,480	106.3	16.3	5.4
15	3,880	108.2	18.2	5.6
20	4,290	110.1	20.1	5.9
25	4,740	112.2	22.2	6.2