

FJAM-A200-TFC-020

HFC, R-507, 60Hz, 3- Phase, 208/230 V



Availability : **Obsolete**

Mechanical

Unit Height (in):	19.0
Unit Length (in):	25.2
Unit Width (in):	34.0
Ship Weight (lbs):	190.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 S
Suction Connection Size (in)/Type:	7/8 S
Discharge Line Size(in):	0.375
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	45

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	11.7
Compressor:	CS12K6E-TF5-256
Compressor LRA - Low:	
Compressor LRA - High:	51.0
Compressor LRA - Half winding:	
Compressor RLA:	8.6
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	0.6
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	31-May-2002	Return Gas Temp. (°F):	40
Compressor:	CS12K6E-TF5-256 x 1	Subcooling (°F):	5
Performance No:	3746	Air Flow Rate (CFM)	1680

90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-5	7,540	103.7	13.7	4.7
0	8,770	105.4	15.4	5.1
5	10,200	106.7	16.7	5.5
10	11,600	108.3	18.3	5.9
15	13,000	110.0	20.0	6.3
20	14,500	111.7	21.7	6.7
25	16,100	113.5	23.5	7.1