

4DR3R28M0-FSD

HCFC, R-22, 60Hz, 3- Phase, 460 V
Air Conditioning



Production Status: This compressor and/or application of this compressor is not available to U.S. OEM customers. A field replacement is currently available through a U.S. Emerson Climate Technologies Wholesaler. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	45 / 130	35 / 105
RG(°F)/Liq(°F)	65.0 / 115.0	55.0 / 90.0
Capacity (Btu/hr)	318000	308000
Power (Watts):	29100	22500
Current (Amps):	44.10	36.20
EER (Btu/Wh):	10.90	13.70
Mass Flow (lbs/hr):	4660	4100
Sound Power (dBA):		
Vibration (mils(peak-peak)):		2.33 Max
Record Date:	2007-06-12	

Mechanical

Number of Cylinders:	4	Displ(in ³ /Rev):	59.33
Bore Size(in):	2.94	Displ(ft ³ /hr):	3605.24
Stroke(in):	2.19		
Overall Length (in):	27.03	Mounting Length (in):	15.00
Overall Width (in):	20.38	Mounting Width (in):	12.00
Overall Height (in):	17.91	Mounting Height (in):	19.19 *
Suction Size (in):		2 1/8 Sweat	
Discharge Size (in):		1 3/8 Sweat	
Oil Recharge (oz):		125	
Initial Oil Charge (oz):		135	
Net Weight (lbs):		450	
Internal Free Volume (in ³):			
Horse Power:		25	
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	235.0	MCC (Amps):	63.0	UL File No:	SA-2337
LRA-Half Winding:	141.0	RPM:	3500	UL File Date:	07-Apr-1971
LRA Low*:		Max Operating Current:			
RLA(=MCC/1.4;use for contactor selection):		45			
RLA(=MCC/1.56;use for breaker & wire size selection):		40.4			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-22 HCFC	50	3	380/420	Air Conditioning
R-22 HCFC	50	3	380/420	Medium Temp, Low Condensing
R-502 CFC	50	3	380/420	Medium Temperature
R-22 HCFC	60	3	460	Medium Temp, Low Condensing
R-502 CFC	60	3	460	Medium Temperature