

FPAK-039Z-TFC-071

HFC, R-134a, 60Hz, 3- Phase, 208/230 V



Availability : Standard US Wholesaler

Mechanical

Unit Height (in):	19.0
Unit Length (in):	25.2
Unit Width (in):	34.1
Ship Weight (lbs):	220.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 S
Suction Connection Size (in)/Type:	7/8 S
Discharge Line Size(in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	42

Electrical

Max Fuse Size:	45
Min Circuit Ampacity:	28.4
Compressor:	ZS29KAE-TF5-118
Compressor LRA - Low:	
Compressor LRA - High:	114.0
Compressor LRA - Half winding:	
Compressor RLA:	20.5
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	26-Jul-2013	Return Gas Temp. (°F):	40
Compressor:	ZS29KAE-TF5-118 x 1	Subcooling (°F):	5
Performance No:	8909	Air Flow Rate (CFM)	2170

90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
0	11,300	103.5	13.5	5.9
5	12,800	104.8	14.8	6.5
10	14,300	106.2	16.2	7.0
15	16,000	107.7	17.7	7.6
20	17,800	109.3	19.3	8.2
25	19,700	110.9	20.9	8.9