

ZR57K3E-TF5

HCFC, R-22, 60Hz, 3- Phase, 200/230 V

Air Conditioning



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	45 / 130	45 / 100
RG(°F)/Liq(°F)	65.0 / 115.0	65.0 / 85.0
Capacity (Btu/hr)	58500	68500
Power (Watts):	4980	3430
Current (Amps):	14.50	11.10
EER (Btu/Wh):	11.70	20.00
Mass Flow (lbs/hr):	860	880
Sound Power (dBA):	74 Avg	79 Max
Vibration (mils(peak-peak)):	2.0 Avg	3.0 Max
Record Date:	2014-03-06	

Mechanical

Number of Cylinders:	0	Displ(in ³ /Rev):	4.71
Bore Size(in):	0.00	Displ(ft ³ /hr):	572.40
Stroke(in):	0.00		
Overall Length (in):	9.69	Mounting Length (in):	7.50
Overall Width (in):	9.69	Mounting Width (in):	7.50
Overall Height (in):	17.24	Mounting Height (in):	17.99 *
Suction Size (in):		7/8 Stub	
Discharge Size (in):		1/2 Stub	
Oil Recharge (oz):		62	
Initial Oil Charge (oz):		66	
Net Weight (lbs):		85	
Internal Free Volume (in ³):		257.0	
Horse Power:		4.75	
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	123.0	MCC (Amps):	27.0	UL File No:	SA-2337
LRA-Half Winding:		RPM:	3500	UL File Date:	26-Jul-1993
LRA Low*:		Max Operating Current:	18.0		
RLA(=MCC/1.4;use for contactor selection):		19.3			
RLA(=MCC/1.56;use for breaker & wire size selection):		17.3			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-407C HFC	50	3	200/220	Air Conditioning
R-22 HCFC	50	3	200/220	Air Conditioning
R-407C HFC	60	3	200/230	Air Conditioning