

Klixon Pressure Switches

MARS SERIES **333**



KLIXON



43341

Fixed Setting Pressure Controls

Low pressure controls.

Specifications:

- Contacts rated at 6 amps, 24-240 volts
- 18" leads

Features:

- Tamper proof construction
- Direct mounting on tubing
- UL & CSA recognized

The 4 - Series Klixon Pressure Switches. This newest set of designs delivers the reliability and performance that has made Klixon the most trusted name in the electromechanical sensor business. The 4 - Series line of pressure switches covers many new R410A applications along with traditional pressure setting switches.

Klixon Brand, UL and CUL, Compact size, light weight for direct mounting, Factory Set, Hermetically Sealed Sensor.

5.8 FLA - 34.8 LRA @ 120 VAC, 2.9 FLA - 15.0 LRA @ 240 VAC, 100,000 Cycle Life at Rated Current.

Low Pressure Cut-Out - Open on Pressure Drop, Automatic Reset Normally Open

3 SERIES MARS NO.	4 SERIES MARS NO.	CUT OUT	CUT IN	NOTES
33329	43341	5	20	1/4" Female Flare S.A.E. Mounting
	43342	5	30	1/4" Female Flare S.A.E. Mounting
33330	43343	10	25	1/4" Female Flare S.A.E. Mounting
33333	43344	15	35	1/4" Female Flare S.A.E. Mounting
	43371	15	40	1/4" Copper Clad SS Tube, 90 degree elbow w/36" leads
	43345	20	45	1/4" Female Flare S.A.E. Mounting
	43372	22	50	1/4" Copper Clad SS Tube w/38" leads
	43373	25	40	Gold Contacts 1/4" Female Flare w/36" leads
33362	43346	25	50	1/4" Female Flare S.A.E. Mounting
33336	43347	25	65	1/4" Female Flare S.A.E. Mounting
33363	43348	25	80	1/4" Female Flare S.A.E. Mounting
	43349	35	60	1/4" Female Flare S.A.E. Mounting
33364	43350	40	80	1/4" Female Flare S.A.E. Mounting
	43351	45	60	1/4" Female Flare S.A.E. Mounting
33339	43352	50	90	1/4" Female Flare S.A.E. Mounting
	43374	50	95	1/4" Copper Clad SS Tube w/36" leads
33342	43353	75	100	1/4" Female Flare S.A.E. Mounting
	43375	90	120	1/4" Female Flare, w/18" leads
	43354	150	225	1/4" Female Flare S.A.E. Mounting
	43355	170	250	1/4" Female Flare S.A.E. Mounting
	43361	165	215	1/4" Female Flare S.A.E. Mounting w/Quick Connects
	43362	200	240	1/4" Female Flare S.A.E. Mounting w/Quick Connects, SPDT