## ZR68KCE-TF5

HFC, R-407C, 60Hz, 3- Phase, 200/230 V Air Conditioning



## Production Status:

Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

| Performance                  |              |             |   | Mechanical |                          |           |  |
|------------------------------|--------------|-------------|---|------------|--------------------------|-----------|--|
| Evap(°F)/Cond(°F)            | 45 / 130     | 45 / 100    | Number of Cylinders:                        | 0          | Displ(in^3/Rev):         | 5.68      |  |
|                              |              |             | Bore Size(in):                              | 0.00       | Displ(ft^3/hr):          | 689.79    |  |
| RG(°F)/Liq(°F)               | 65.0 / 115.0 | 65.0 / 85.0 | Stroke(in):                                 | 0.00       |                          |           |  |
| Capacity                     | 68600        | 82000       |   |            |                          |           |  |
| (Btu/hr)<br>Power (Watts):   | 6040         | 4270        | Overall Length (in):                        | 9.69       | Mounting Length (in):    | 7.50      |  |
| Current (Amps):              | 17.55        | 13.75       | Overall Width (in):                         | 9.69       | Mounting Width (in):     | 7.50      |  |
| EER (Btu/Wh):                | 11.35        | 19.20       | Overall Height (in):                        | 17.75      | Mounting Height (in):    | 18.00     |  |
| Mass Flow (lbs/hr):          | 991          | 1010        |   |            |                          |           |  |
|                              |              |             | Suction Size (in):                          |            | 7/8 Stub                 |           |  |
| Sound Power (dBA):           | 75 Avg       | 80 Max      | Discharge Size (in):                        |            | 1/2 Stub                 |           |  |
| Vibration (mils(peak-peak)): | 2.0 Avg      | 3.0 Max     | Oil Recharge (oz):                          |            | 56                       |           |  |
|                              |              |             | Initial Oil Charge (oz):                    |            | 60                       |           |  |
| Record Date:                 | 2014-08-05   |             | Net Weight (lbs):                           |            | 86                       |           |  |
|                              |              |             | Internal Free Volume                        | (in^3):    | 362.0                    |           |  |
|                              |              |             | Horse Power:                                |            | 5.5                      |           |  |
|                              |              |             | *Overall compressor h<br>mounting grommets. | neight on  | Copeland Brand Product's | specified |  |

## Electrical

|                                  |                 | Elocation                          |                 |               |             |
|----------------------------------|-----------------|------------------------------------|-----------------|---------------|-------------|
| LRA-High*:                       | 156.0           | MCC (Amps):                        | 29.0            | UL File No:   | SA-2337     |
| LRA-Half Winding:                |                 | RPM:                               | 3500            | UL File Date: | 26-Jul-1993 |
| LRA Low*:                        |                 | Max Operating Current:             | 25.0            |               |             |
| RLA(=MCC/1.4;use for contacto    | r selection):   | 20.7                               |                 |               |             |
| RLA(=MCC/1.56;use for breaker    | r & wire size s | election): 18.6                    |                 |               |             |
| *Low and High refer to the low a | nd high nomir   | nal voltage ranges for which the m | otor is approve | ed.           |             |
|                                  |                 |                                    |                 |               |             |

| Alternate Applications |           |       |         |                  |  |  |  |  |
|------------------------|-----------|-------|---------|------------------|--|--|--|--|
| Refrigerant            | Freq (Hz) | Phase | Voltage | Application      |  |  |  |  |
| R-22 HCFC              | 50        | 3     | 200/220 | Air Conditioning |  |  |  |  |
| R-407C HFC             | 50        | 3     | 200/220 | Air Conditioning |  |  |  |  |
| R-22 HCFC              | 60        | 3     | 200/230 | Air Conditioning |  |  |  |  |