

FPAK-012Z-TFC-072

HFC, R-134a, 60Hz, 3- Phase, 208/230 V



Availability : Standard US Wholesaler

Mechanical

Unit Height (in):	16.6
Unit Length (in):	24.0
Unit Width (in):	17.1
Ship Weight (lbs):	104.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 S
Suction Connection Size (in)/Type:	5/8 S
Discharge Line Size(in):	0.375
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	25

Electrical

Max Fuse Size:	20
Min Circuit Ampacity:	14.2
Compressor:	ZS11KAE-TF5-118
Compressor LRA - Low:	
Compressor LRA - High:	58.0
Compressor LRA - Half winding:	
Compressor RLA:	10.4
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	0.85
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	26-Jul-2013	Return Gas Temp. (°F):	40
Compressor:	ZS11KAE-TF5-118 x 1	Subcooling (°F):	5
Performance No:	8901	Air Flow Rate (CFM)	650

90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
0	4,730	109.7	19.7	5.1
5	5,300	111.6	21.6	5.5
10	5,920	113.6	23.6	5.9
15	6,560	115.7	25.7	6.2
20	7,250	117.9	27.9	6.7
25	7,980	120.2	30.2	7.1