

CR47KQE-TF5

HCFC, R-22, 60Hz, 3- Phase, 200/230 V

Air Conditioning



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	45 / 130	45 / 100
RG(°F)/Liq(°F)	65.0 / 115.0	65.0 / 85.0
Capacity (Btu/hr)	47200	60500
Power (Watts):	4540	3720
Current (Amps):	13.70	11.90
EER (Btu/Wh):	10.40	16.30
Mass Flow (lbs/hr):	690	780
Sound Power (dBA):	78 Avg	83 Max
Vibration (mils(peak-peak)):	4.0 Avg	5.0 Max
Record Date:	2014-03-06	

Mechanical

Number of Cylinders:	2	Displ(in ³ /Rev):	4.95
Bore Size(in):	1.96	Displ(ft ³ /hr):	602.06
Stroke(in):	0.82		
Overall Length (in):	10.38	Mounting Length (in):	7.50
Overall Width (in):	9.09	Mounting Width (in):	7.50
Overall Height (in):	14.81	Mounting Height (in):	15.19 *
Suction Size (in):	7/8 Stub		
Discharge Size (in):	1/2 Stub		
Oil Recharge (oz):	43		
Initial Oil Charge (oz):	45		
Net Weight (lbs):	77		
Internal Free Volume (in ³):			
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	97.0	MCC (Amps):	22.5	UL File No:
LRA-Half Winding:		RPM:	3500	UL File Date:
LRA Low*:		Max Operating Current:		
RLA(=MCC/1.4;use for contactor selection):		16.1		
RLA(=MCC/1.56;use for breaker & wire size selection):		14.4		
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.				

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-22 HCFC	50	3	200/240	High Temp
R-22 HCFC	60	3	200/230	High Temp
R-407C HFC	60	3	200/230	Air Conditioning
R-22 HCFC	50	3	200/240	Air Conditioning
R-407C HFC	50	3	200/240	Air Conditioning