

# FFAP-022Z-CFV-071

HFC, R-134a, 60Hz, 1- Phase, 208/230 V



**Availability :** Standard US Wholesaler

## Mechanical

Unit Height (in):	19.0
Unit Length (in):	25.2
Unit Width (in):	34.1
Ship Weight (lbs):	194.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 S
Suction Connection Size (in)/Type:	7/8 S
Discharge Line Size(in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	25

## Electrical

Max Fuse Size:	35
Min Circuit Ampacity:	22.4
Compressor:	ZS15KAE-PFV-118
Compressor LRA - Low:	
Compressor LRA - High:	68.0
Compressor LRA - Half winding:	
Compressor RLA:	15.7
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	
Fan Motor Quantity:	2

## Air - Cooled Unit Performance

Release Date:	30-Jan-2015	Return Gas Temp. (°F):	40
Compressor:	ZS15KAE-PFV-118 x 1	Subcooling (°F):	5
Performance No:	9228	Air Flow Rate (CFM)	2170

### 90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
0	6,850	102.9	12.9	4.8
5	7,730	104.1	14.1	5.2
10	8,680	105.4	15.4	5.7
15	9,690	106.8	16.8	6.2
20	10,800	108.3	18.3	6.8
25	12,000	109.8	19.8	7.3