

ZRD72KCE-TF5

HFC, R-407C, 60Hz, 3- Phase, 200/230 V

Air Conditioning



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	45 / 130	45 / 100
RG(°F)/Liq(°F)	65.0 / 115.0	65.0 / 85.0
Capacity (Btu/hr)	70500	86000
Power (Watts):	6550	4790
Current (Amps):	19.00	14.90
EER (Btu/Wh):	10.80	18.00
Mass Flow (lbs/hr):	1030	1070
Sound Power (dBA):	74 Avg	79 Max
Vibration (mils(peak-peak)):	2.0 Avg	3.0 Max
Record Date:	2012-10-08	

Mechanical

Number of Cylinders:	0	Displ(in ³ /Rev):	5.98
Bore Size(in):	0.00	Displ(ft ³ /hr):	727.10
Stroke(in):	0.00		
Overall Length (in):	9.69	Mounting Length (in):	7.50
Overall Width (in):	9.69	Mounting Width (in):	7.50
Overall Height (in):	19.46	Mounting Height (in):	19.71 *
Suction Size (in):		7/8 Stub	
Discharge Size (in):		3/4 Stub	
Oil Recharge (oz):		60	
Initial Oil Charge (oz):		64	
Net Weight (lbs):		88	
Internal Free Volume (in ³):		362.0	
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	156.0	MCC (Amps):	29.0	UL File No:
LRA-Half Winding:		RPM:	3500	UL File Date:
LRA Low*:		Max Operating Current:	22.7	
RLA(=MCC/1.4;use for contactor selection):		20.7		
RLA(=MCC/1.56;use for breaker & wire size selection):		18.6		
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.				

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-407C HFC	60	3	200/230	A/C, 50% Load Of Compressor
R-407C HFC	50	3	200/220	A/C, 50% Load Of Compressor
R-22 HCFC	50	3	200/220	
R-407C HFC	50	3	200/220	Air Conditioning
R-22 HCFC	60	3	200/230	