

# W2WH-0075-TAC-001

HCFC, R-22, 60Hz, 3- Phase, 208/230 V

**Availability :** Standard US Wholesaler

## Mechanical

Unit Height (in):	17.5
Unit Length (in):	27.3
Unit Width (in):	14.5
Ship Weight (lbs):	166.0
Condensor Type:	Water
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 S
Suction Connection Size (in)/Type:	5/8 S
Discharge Line Size(in):	0.38
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	MIN
Oil Recharge Amount (oz):	22

## Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	4.4
Compressor:	KWN1-0075-TAC-100
Compressor LRA - Low:	
Compressor LRA - High:	19.9
Compressor LRA -	
Compressor RLA:	3.5
Elect Application	1
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	
Fan Motor Quantity:	1.00

## Water- Cooled Unit Performance

Release Date:	23-Oct-2002	Return Gas Temp. (°F):	65
Compressor:	KWN1-0075-TAC-100 x 1	Subcooling (°F):	5
Performance No:	6210	Condenser Water Inlet Temp.(°F)	85.0
		Water Temp Diff.(°F)	10

  

105°F Condensing Temperature			
<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond Water</u> <u>(gal/min)</u>	<u>(psi)</u>
0	3,450	1.1	
5	3,980	1.2	
10	4,570	1.3	
15	5,230	1.5	
20	5,960	1.5	
25	6,750	1.7	
30	7,610	1.9	
35	8,550	2.1	
40	9,570	2.3	
45	10,700	2.5	