

# ZR72KC-TF7

HCFC, R-22, 60Hz, 3- Phase, 380 V  
Air Conditioning



**Production Status:** Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

## Performance

Evap(°F)/Cond(°F)	45 / 130	45 / 100
RG(°F)/Liq(°F)	65.0 / 115.0	65.0 / 85.0
Capacity (Btu/hr)	73500	86000
Power (Watts):	6250	4460
Current (Amps):	10.50	7.80
EER (Btu/Wh):	11.70	19.30
Mass Flow (lbs/hr):	1080	1110
Sound Power (dBA):	75 Avg	80 Max
Vibration (mils(peak-peak)):	2.0 Avg	3.0 Max
Record Date:	2004-03-11	

## Mechanical

Number of Cylinders:	0	Displ(in <sup>3</sup> /Rev):	5.98
Bore Size(in):	0.00	Displ(ft <sup>3</sup> /hr):	727.10
Stroke(in):	0.00		
Overall Length (in):	9.69	Mounting Length (in):	7.50
Overall Width (in):	9.69	Mounting Width (in):	7.50
Overall Height (in):	17.75	Mounting Height (in):	18.00 *
Suction Size (in):		7/8 Stub	
Discharge Size (in):		1/2 Stub	
Oil Recharge (oz):		56	
Initial Oil Charge (oz):		60	
Net Weight (lbs):		85	
Internal Free Volume (in <sup>3</sup> ):		248.0	
Horse Power:		6	
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

## Electrical

LRA-High*:	70.0	MCC (Amps):	15.0	UL File No:	SA-2337
LRA-Half Winding:		RPM:	3500	UL File Date:	26-Jul-1993
LRA Low*:		Max Operating Current:	14.0		
RLA(=MCC/1.4;use for contactor selection):		10.7			
RLA(=MCC/1.56;use for breaker & wire size selection):		9.6			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

## Alternate Applications

<u>Refrigerant</u>	<u>Freq (Hz)</u>	<u>Phase</u>	<u>Voltage</u>	<u>Application</u>
--------------------	------------------	--------------	----------------	--------------------