

KWKB-020A-CAV

HCFC, R-22, 60Hz, 1- Phase, 208/230 V
High Temp



Production Status: This model is obsolete and is no longer in production for both OEM and service replacement. Please contact Customer Service about possible replacement models.

Performance

Evap(°F)/Cond(°F)	45 / 130	20 / 120
RG(°F)/Liq(°F)	65.0 / 130.0	65.0 / 120.0
Capacity (Btu/hr)	21800	13500
Power (Watts):	2290	1840
Current (Amps):	11.00	9.00
EER (Btu/Wh):	9.50	7.30
Mass Flow (lbs/hr):	344	197
Sound Power (dBA):		
Vibration (mils(peak-peak)):		4.76 Max
Record Date:	2007-01-03	

Mechanical

Number of Cylinders:	2	Displ(in ³ /Rev):	4.20
Bore Size(in):	1.69	Displ(ft ³ /hr):	255.09
Stroke(in):	0.94		
Overall Length (in):	14.38	Mounting Length (in):	8.19
Overall Width (in):	9.50	Mounting Width (in):	6.38
Overall Height (in):	10.44	Mounting Height (in):	11.19 *
Suction Size (in):		7/8 Sweat	
Discharge Size (in):		1/2 Flare	
Oil Recharge (oz):		20	
Initial Oil Charge (oz):		22	
Net Weight (lbs):		92	
Internal Free Volume (in ³):			
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	55.0	MCC (Amps):	14.8	UL File No:	SA-2337
LRA-Half Winding:		RPM:	3500	UL File Date:	23-Jul-1984
LRA Low*:		Max Operating Current:			
RLA(=MCC/1.4;use for contactor selection):		10.6			
RLA(=MCC/1.56;use for breaker & wire size selection):		9.5			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					
Type	Part No	Low MFD	High MFD	Volts	User Description
Start Capacitor	014-0061-30	130.0	156.0	330	SPECIAL CUST.
Run Capacitor	014-0064-19	25.0	0.0	482	

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-12 CFC	50	1	200/220	
R-22 HCFC	50	1	200/220	Low Temperature
R-22 HCFC	50	1	200/220	High Temp
R-22 HCFC	50	1	200/220	Medium Temperature
R-502 CFC	50	1	200/220	
R-12 CFC	60	1	208/230	
R-22 HCFC	60	1	208/230	Low Temperature
R-22 HCFC	60	1	208/230	Medium Temperature
R-502 CFC	60	1	208/230	