

# RRT10K1-PFV

CFC, R-12, 60Hz, 1- Phase, 208/230 V  
High Temp



**Production Status:** This compressor and/or application of this compressor is not available to U.S. OEM customers. A field replacement is currently available through a U.S. Emerson Climate Technologies Wholesaler. Please check with your local Emerson Climate Technologies Representative for international availability.

## Performance

|                              |              |              |
|------------------------------|--------------|--------------|
| Evap(°F)/Cond(°F)            | 45 / 130     | 20 / 120     |
| RG(°F)/Liq(°F)               | 65.0 / 130.0 | 65.0 / 120.0 |
| Capacity (Btu/hr)            | 10600        | 6860         |
| Power (Watts):               | 1260         | 932          |
| Current (Amps):              | 6.30         | 5.00         |
| EER (Btu/Wh):                | 8.40         | 7.40         |
| Mass Flow (lbs/hr):          | 228          | 137          |
| Sound Power (dBA):           | 0 Avg        | 0 Max        |
| Vibration (mils(peak-peak)): | 0.0 Avg      | 0.0 Max      |
| Record Date:                 | 2012-05-21   |              |

## Mechanical

|   |          |                              |         |
|---|----------|------------------------------|---------|
| Number of Cylinders:  | 1        | Displ(in <sup>3</sup> /Rev): | 1.70    |
| Bore Size(in):  | 1.50     | Displ(ft <sup>3</sup> /hr):  | 206.38  |
| Stroke(in):   | 0.96     |                              |         |
| Overall Length (in):  | 10.30    | Mounting Length (in):        | 8.00    |
| Overall Width (in):   | 7.10     | Mounting Width (in):         | 4.80    |
| Overall Height (in):  | 9.80     | Mounting Height (in):        | 10.40 * |
| Suction Size (in):  | 1/2 Stub |                              |         |
| Discharge Size (in):  | 3/8 Stub |                              |         |
| Oil Recharge (oz):  | 20       |                              |         |
| Initial Oil Charge (oz):  | 22       |                              |         |
| Net Weight (lbs):   | 39.2     |                              |         |
| Internal Free Volume (in <sup>3</sup> ):  |          |                              |         |
| Horse Power:  |          |                              |         |
| *Overall compressor height on Copeland Brand Product's specified mounting grommets. |          |                              |         |

## Electrical

|   |             |                        |          |               |                  |
|---|-------------|------------------------|----------|---------------|------------------|
| LRA-High*:  | 46.0        | MCC (Amps):            | 11.2     | UL File No:   |                  |
| LRA-Half Winding:   |             | RPM:                   | 3500     | UL File Date: |                  |
| LRA Low*:   |             | Max Operating Current: |          |               |                  |
| RLA(=MCC/1.4;use for contactor selection):  |             | 8                      |          |               |                  |
| RLA(=MCC/1.56;use for breaker & wire size selection):   |             | 7.2                    |          |               |                  |
| *Low and High refer to the low and high nominal voltage ranges for which the motor is approved. |             |                        |          |               |                  |
| Type  | Part No     | Low MFD                | High MFD | Volts         | User Description |
| Start Capacitor   | 014-0061-29 | 108.0                  | 130.0    | 330           |                  |
| Run Capacitor   | 014-0064-11 | 25.0                   | 0.0      | 440           |                  |

## Alternate Applications

| Refrigerant | Freq (Hz) | Phase | Voltage | Application |
|-------------|-----------|-------|---------|-------------|
| R-12 CFC    | 60        | 1     | 208/230 |             |