

July 2010

Your monthly newsletter from Maxitrol
Tel: 248.356.1400 Fax: 248.356.0829

THE 325-7AL IS NOW AVAILABLE!!

A Line Pressure Regulator Rated for Over 1 Million Btu/hr is Now Available.

The new 325-7AL is a line pressure regulator that offers a capacity of 1.25 million Btu/hr. This is the highest capacity 325 regulator Maxitrol has ever produced. The new 325-7AL regulator can be used in a wider range of applications and is available with a new vent limiting device. Maxitrol also offers Imblue Technology™ for the 325-7AL.

Note: With the implementation of ANSI Z21.80/CSA 6.22, appliance regulators can no longer be used as line regulators.



325-7AL

Specifications for the 325-7A(B)L:

Gases:

Suitable for natural, manufactured, mixed gases, liquefied petroleum gases and LP gas-air mixture piping systems.

Approvals:

ANSI Z21.80/CSA 6.22

Maximum Inlet Pressure:

CSA Certified..... 2 psi (140 mbar)

Minimum Inlet Pressure:

CSA Certified..... 1 psi (70 mbar)

Emergency Exposure Limits:

Inlet side only..... 65 psi (4.5 bar)

Outlet Pressure Range:

Certified Spring..... 7 - 11" w.c.

Maximum Individual Load: Largest single appliance served by the regulator..... 1,250,000 Btu/hr

Capacity:

Total load of multiple appliances combined.....1,250,000 Btu/hr

Vent Pipe Connection:..... 1/2" NPT

Ambient Temperature Limits:

.....-40°F to 205°F (-40°C to 96°C)

BREAKTHROUGH!!

vLimiter™ now available for the FIRST time on the 325-7 series!!

NEW!



vLimiter™
12A49

Having to run vent piping for a line pressure regulator can be an expensive and time consuming job. The Maxitrol vent limiting device is the perfect solution. The vLimiter eliminates the need to run vent piping to the outside by limiting gas escapement to within

ANSI standard requirements in the event of a diaphragm rupture. This will save you time and money!! Maxitrol's vLimiter 12A49 is tested and approved to ANSI Z21.80/CSA 6.22 for use with the 325-7AL.

Imblue Technology™ increases corrosion resistance and provides extra protection against the elements for regulators used in outdoor applications. When ordering be sure to specify Imblue Technology by including the suffix "B" in the part number.



325-7ABL

For more information on the 325-7AL or other Maxitrol products contact a Maxitrol Regional Salesman.
Tom Ganfield (East of the Mississippi) 248-894-0481
or **Rob Peters** (West of the Mississippi) 248-761-1708

If you would prefer to receive Maxitrol's monthly newsletter as an email, please send your email address to kholbrook@maxitrol.com with the word "Subscribe" in the subject line. This is for Maxitrol's use only, and will not be used for any other purpose. You can request to remove yourself from the email list at any time.