

FBAH-B100-CAV-020

CFC, R-12, 60Hz, 1- Phase, 208/230 V



Availability : **Obsolete**

Mechanical

Unit Height (in):	13.1
Unit Length (in):	24.0
Unit Width (in):	16.9
Ship Weight (lbs):	89.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 F
Suction Connection Size (in)/Type:	5/8 F
Discharge Line Size(in):	
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	MIN
Oil Recharge Amount (oz):	24

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	11.5
Compressor:	RR10K2-CAV-101
Compressor LRA - Low:	
Compressor LRA - High:	40.0
Compressor LRA - Half winding:	
Compressor RLA:	8.3
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	0.85
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	24-Sep-2002	Return Gas Temp. (°F):	65
Compressor:	RR10K2-CAV-101 x 1	Subcooling (°F):	5
Performance No:	5687	Air Flow Rate (CFM)	650

90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
45	10,400	129.6	39.6	6.9