

MBFS-A033-IAA-272

CFC, R-12, 60Hz, 1- Phase, 115 V



Availability : Standard US Wholesaler

Mechanical

Unit Height (in):	11.4
Unit Length (in):	14.4
Unit Width (in):	12.9
Ship Weight (lbs):	53.0
Condensor Type:	Air
Copevap Water Storage:	NA
Liquid Connection Size (in)/Type:	1/4 S
Suction Connection Size (in)/Type:	3/8 S
Discharge Line Size (in):	0.25
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	ABO
Oil Recharge Amount (oz):	12

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	9.5
Compressor:	ARE40C4-IAA-199
Compressor LRA - Low:	
Compressor LRA - High:	37.0
Compressor LRA - Half winding:	
Compressor RLA:	7.0
UL:	Recognized
UL File #:	SA633
UL Guide Card:	LZFE2
UL Fan Motor FLA Rating Per Motor:	0.36
Fan Motor Quantity:	1

Air Cooled Unit Performance

Release Date:	23-May-2012	Return Gas Temp. (°F):	65
Compressor:	ARE40C4-IAA-199 x 1	Subcooling (°F):	5
Performance No:	8328	Air Flow Rate (CFM)	220

90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
0	1,490	114.5	24.5	3.6
5	1,670	117.3	27.3	3.8
10	1,860	120.1	30.1	4.0
15	2,050	123.0	33.0	4.2
20	2,260	125.9	35.9	4.3
25	2,470	128.9	38.9	4.5
30	2,690	131.9	41.9	4.6
35	2,920	135.1	45.1	4.8
40	3,160	138.4	48.4	4.9