

# 3DS3R17ME-TFD

HFC , R-407A, 60Hz, 3- Phase, 460 V

Air Conditioning



**Production Status:** Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

## Performance

Evap(°F)/Cond(°F)	<u>45 / 130</u>	<u>35 / 105</u>
RG(°F)/Liq(°F)	<u>65 / 115</u>	<u>55 / 90</u>
Capacity (Btu/hr)	192000	189500
Power (Watts):	17900	13800
Current (Amps):	26.75	21.60
EER (Btu/Wh):	10.70	13.70
Mass Flow (lbs/hr):	3050	2650
Sound Power (dBA):	0 Avg	0 Max
Vibration (mils(peak-))	0.0 Avg	0.0 Max
Record Date:	2010-11-23	

## Mechanical

Number of Cylinders:	3	Displ(in <sup>3</sup> /Rev):	35.01
Bore Size(in):	2.44	Displ(ft <sup>3</sup> /hr):	2127.41
Stroke(in):	2.50		
Overall Length (in):	28.03	Mounting Length (in):	15.00
Overall Width (in):	15.06	Mounting Width (in):	12.00
Overall Height (in):	18.03	Mounting Height (in):	19.06 *
Suction Size (in):	1 5/8 Sweat		
Discharge Size (in):	1 1/8 Sweat		
Oil Recharge (oz):	115		
Initial Oil Charge (oz):	125		
Net Weight (lbs):	385		
Internal Free Volume (in <sup>3</sup> ):			
Horse Power:	15		
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

## Electrical

LRA-High*:	138.0	MCC (Amps):	40.6	UL File No:	SA-2337
LRA-Half Winding:		RPM:	0	UL File Date:	26-Jul-1985
LRA Low*:		Max Operating Current:			
RLA(=MCC/1.4;use for contactor selection):			29		
RLA(=MCC/1.56;use for breaker & wire size)			26		
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

## Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-22 HCFC	60	3	460	Air Conditioning
R-22 HCFC	60	3	460	Medium Temp, Low Condensing
R-404A HFC	60	3	460	Medium Temp, Low Condensing
R-407A HFC	60	3	460	Medium Temp, Low Condensing
R-407A HFC	60	3	460	Medium Temp, Low Condensing
R-407C HFC	60	3	460	Air Conditioning
R-407C HFC	60	3	460	Medium Temp, Low Condensing
R-407C HFC	60	3	460	Medium Temp, Low Condensing
R-502 CFC	60	3	460	Medium Temp, Low Condensing
R-507 HFC	60	3	460	Medium Temp, Low Condensing
R-22 HCFC	50	3	380/420	Air Conditioning

## Alternate Applications

<u>Refrigerant</u>	<u>Freq (Hz)</u>	<u>Phase</u>	<u>Voltage</u>	<u>Application</u>
R-22 HCFC	50	3	380/420	Medium Temp, Low Condensing
R-404A HFC	50	3	380/420	Medium Temp, Low Condensing
R-407A HFC	50	3	380/420	
R-407A HFC	50	3	380/420	
R-407C HFC	50	3	380/420	
R-407C HFC	50	3	380/420	
R-502 CFC	50	3	380/420	
R-507 HFC	50	3	380/420	Medium Temp, Low Condensing