



SIMPLE GREEN CLEANER DEGREASER

Concentrated, nontoxic, biodegradable and F.D.A. approved for use in the food service industry.

SIMPLE GREEN

PART NO.	DESCRIPTION	PACKAGING
13012	24 Oz. with trigger spray head	12/Case

CRYSTAL SIMPLE GREEN

PART NO.	DESCRIPTION	PACKAGING
19024	24 Oz. with trigger spray head	12/Case
19128	1 Gallon container	6/Case



AT5 ACID TEST KIT

Only one drop of oil from any refrigeration or air conditioning system is required to test for damaging acid which can cause...

- Clogged cap tubes
- Defective fan motors
- Dirty condensers
- Defective run capacitors
- Low voltage
- Cycling of overloads
- Open start capacitors
- Defective start relays

FEATURES

- Kit contains 5 acid test pads and solution for 20 tests
- Inexpensive — average cost per test is about \$1
- Easy to use — Supco's "Bullet[®]" method allows for removal of some oil from sealed systems

It takes only one minute to test. The gas does not have to be evacuated from the compressor. **Order No. AT5**



APOXI REPAIR KIT

REPAIRS ALUMINUM EVAPORATORS

CURES IN 12 HOURS. Ideal for repairing leaks in aluminum evaporators, copper to aluminum joints and all other metals. APOXI will also eliminate electrolytic action between dissimilar metals. Tested with R12, R22, and R 502 with 1500 PSIG.

Each kit contains 2 tubes of APOXI, vial of methyl ethyl keytone, mixing sticks, and emery cloth.

Order No. APOXI



S8, S16 SUPCO "88" OIL ADDITIVE

Supco 88, first introduced in 1954, is the only oil additive that has been used world wide, in all refrigeration systems that use mineral, alkylbenzene and polyolester oil in their compressors. Supco 88 dissolves sludge build up on bearing and valve surfaces and keeps them clean and bright. Supco 88 virtually prevents high speed compressors from binding. It's superior lubricity is a "must use" in preventative maintenance programs. Use Supco 88 on all bearing surfaces that are binding because of a gummy substance and prevent future build up. Compatible with all refrigeration oils.

EXPANSION VALVES AND CAPILLARIES

One part of Supco 88 to 9 parts of refrigeration oil in a system will prevent excess wear on expansion valve needles and seats. Supco 88 penetrates the pores of ALL moving metal parts of the expansion valve and keeps them constantly lubricated, preventing and correcting erratic action.

MOTORS... IN BLOWERS, AIR CONDITIONERS OR ANY H.P.

ELECTRIC MOTOR

A few drops of Supco 88 will almost instantly FREE a "frozen" or sticking shaft. It is the "perfect" bearing lubricant when mixed nine to one for regular motor bearing maintenance. This mixture, when used on motors running in high humid conditions decreases "bearing to shaft" friction and prevents sludge accumulation and build up.

HIGH SPEED COMPRESSORS... HERMETICS, SEMI-HERMETIC, BELT DRIVEN AND AUTOMOTIVE

Supco 88 vastly increases the lubricating capability of mineral oils used in high speed compressors. Current draw is reduced when Supco 88 is used in new units by reducing friction and preventing overloading. Supco 88 can be left in the system permanently.

PART NO.	BOTTLE SIZE	PACKAGING
S8	8 OZ.	24/CTN
S16	16 OZ.	15/CTN



84104 STARBRITE LIQUID ELECTRICAL TAPE

A TERRIFIC TIME SAVER!

Reinsulates cracked and frayed conductor insulation without disconnecting the wire.

PART NO.	OZ.	QUANTITY
84104	4 OZ.	1/CTN



KA12



SFL8

SFL8 SPOT-IT LEAK DETECTOR

When SPOT-IT locates even the smallest leak it produces an extra large fluorescent bubble. SPOT-IT works equally well on all pressurized systems including air, CO₂, nitrogen, natural gas, etc. Pin holes and joint leaks are detected fast. SPOT-IT surpasses all old style soap solution capabilities.

SPOT-IT does not stain, is harmless to skin and is easily rinsed off when spilled. SPOT-IT acts as a corrosion resistant agent when left to dry on metal parts.

PART NO.	BOTTLE SIZE	PACKAGING
SFL8	8 OZ.	24/Case

KA12 & KA36 KLEEN-AIR ODOR ABSORBER

By simply opening the lift spout, one 8 ounce bottle of KLEEN-AIR will absorb and remove all kinds of odors for ONE FULL YEAR, in a standard size 9' x 12' room.

PART NO.	BOTTLE SIZE	PACKAGING
KA12	8 OZ.	12/Case
KA36	8 OZ.	36/Case*

*KA36 case is a counter display 13" x 13" x 15"



MO98 SURE REACH OILER WITH PULLOUT SPOUT

SUPER TURBINE OIL is a paraffin base, nongumming, high quality lubricating oil that withstands high temperatures without breaking down. This multipurpose oil lubricates all types of motors, blowers, oil burner bearings, linkages, appliance pumps, etc. Use MO98 on ALL high speed shaft bearings. Operates on normal speed bearings with equal efficiency.

FEATURES

- Flexible spout extends and retracts
- Spout is easily adjusted to any in-between length
- Contains highest quality ALL PURPOSE lubricating oil
- Squeeze pressure on the container allows the oil to flow through the spout in any direction, including straight up

PART NO.	BOTTLE SIZE	PACKAGING
MO98	4 OZ.	12/Case

Furnished in an attractive countertop display box.



MO44 RUST CUTTER SOLVENT WITH PULLOUT SPOUT

FEATURES

- Telescoping Spout Applicator
- Loosens rust in seconds
- No lingering odor!

PART NO.	SIZE	QUANTITY
MO44	4 OZ.	12/Case

Furnished in an attractive countertop display box.