

XJAL-030Z-TFC-022

HFC, R-404A, 60Hz, 3- Phase, 208/230 V



Availability : Standard US Wholesaler

Mechanical

Unit Height (in):	
Unit Length (in):	
Unit Width (in):	
Ship Weight (lbs):	271.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	null null
Suction Connection Size (in)/Type:	null null
Discharge Line Size(in):	
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	3MA
Oil Recharge Amount (oz):	25

Electrical

Max Fuse Size:	25
Min Circuit Ampacity:	15.4
Compressor:	ZXI09KCE-TF5-687
Compressor LRA - Low:	
Compressor LRA - High:	73.0
Compressor LRA - Half winding:	
Compressor RLA:	12.9
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	10-Jun-2009	Return Gas Temp. (°F):	65
Compressor:	ZXI09KCE-TF5-687 x 1	Subcooling (°F):	0
Performance No:	7912	Air Flow Rate (CFM)	2050

90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-15	15,620	104.5	14.5	5.7
-10	17,170	105.8	15.8	6.1
-5	18,730	107.1	17.1	5.4
0	20,280	108.4	18.4	6.7
-20	14,060	103.2	13.2	5.3
-40	7,840	98.0	8.0	3.4
-35	9,390	99.3	9.3	4.0
-30	10,950	100.6	10.6	4.4
-25	12,500	101.9	11.9	4.9