

MRF2-050A-TFC

CFC, R-12, 60Hz, 3- Phase, 208/230 V
High Temp



Production Status: This compressor and/or application of this compressor is not available to U.S. OEM customers. A field replacement is currently available through a U.S. Emerson Climate Technologies Wholesaler. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	45 / 130	20 / 120
RG(°F)/Liq(°F)	65.0 / 130.0	65.0 / 120.0
Capacity (Btu/hr)	48900	30100
Power (Watts):	5650	4390
Current (Amps):	17.20	12.90
EER (Btu/Wh):	8.70	6.90
Mass Flow (lbs/hr):	1050	600
Sound Power (dBA):	0 Avg	0 Max
Vibration (mils(peak-peak)):	0.0 Avg	0.0 Max
Record Date:	2006-10-16	

Mechanical

Number of Cylinders:	2	Displ(in ³ /Rev):	17.80
Bore Size(in):	2.50	Displ(ft ³ /hr):	1081.51
Stroke(in):	1.81		
Overall Length (in):	22.44	Mounting Length (in):	11.63
Overall Width (in):	13.00	Mounting Width (in):	11.00
Overall Height (in):	16.94	Mounting Height (in):	18.00 *
Suction Size (in):	1 3/8 Sweat		
Discharge Size (in):	7/8 Sweat		
Oil Recharge (oz):	70		
Initial Oil Charge (oz):	80		
Net Weight (lbs):	261		
Internal Free Volume (in ³):			
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	115.0	MCC (Amps):	28.0	UL File No:	
LRA-Half Winding:		RPM:	3500	UL File Date:	26-Apr-1972
LRA Low*:		Max Operating Current:			
RLA(=MCC/1.4;use for contactor selection):		20			
RLA(=MCC/1.56;use for breaker & wire size selection):		17.9			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-22 HCFC	50	3	200/220	
R-502 CFC	50	3	200/220	
R-12 CFC	60	3	208/230	
R-22 HCFC	60	3	208/230	
R-12 CFC	50	3	200/220	UL Medium Temp
R-12 CFC	50	3	200/220	UL High Temp
R-502 CFC	60	3	208/230	UL Medium Temp