

ZRT144KCE-TF5**Tandem**

HCFC, R-22, 60Hz, 3- Phase, 200/230 V

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	45 / 130	45 / 100
RG(°F)/Liq(°F)	65.0 / 115.0	65.0 / 85.0
Capacity (Btu/hr)	144000	169000
Power (Watts):	12600	9100
Current (Amps):	36.60	28.30
EER (Btu/Wh):	11.40	18.60
Mass Flow (lbs/hr):	2110	2170
Sound Power (dBA):	75 Avg	80 Max
Vibration (mils(peak-peak)):	2.0 Avg	3.0 Max
Record Date:	2014-03-06	

Mechanical

Number of Cylinders:	0	Displ(in ³ /Rev):	11.97
Bore Size(in):	0.00	Displ(ft ³ /hr):	1454.20
Stroke(in):	0.00		
Overall Length (in):	24.65	Mounting Length (in):	21.50
Overall Width (in):	11.69	Mounting Width (in):	7.50
Overall Height (in):	18.80	Mounting Height (in):	19.13 *
Suction Size (in):	1 1/8 Stub		
Discharge Size (in):	3/4 Stub		
Oil Recharge (oz):	106		
Initial Oil Charge (oz):	114		
Net Weight (lbs):	205		
Internal Free Volume (in ³):	496.0		
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	MCC (Amps):	0.0	UL File No:	SA-2337
LRA-Half Winding:	RPM:	3500	UL File Date:	26-Jul-1993
LRA Low*:	Max Operating Current:			
RLA(=MCC/1.4;use for contactor selection):				
RLA(=MCC/1.56;use for breaker & wire size selection):				
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.				

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-134a HFC	50	3	200/220	A/C, Half of Even Tandem
R-22 HCFC	50	3	200/220	A/C, Half of Even Tandem
R-407C HFC	50	3	200/220	Air Conditioning
R-134a HFC	60	3	200/230	A/C, Half of Even Tandem
R-407C HFC	60	3	200/230	A/C, Half of Even Tandem
R-134a HFC	50	3	200/220	Air Conditioning
R-22 HCFC	50	3	200/220	Air Conditioning
R-407C HFC	50	3	200/220	A/C, Half of Even Tandem
R-134a HFC	60	3	200/230	Air Conditioning
R-22 HCFC	60	3	200/230	A/C, Half of Even Tandem

Alternate Applications

<u>Refrigerant</u>	<u>Freq (Hz)</u>	<u>Phase</u>	<u>Voltage</u>	<u>Application</u>
R-407C HFC	60	3	200/230	Air Conditioning