

# M4FH-0050-CAV-272

HFC, R-404A, 60Hz, 1- Phase, 208/230 V



**Availability :** Standard US Wholesaler

## Mechanical

Unit Height (in):	11.7
Unit Length (in):	16.2
Unit Width (in):	13.1
Ship Weight (lbs):	53.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	1/4 S
Suction Connection Size (in)/Type:	3/8 S
Discharge Line Size(in):	0.250
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	12

## Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	6.7
Compressor:	ASE32C3E-CAV-103
Compressor LRA - Low:	
Compressor LRA - High:	24.8
Compressor LRA - Half winding:	
Compressor RLA:	4.9
UL:	Recognized
UL File #:	SA633
UL Guide Card:	LZFE2
Amps Per Motor:	0.27
Fan Motor Quantity:	1

## Air - Cooled Unit Performance

Release Date:	05-Feb-2001	Return Gas Temp. (°F):	65
Compressor:	ASE32C3E-CAV-103 x 1	Subcooling (°F):	5
Performance No:	3369	Air Flow Rate (CFM)	300

### 90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
0	2,680	105.7	15.7	5.4
5	2,990	107.6	17.6	5.1
10	3,320	109.8	19.8	5.2
15	3,660	112.1	22.1	5.2
20	4,010	114.5	24.5	5.5
25	4,380	117.1	27.1	5.6
30	4,770	119.7	29.7	5.8
35	5,180	122.3	32.3	6.0
40	5,600	125.0	35.0	6.2
45	6,040	127.7	37.7	6.2