

CR30K6E-PFV

HFC, R-407C, 50Hz, 1- Phase, 200 V

Air Conditioning



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

| | | |
|------------------------------|--------------|-------------|
| Evap(°F)/Cond(°F) | 45 / 130 | 45 / 100 |
| RG(°F)/Liq(°F) | 65.0 / 115.0 | 65.0 / 85.0 |
| Capacity (Btu/hr) | 22800 | 30100 |
| Power (Watts): | 2130 | 1670 |
| Current (Amps): | 11.60 | 9.30 |
| EER (Btu/Wh): | 10.70 | 18.00 |
| Mass Flow (lbs/hr): | 331 | 374 |
| Sound Power (dBA): | 0 Avg | 0 Max |
| Vibration (mils(peak-peak)): | 4.4 Avg | 5.4 Max |
| Record Date: | 2010-04-19 | |

Mechanical

| | | | |
|---|-------|------------------------------|---------|
| Number of Cylinders: | 2 | Displ(in ³ /Rev): | 3.14 |
| Bore Size(in): | 1.66 | Displ(ft ³ /hr): | 316.20 |
| Stroke(in): | 0.73 | | |
| Overall Length (in): | 10.23 | Mounting Length (in): | 7.50 |
| Overall Width (in): | 9.65 | Mounting Width (in): | 7.50 |
| Overall Height (in): | 13.81 | Mounting Height (in): | 14.19 * |
| Suction Size (in): | | 3/4 Stub | |
| Discharge Size (in): | | 1/2 Stub | |
| Oil Recharge (oz): | | 43 | |
| Initial Oil Charge (oz): | | 45 | |
| Net Weight (lbs): | | 66 | |
| Internal Free Volume (in ³): | | | |
| Horse Power: | | | |
| *Overall compressor height on Copeland Brand Product's specified mounting grommets. | | | |

Electrical

| | | | | | |
|---|-------------|------------------------|----------|---------------|------------------|
| LRA-High*: | 82.0 | MCC (Amps): | 22.4 | UL File No: | |
| LRA-Half Winding: | | RPM: | 2900 | UL File Date: | 28-Dec-1984 |
| LRA Low*: | | Max Operating Current: | | | |
| RLA(=MCC/1.4;use for contactor selection): | | 16 | | | |
| RLA(=MCC/1.56;use for breaker & wire size selection): | | 14.4 | | | |
| *Low and High refer to the low and high nominal voltage ranges for which the motor is approved. | | | | | |
| Type | Part No | Low MFD | High MFD | Volts | User Description |
| Start Capacitor | 014-0061-16 | 43.0 | 52.0 | 330 | LOW TORQUE |
| Start Capacitor | 014-0061-28 | 145.0 | 175.0 | 250 | HIGH TORQUE |
| Run Capacitor | 014-0064-07 | 35.0 | 0.0 | 370 | |

Alternate Applications

| Refrigerant | Freq (Hz) | Phase | Voltage | Application |
|-------------|-----------|-------|---------|------------------|
| R-22 HCFC | 50 | 1 | 200 | |
| R-404A HFC | 50 | 1 | 200 | High Temp |
| R-22 HCFC | 60 | 1 | 208/230 | |
| R-407C HFC | 60 | 1 | 208/230 | Air Conditioning |