

MBAM-0075-CFV-020

CFC, R-12, 60Hz, 1- Phase, 208/230 V



Availability : Standard US Wholesaler

Mechanical

Unit Height (in):	13.1
Unit Length (in):	24.0
Unit Width (in):	17.5
Ship Weight (lbs):	75.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 S
Suction Connection Size (in)/Type:	5/8 S
Discharge Line Size(in):	0.375
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	ABO
Oil Recharge Amount (oz):	22

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	11.2
Compressor:	RRT10K1-PFV-199
Compressor LRA - Low:	
Compressor LRA - High:	46.0
Compressor LRA - Half winding:	
Compressor RLA:	8.0
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	0.85
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	23-May-2012	Return Gas Temp. (°F):	65
Compressor:	RRT10K1-PFV-199 x 1	Subcooling (°F):	5
Performance No:	8332	Air Flow Rate (CFM)	680

90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
0	4,320	112.1	22.1	5.3
5	4,900	114.5	24.5	5.6
10	5,490	117.1	27.1	5.9
15	6,100	119.8	29.8	6.2
20	6,720	122.5	32.5	6.4
25	7,360	125.2	35.2	6.6