

# ZR72KCE-TF5

HFC, R-407C, 60Hz, 3- Phase, 200/230 V

Air Conditioning



**Production Status:** Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

## Performance

Evap(°F)/Cond(°F)	45 / 130	45 / 100
RG(°F)/Liq(°F)	65.0 / 115.0	65.0 / 85.0
Capacity (Btu/hr)	72300	86800
Power (Watts):	6420	4400
Current (Amps):	18.85	14.45
EER (Btu/Wh):	11.25	19.75
Mass Flow (lbs/hr):	1045	1070
Sound Power (dBA):	75 Avg	80 Max
Vibration (mils(peak-peak)):	2.0 Avg	3.0 Max
Record Date:	2014-08-05	

## Mechanical

Number of Cylinders:	0	Displ(in <sup>3</sup> /Rev):	5.98
Bore Size(in):	0.00	Displ(ft <sup>3</sup> /hr):	727.10
Stroke(in):	0.00		
Overall Length (in):	9.69	Mounting Length (in):	7.50
Overall Width (in):	9.69	Mounting Width (in):	7.50
Overall Height (in):	17.75	Mounting Height (in):	18.00 *
Suction Size (in):		7/8 Stub	
Discharge Size (in):		1/2 Stub	
Oil Recharge (oz):		56	
Initial Oil Charge (oz):		60	
Net Weight (lbs):		85	
Internal Free Volume (in <sup>3</sup> ):		248.0	
Horse Power:		6	
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

## Electrical

LRA-High*:	156	MCC (Amps):	29.0	UL File No:	SA-2337
LRA-Half Winding:		RPM:	3500	UL File Date:	26-Jul-1993
LRA Low*:		Max Operating Current:	26.0		
RLA(=MCC/1.4;use for contactor selection):		20.7			
RLA(=MCC/1.56;use for breaker & wire size selection):		18.6			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

## Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-134a HFC	50	3	200/220	Air Conditioning
R-134a HFC	60	3	200/230	Air Conditioning
R-407C HFC	50	3	200/220	Air Conditioning
R-22 HCFC	50	3	200/220	Air Conditioning
R-22 HCFC	60	3	200/230	Air Conditioning