

DJAL-030Z-TFC-015

HFC, R-404A, 60Hz, 3- Phase, 208/230 V



Availability : Standard US Wholesaler

Mechanical

Unit Height (in):	19.0
Unit Length (in):	25.2
Unit Width (in):	34.0
Ship Weight (lbs):	239.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 S
Suction Connection Size (in)/Type:	1-1/8 S
Discharge Line Size(in):	0.500
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	64

Electrical

Max Fuse Size:	30
Min Circuit Ampacity:	21.6
Compressor:	ZF13K4E-TF5-251
Compressor LRA - Low:	
Compressor LRA - High:	99.0
Compressor LRA - Half winding:	
Compressor RLA:	15.0
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	22-Jul-2002	Return Gas Temp. (°F):	65
Compressor:	ZF13K4E-TF5-251 x 1	Subcooling (°F):	5
Performance No:	4062	Air Flow Rate (CFM)	2170

90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-5	20,900	111.8	21.8	5.2
-40	9,280	102.7	12.7	2.9
-35	10,600	103.7	13.7	3.2
-30	12,100	104.8	14.8	3.6
-25	13,600	106.0	16.0	3.9
-20	15,300	107.3	17.3	4.3
-15	17,100	108.8	18.8	4.6
-10	18,900	110.2	20.2	4.9
0	22,900	113.9	23.9	5.5