

# DJWL-C150-TAC-020

HFC, R-404A, 60Hz, 3- Phase, 208/230 V

**Availability :**      **Standard US Wholesaler**

## Mechanical

Unit Height (in):	12.9
Unit Length (in):	24.0
Unit Width (in):	17.0
Ship Weight (lbs):	152.0
Condensor Type:	Water
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 S
Suction Connection Size (in)/Type:	7/8 S
Discharge Line Size(in):	0.50
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	22

## Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	8.3
Compressor:	KWLA-016E-TAC-101
Compressor LRA - Low:	
Compressor LRA - High:	50.0
Compressor LRA -	
Compressor RLA:	6.6
Elect Application	1
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	
Fan Motor Quantity:	1.00

## Water- Cooled Unit Performance

Release Date:	09-Oct-2002	Return Gas Temp. (°F):	65
Compressor:	KWLA-016E-TAC-101 x      1	Subcooling (°F):	5
Performance No:	6011	Condenser Water Inlet Temp.(°F)	85.0
		Water Temp Diff.(°F)	10

  

105°F Condensing Temperature			
<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond Water</u> <u>(gal/min)</u>	<u>(psi)</u>
-40	3,110	1.1	0.2
-35	4,010	1.3	0.2
-30	4,900	1.5	0.3
-25	5,810	1.7	0.4
-20	6,750	2.0	0.5
-15	7,760	2.2	0.6
-10	8,870	2.4	0.8
-5	10,100	2.7	0.9
0	11,400	3.0	1.0