


Nuts



Features:


- Recommended maximum working pressure (PS): 700 psig, 48 bar
- In conformance with Refrigeration Fitting Standards SAE J513, Military Standards MS-35867 through MS35873 inclusive, MS-35919, MS-24815 and MS-16993
- Fabricated from brass forgings or drawn brass rod eliminating the possibility of seepage by porosity
- Accurately machined and fully protected against damage during shipping, handling and storage to assure tight leak-proof joints
- Smooth interior finish provides unrestricted flow and reduced pressure drop



Long Forged Nuts

Long Forged Nuts


Cat Number	Part Number	Flare A (in)	Size Tube	Hex	A (in)	B (in)	Box Qty	Wt(lb)
N4-4	A 00440	1/4	1/4	5/8	0.26	0.94	25	0.048
N4-6	A 00441	3/8	3/8	13/16	0.38	1.06	25	0.075
N4-8	A 00442	1/2	1/2	15/16	0.51	1.19	10	0.108
N4-10	A 01112	5/8	5/8	1 1/16	0.63	1.44	5	0.185
N4-12	A 04731	3/4	3/4	1 5/16	0.76	1.75	5	0.345



Flare Seal Cap

Flare Seal Caps


Cat Number	Part Number	Flare A (in)	Size Tube	Hex	A (in)	B (in)	Box Qty	Wt(lb)
N5-4	A 04544	1/4		9/16	0.34	0.56	50	0.030
N5-5	A 04758	5/16		5/8	0.38	0.56	25	0.027
N5-6	A 04545	3/8		3/4	0.44	0.69	25	0.050
N5-8	A 04546	1/2		7/8	0.55	0.81	25	0.069
N5-10	A 04560	5/8		1 1/16	0.63	0.94	10	0.137
N5-12	A 04951	3/4		1 5/16	0.75	1.09	10	0.221



Flare Seal Cap - Finger Tightening

Flare Seal Caps - Finger Tightening

Cat Number	Part Number	Flare A (in)	Size Tube	Hex	A (in)	B (in)	Box Qty	Wt(lb)
NFT5-4	A 16447	1/4			0.56	0.48	N/A	0.015
NFT5-6	A 16448	3/8			0.73	0.67	N/A	0.038



Short Forged

Short Forged Reducing Nuts

Cat Number	Part Number	Flare A (in)	Size Tube	Hex	A (in)	B (in)	Box Qty	Wt(lb)
NRS4-43	A 05132	1/4	3/16	5/8	0.19	0.59	10	0.027
NRS4-54	A 05247	5/16	1/4	11/16	0.26	0.63	10	0.055
NRS4-64	A 05140	3/8	1/4	13/16	0.26	0.69	25	0.060
NRS4-65	A 05282	3/8	5/16	13/16	0.32	0.69	10	0.027
NRS4-86	A 05141	1/2	3/8	15/16	0.38	0.81	15	0.094
NRS4-108	A 05228	5/8	1/2	1 1/16	0.51	0.94	15	0.125

Short Forged Nuts

Cat Number	Part Number	Flare A (in)	Size Tube	Hex	A (in)	B (in)	Box Qty	Wt(lb)
NS4-3	A 05238	3/16	3/16	1/2	0.19	0.53	50	0.024
NS4-4	A 05051	1/4	1/4	5/8	0.26	0.59	50	0.035
NS4-5	A 05239	5/16	5/16	11/16	0.32	0.63	25	0.040
NS4-6	A 05052	3/8	3/8	13/16	0.38	0.69	25	0.052
NS4-8	A 05053	1/2	1/2	15/16	0.51	0.81	15	0.084
NS4-10	A 05157	5/8	5/8	1 1/16	0.63	0.94	10	0.120
NS4-12	A 05222	3/4	3/4	1 5/16	0.76	1.13	10	0.235