

# 4DA3R12ME-TSK

CFC, R-502, 60Hz, 3- Phase, 460 V

Low Temperature



**Production Status:** This model is obsolete and is no longer in production for both OEM and service replacement. Please contact Customer Service about possible replacement models.

## Performance

Evap(°F)/Cond(°F)	-25 / 105	-40 / 105
RG(°F)/Liq(°F)	65.0 / 105.0	65.0 / 105.0
Capacity (Btu/hr)	48000	29100
Power (Watts):	8700	6550
Current (Amps):	14.25	11.95
EER (Btu/Wh):	5.50	4.50
Mass Flow (lbs/hr):	950	565
Sound Power (dBA):		
Vibration (mils(peak-peak)):		2.33 Max
Record Date:	2007-08-01	

## Mechanical

Number of Cylinders:	4	Displ(in <sup>3</sup> /Rev):	39.27
Bore Size(in):	2.50	Displ(ft <sup>3</sup> /hr):	2386.12
Stroke(in):	2.00		
Overall Length (in):	25.47	Mounting Length (in):	15.00
Overall Width (in):	21.25	Mounting Width (in):	12.00
Overall Height (in):	17.50	Mounting Height (in):	19.25 *
Suction Size (in):		1 5/8 Sweat	
Discharge Size (in):		1 1/8 Sweat	
Oil Recharge (oz):		125	
Initial Oil Charge (oz):		135	
Net Weight (lbs):		461	
Internal Free Volume (in <sup>3</sup> ):			
Horse Power:		8	
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

## Electrical

LRA-High*:	120.0	MCC (Amps):	29.4	UL File No:	SA-2337
LRA-Half Winding:		RPM:	3500	UL File Date:	07-Apr-1971
LRA Low*:		Max Operating Current:			
RLA(=MCC/1.4;use for contactor selection):		21			
RLA(=MCC/1.56;use for breaker & wire size selection):		18.8			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

## Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-22 HCFC	50	3	200	
R-502 CFC	50	3	200	
R-134a HFC	50	3	200	
R-134a HFC	50	3	200	
R-407C HFC	50	3	200	Low Temp, Low Condensing
R-407A HFC	50	3	200	Low Temp, Low Condensing
R-407F HFC	50	3	200	Low Temp, Low Condensing
R-22 HCFC	60	3	460	
R-134a HFC	60	3	460	High Temp
R-134a HFC	60	3	460	

## Alternate Applications

<u>Refrigerant</u>	<u>Freq (Hz)</u>	<u>Phase</u>	<u>Voltage</u>	<u>Application</u>
R-407C HFC	60	3	460	Low Temp, Low Condensing
R-407A HFC	60	3	460	Low Temp, Low Condensing
R-407F HFC	60	3	460	Low Temp, Low Condensing
R-22 HCFC	60	3	208/230	
R-502 CFC	60	3	208/230	Low Temperature
R-134a HFC	60	3	208/230	High Temp
R-134a HFC	60	3	208/230	
R-407C HFC	60	3	208/230	Low Temp, Low Condensing
R-407A HFC	60	3	208/230	Low Temp, Low Condensing
R-407F HFC	60	3	208/230	Low Temp, Low Condensing
R-22 HCFC	50	3	380/400	
R-502 CFC	50	3	380/400	
R-134a HFC	50	3	380/400	High Temp
R-134a HFC	50	3	380/400	
R-407C HFC	50	3	380/400	Low Temp, Low Condensing
R-407A HFC	50	3	380/400	Low Temp, Low Condensing
R-407F HFC	50	3	380/400	Low Temp, Low Condensing
R-407C HFC	60	3	208/230	Low Temperature
R-407C HFC	60	3	460	Low Temperature