

ZR38K5E-TF5

HCFC, R-22, 60Hz, 3- Phase, 200/230 V

Air Conditioning



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	45 / 130	50 / 100
RG(°F)/Liq(°F)	65.0 / 115.0	70.0 / 85.0
Capacity (Btu/hr)	38000	49400
Power (Watts):	3400	2300
Current (Amps):	10.35	8.00
EER (Btu/Wh):	11.20	21.40
Mass Flow (lbs/hr):	556	632
Sound Power (dBA):	73 Avg	78 Max
Vibration (mils(peak-peak)):	2.0 Avg	3.0 Max
Record Date:	2014-04-15	

Mechanical

Number of Cylinders:	0	Displ(in ³ /Rev):	3.11
Bore Size(in):	0.00	Displ(ft ³ /hr):	377.71
Stroke(in):	0.00		
Overall Length (in):	9.69	Mounting Length (in):	7.50
Overall Width (in):	9.69	Mounting Width (in):	7.50
Overall Height (in):	19.94	Mounting Height (in):	17.17 *
Suction Size (in):		7/8 Stub	
Discharge Size (in):		1/2 Stub	
Oil Recharge (oz):		34	
Initial Oil Charge (oz):		42	
Net Weight (lbs):		60.5	
Internal Free Volume (in ³):		226.0	
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	93.0	MCC (Amps):	19.0	UL File No:	SA-2337
LRA-Half Winding:		RPM:	3500	UL File Date:	
LRA Low*:		Max Operating Current:	14.0		
RLA(=MCC/1.4;use for contactor selection):			13.6		
RLA(=MCC/1.56;use for breaker & wire size selection):			12.2		
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-22 HCFC	50	3	200/220	Air Conditioning
R-407C HFC	50	3	200/220	Air Conditioning
R-407C HFC	60	3	200/230	Air Conditioning