

# KATB-010A-CAV

CFC, R-12, 60Hz, 1- Phase, 208/230 V

Low Temperature



**Production Status:** This model is obsolete and is no longer in production for both OEM and service replacement. Please contact Customer Service about possible replacement models.

## Performance

Evap(°F)/Cond(°F)	-25 / 105	-40 / 105
RG(°F)/Liq(°F)	65.0 / 105.0	65.0 / 105.0
Capacity (Btu/hr)	4230	2500
Power (Watts):	972	750
Current (Amps):	4.20	3.70
EER (Btu/Wh):	4.40	3.30
Mass Flow (lbs/hr):	77	45
Sound Power (dBA):		
Vibration (mils(peak-peak)):		4.76 Max
Record Date:	2006-10-16	

## Mechanical

Number of Cylinders:	2	Displ(in <sup>3</sup> /Rev):	6.38
Bore Size(in):	1.88	Displ(ft <sup>3</sup> /hr):	387.89
Stroke(in):	1.16		
Overall Length (in):	14.38	Mounting Length (in):	8.19
Overall Width (in):	8.50	Mounting Width (in):	6.38
Overall Height (in):	10.44	Mounting Height (in):	11.19 *
Suction Size (in):		5/8 Flare	
Discharge Size (in):		1/2 Flare	
Oil Recharge (oz):		20	
Initial Oil Charge (oz):		22	
Net Weight (lbs):		91	
Internal Free Volume (in <sup>3</sup> ):			
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

## Electrical

LRA-High*:	40.0	MCC (Amps):	10.1	UL File No:	
LRA-Half Winding:		RPM:	3500	UL File Date:	23-Jul-1984
LRA Low*:		Max Operating Current:			
RLA(=MCC/1.4;use for contactor selection):		7.2			
RLA(=MCC/1.56;use for breaker & wire size selection):		6.5			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					
Type	Part No	Low MFD	High MFD	Volts	User Description
Start Capacitor	014-0061-04	145.0	175.0	220	
Run Capacitor	014-0064-10	20.0	0.0	440	

## Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-12 CFC	50	1	200/220	UL Low Temp
R-502 CFC	50	1	200/220	
R-502 CFC	60	1	208/230	