

FJAM-A325-CFV-020

HFC, R-507, 60Hz, 1- Phase, 208/230 V



Availability : Standard US Wholesaler

Mechanical

Unit Height (in):	19.0
Unit Length (in):	25.2
Unit Width (in):	34.0
Ship Weight (lbs):	205.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 S
Suction Connection Size (in)/Type:	1-1/8 S
Discharge Line Size(in):	0.500
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	45

Electrical

Max Fuse Size:	40
Min Circuit Ampacity:	29.1
Compressor:	CS20K6E-PFV-256
Compressor LRA - Low:	
Compressor LRA - High:	96.0
Compressor LRA - Half winding:	
Compressor RLA:	20.0
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	31-May-2002	Return Gas Temp. (°F):	40
Compressor:	CS20K6E-PFV-256 x 1	Subcooling (°F):	5
Performance No:	3722	Air Flow Rate (CFM)	2170

90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-5	12,600	104.9	14.9	5.0
0	14,300	106.7	16.7	5.3
5	16,400	107.9	17.9	5.7
10	18,500	109.6	19.6	6.1
15	20,800	111.4	21.4	6.5
20	23,300	113.4	23.4	6.8
25	26,100	115.5	25.5	7.2