

3DA3F28KE-TFD

HFC, R-404A, 60Hz, 3- Phase, 460 V
Low Temp, Low Condensing



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	-25 / 105	-40 / 105
RG(°F)/Liq(°F)	65.0 / 105.0	65.0 / 105.0
Capacity (Btu/hr)	27800	17400
Power (Watts):	5300	4120
Current (Amps):	8.90	7.70
EER (Btu/Wh):	5.20	4.20
Mass Flow (lbs/hr):	499	307
Sound Power (dBA):	0 Avg	0 Max
Vibration (mils(peak-peak)):	0.0 Avg	0.0 Max
Record Date:	2006-10-18	

Mechanical

Number of Cylinders:	3	Displ(in ³ /Rev):	22.56
Bore Size(in):	2.19	Displ(ft ³ /hr):	1370.78
Stroke(in):	2.00		
Overall Length (in):	25.86	Mounting Length (in):	15.00
Overall Width (in):	14.92	Mounting Width (in):	12.00
Overall Height (in):	19.13	Mounting Height (in):	21.09 *
Suction Size (in):	1 3/8 Sweat		
Discharge Size (in):	1 1/8 Sweat		
Oil Recharge (oz):	115		
Initial Oil Charge (oz):	125		
Net Weight (lbs):	385		
Internal Free Volume (in ³):	5		
Horse Power:	5		
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	77.0	MCC (Amps):	16.8	UL File No:	SA-2337
LRA-Half Winding:		RPM:	3500	UL File Date:	26-Jul-1985
LRA Low*:		Max Operating Current:			
RLA(=MCC/1.4;use for contactor selection):		12			
RLA(=MCC/1.56;use for breaker & wire size selection):		10.8			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-407C HFC	60	3	460	Low Temperature
R-12 CFC	60	3	460	
R-12 CFC	60	3	460	
R-22 HCFC	60	3	460	Low Temperature
R-502 CFC	60	3	460	
R-134a HFC	60	3	460	High Temp
R-134a HFC	60	3	460	
R-507 HFC	60	3	460	Low Temp, Low Condensing
R-407C HFC	60	3	460	Low Temp, Low Condensing
R-407A HFC	60	3	460	Low Temp, Low Condensing

Alternate Applications

<u>Refrigerant</u>	<u>Freq (Hz)</u>	<u>Phase</u>	<u>Voltage</u>	<u>Application</u>
R-407F HFC	60	3	460	Low Temp, Low Condensing
R-12 CFC	50	3	380/420	
R-12 CFC	50	3	380/420	
R-22 HCFC	50	3	380/420	Low Temperature
R-502 CFC	50	3	380/420	
R-134a HFC	50	3	380/420	High Temp
R-134a HFC	50	3	380/420	
R-404A HFC	50	3	380/420	Low Temp, Low Condensing
R-507 HFC	50	3	380/420	Low Temp, Low Condensing
R-407C HFC	50	3	380/420	
R-407A HFC	50	3	380/420	Low Temp, Low Condensing
R-407F HFC	50	3	380/420	Low Temp, Low Condensing
R-407A HFC	60	3	460	Low Temperature