

CNAG-0200-TAC-001

HFC, R-134a, 60Hz, 3- Phase, 208/230 V



Availability : Standard US Wholesaler

Mechanical

Unit Height (in):	19.1
Unit Length (in):	33.4
Unit Width (in):	20.0
Ship Weight (lbs):	286.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	1/2 F
Suction Connection Size (in)/Type:	7/8 S
Discharge Line Size(in):	0.500
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	60

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	11.1
Compressor:	EAVA-021E-TAC-100
Compressor LRA - Low:	
Compressor LRA - High:	50.0
Compressor LRA - Half winding:	
Compressor RLA:	7.4
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	1.5
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	12-Sep-2002	Return Gas Temp. (°F):	65
Compressor:	EAVA-021E-TAC-100 x 1	Subcooling (°F):	5
Performance No:	5548	Air Flow Rate (CFM)	1510

90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
0	8,120	107.8	17.8	5.2
5	9,380	110.0	20.0	5.6
10	10,700	112.5	22.5	6.0
15	12,000	115.0	25.0	6.3
20	13,500	117.6	27.6	6.7
25	15,000	120.2	30.2	7.0
30	16,600	123.0	33.0	7.4
35	18,300	125.8	35.8	7.7
40	20,100	128.7	38.7	8.0
45	22,000	131.8	41.8	8.4